



Historic Preservation Commission

Regular Meeting

<http://www.townofboone.net/>

~ Agenda ~

Jane Shook
828-268-6960

Tuesday, September 10, 2019

3:00 PM Planning and Inspections Conference Room

I. Call to Order

II. Adoption of Agenda

III. Approval of Minutes

August 13, 2019 Meeting Minutes

IV. State/Local Marker & Statue for Burrell Street

Request To Honor Our Past

V. Foundation Forward, Inc.

VI. Junaluska Marker Application

VII. Historic Design Guidelines

VIII. Other Matters by Commission Members or Staff

Set Agenda

IX. Adjournment

**TOWN OF BOONE
HISTORIC PRESERVATION COMMISSION
MEETING MINUTES
AUGUST 13, 2019
3:00 PM**

Historic Preservation Commission Members in Attendance: Chairperson Eric Plaag, Vice-Chairperson Phoebe Pollitt, Bettie Bond, Teresa Pearman and Rennie Brantz

Town Staff in Attendance: Christy Turner-Senior Planner and Marlene Crosby-Board Secretary

Others Present:

Call to Order

Chairperson Eric Plaag called the meeting of the Boone Historic Preservation Commission, held in the Planning & Inspections upstairs conference room located at 680 West King Street, to order at 3:00 p.m.

Adoption of Agenda

Vice-Chairperson Pollitt made a motion, seconded by Member Bond to adopt the agenda as written.

Vote:

Aye – All

Nay – None

The motion passed.

Approval of Minutes

Member Brantz made a motion, seconded by Vice-Chairperson Pollitt to approve the July 9, 2019 meeting minutes as amended.

Vote:

Aye – All

Nay – None

The motion passed.

Foundation Forward, Inc.

Ms. Christy Turner, Senior Planner explained that Boone Town Manager, Mr. John Ward had been approached by an educational non-profit, regarding Foundation Forward, Inc. He said they are working on erecting displays of “The Declaration of Independence, The United States Constitution and The Bill of Rights in each County throughout North Carolina. He also included that they have a long list of sites that have been completed and dedicated throughout North Carolina and beyond.

Ms. Turner said that Mr. Ward had asked the Historic Preservation Commission to review this topic; to see if they are interested in discussing some ideas on where to locate such a display, if we move forward with a recommendation to the Boone Town Council.

During the meeting, Ms. Turner reviewed various websites to see the completed displays in Sylva and Morganton, North Carolina.

Discussion ensued on Foundation Forward, Inc. Chairperson Plaag noted that he would like to review the charge of the HPC to see if reviewing this type of topic fits into the charge. He noted that this would include reviewing the design to see if it is appropriate for Downtown Boone.

Chairperson Plaag noted that one location could be beside the war memorial and Town parking lot on W. King Street near Town Hall. He noted that another location would be to place it beside the Watauga County Courthouse, if the County gave permission to do so.

Ms. Turner said she would get more information on this topic and provide it at the next HPC meeting.

Junaluska Marker Application

Chairperson Plaag explained that he has not been able to work on the draft Junaluska Marker Application since the last meeting. He suggested that this agenda item be tabled to the HPC's September 2019 meeting.

Motion and Vote:

Member Brantz made a motion, seconded by Member Bond to table the draft Junaluska Marker Application agenda item to the HPC's September 2019 meeting.

Vote:

Aye – All

Nay – None

The motion passed.

Historic Design Guidelines

Chairperson Plaag began reviewing the language for proposed changes in the draft design guidelines starting on page 82 of the handbook (permanently attached), Section 6.12 through page 90, Section 9.4. It was agreed upon by the HPC members at the next meeting they would start reviewing the language on page 90, Section 10.

The following proposed changes were made to the following sections:

- | | |
|--------------|---|
| Section 6.13 | Removed wording and kept photograph and changed the Photo courtesy from Becky Haney to David Wyke Collection and Digital Watauga Project. |
| Section 6.14 | Changed this section to 6.13 |

Section 6.15	Changed this section to 6.14
Section 6.16	Changed this section to 6.15
Section 7.2	In the last sentence, changed “house” to “building”
Section 7.4	In the last sentence, put a comma after louvered and wood
Section 7.6	In the next to last sentence, change “shingles” to “materials”. In the last sentence, change “also” to “never”

Discussion ensued on the guidelines in the Unified Development Ordinance regarding paint and paint color. Ms. Turner reviewed the current guidelines of the UDO and answered questions on it. Chairperson Plaag asked Ms. Turner about how the guidelines apply to the Farmers Ski Shop building. Ms. Turner talked about the UDO section regarding non-conformities. She further explained UDO Section 7.05.02 (A) through (C2) which explains Tiers 1 and 2 and how the dollar amount of development costs triggers each tier.

Ms. Turner explained that the requirements are fundamentally neutral series of colors with a light reflective value of 59 or below and the accent colors are at 60 or above and cannot be more than five percent (5%) of the total coverage area. She said that neutral colors must be used and the color white is not allowed.

Chairperson Plaag asked about the current regulations on painting brick. Ms. Turner said it is not allowed in the Downtown District. Ms. Turner explained that if the brick on a building is already painted, it is preferred that they remove the paint. She further explained that there have been several problems with the paint removal. She said on the Vetro Building the paint was about one-inch thick and they are having trouble removing it. She said they would need to paint it. Chairperson Plaag asked Mr. Turner, if anyone has consulted with SHPO regarding this issue. He suggested asking the paint removal person to SHPO to get more information on it before they start repainting the building. Chairperson Plaag talked about the contractor doing the work may having the experience to remove the paint and suggested asking the SHPO for a referral to an experienced contractor for this type of paint removal. (The revisions continued on the design guidelines).

Section 9.0	In the second paragraph in the third sentence put a hyphen between Depression and era.
-------------	--

In the third paragraph remove “While the Boone Historic Preservation Commission does not regulate paint colors per se” and add “The Town of Boone UDO Section 7.05.02 regulates the colors used in commercial properties throughout Boone. The application of new paint, to buildings in the Historic District must conform to this UDO section 7.05.02 unless Historic precedence or use of a non-conforming color can be demonstrated through historic images or color chronology testing”.

Section 9.2	In the first sentence remove “surface” and add “exterior materials”.
-------------	--

Section 9.3 In the second sentence, change the word “house” to “building”. Remove “Typically, trimwork-including window and door casings and surrounds, soffits, fascia, and other elements – is often painted with a contrasting or lower value hue than the weatherboard or siding, especially on Victorian-era properties. Wood shingles are usually stained a dark color and often darker than any associated wood siding”.

Other Matters by Commission Members or Staff

Chairperson Plaag suggested adding the following agenda items to the next meeting agenda: Junaluska Marker Application and the Historic Design Guidelines

There were no other topics discussed at this meeting.

Adjournment

Vice-Chairperson Pollitt made a motion, seconded by Member Bond to adjourn the meeting at 4:52 p.m.

Vote:

Aye – All

Nay – None

The motion passed.

Eric Plaag, Chairperson

Marlene Crosby, Board Secretary

Communication: August 13, 2019 Meeting Minutes (Approval of Minutes)

Town of Boone Historic Design Guidelines And Handbook

*The Town of Boone circa 1939, from the hill near the Rivers House looking northeast.
Photo courtesy of Robert Snead and the Town of Boone Cultural Resources
Department.*

Town of Boone Historic Preservation Commission

DRAFT, June 2014

Town of Boone Historic Design Guidelines and Handbook

Andy Ball, **Mayor**

Fred Hay, **Council Member**

Rennie Brantz, **Mayor Pro-Tem**

Jennifer Pena, **Council Member**

Lynne Mason, **Council Member**

Quint David, **Council Member**

Greg Young, **Town Manager**

Sam Furgiuele, **Town Attorney**

Bill Bailey, **Director of Planning and Inspections**

Christy Turner, **Planner**

Brenda Henson, **Board Secretary**

Town of Boone Historic Preservation Commission Members: Cliff Baldwin, Diane Blanks, Bettie Bond, Rennie Brantz, Bill Dixon, Jennifer Pena, Eric Plaag

Additional Contributors: Andy Ball, Trent Margrif, Jules Oroukin, Chuck Watkins, Heather Gibson, Virgil Greer, Janet Pepin, Allan Scherlen, Virginia Falck

INTRODUCTION

Historic Preservation in Boone

The Boone Town Council established the Historic Preservation Commission (hereafter referred to as the HPC or the Commission) of Boone on March 15, 2007, and on April 15, 2010, the Commission adopted their Rules of Procedure. The Commission is required to develop and adopt guidelines for altering, restoring, moving, or demolishing properties that the Commission has designated as landmarks or that are located within an area that the Commission has designated as a historic district, pursuant to the requirements dictated in North Carolina General Statute 160A-400.6 as well as the Unified Development Ordinance (hereafter referred to as "UDO") Article XXIII A.

In order to facilitate the continued conservation of historic districts and landmarks, the Commission offers advisory assistance to property owners who may wish to renovate in areas identified as historic so that they may meet the requirements of the ordinance. However, in certain circumstances preservation power is intended to prevent change when there is a superior reason to preserve, such as in the case of planned demolition. This will ensure that changes are within the spirit and character of the historic property or district. Through the Design Guidelines of the HPC, the historic character of the town of Boone can be preserved for the enjoyment of both current and future residents and visitors.

Benefits of Historic District Designation at the Local and/or National Level:

- Designation often stabilizes property values and encourages investment in older residential and commercial areas.
- Increased property values boost the local tax base and facilitate investment in much-needed city services.
- Preservation and designation encourage tourism, which further enhances local tax revenues and benefits local businesses.
- The presence of established historic districts often increases property values within those districts and in surrounding neighborhoods, making it easier for businesses to attract top candidates for open positions.
- Historic landmarks and districts provide a direct, tangible, and meaningful link to the past, particularly if they are publicly interpreted through approved signage, thus promoting a sense of identity, meaning, connection, and character within the surrounding community.
- Designation on the National Register of Historic Places, either individually or as a contributing property to an Historic District, may make a property eligible for a variety of state and federal tax credits that can reduce the rehabilitation costs for historic properties by up to 40%. (For more on these tax credit programs, visit the tax credits page at the North Carolina State Historic Preservation Office website: <http://www.hpo.ncdcr.gov/tchome.htm>.)

Historic Districts

Historic Landmarks and Historic Districts Defined:

Local governments may designate individual properties as historic landmarks and groups of properties as historic districts because of their historical, pre-historical, architectural, or cultural significance. To qualify for designation, a property or area must also show integrity of design, setting, workmanship, materials, feeling, or association. Integrity enables a property or area to convey its significance to the observer; it mainly has to do with the intactness of the property's physical features.

The Difference between Local Designation and National Register Listing:

Designation by a local governing board has no direct connection with listing in the National Register of Historic Places. The National Register is the nation's official listing of buildings, structures, objects, sites, and districts worthy of preservation for their significance in American history, architecture, archaeology, or culture. A historic property or district may qualify for both local designation and National Register listing, but these are separate processes, with different consequences.

Local Historic District Designation (Overlay District):

Local historic district designation is a type of zoning that applies to a group of contiguous properties. As with historic landmarks, owners who wish to make certain kinds of changes to properties in historic districts must first have their plans reviewed and approved by the Commission. Historic District designation would be an overlay district, meaning that the existing zoning laws in effect still apply to the district, but the additional regulations set forth by historic designation would also apply.

Purpose and Applicability of the Guidelines

These guidelines have been prepared to assist property owners, developers, architects, and designers conducting building projects within historic districts of Boone. They outline the requirements for the rehabilitation of historic buildings and the construction of compatible new designs to maintain the historic character of the community.

Decisions made about renovations to historic landmarks should remain within the regulations provided by these guidelines in order to ensure that any changes will serve to enhance the historic qualities of the Town. Through the enforcement of these provisions, rehabilitation of historic landmarks will remain consistent with the inherent historic qualities of Boone.

The basis of the guidelines may be found in the Secretary of the Interior's Standards for the Rehabilitation of Historic landmarks (see below). Basic key ideas in utilizing the Standards are to:

- Retain the historic use of the property or find a new use that will allow as many historic features as possible to be retained.
- Preserve the historic character of the property by being sensitive to its appearance and designated use over time.
- Stabilize, consolidate, and conserve existing historic materials whenever possible, rather than adding modern or reproduction materials.
- Replace a minimal amount of building features. If features of the building must be replaced, new features should match the existing historic features of the structure in design and material.
- Repair and retain significant features instead of removal and replacement.

The Design Guidelines for the HPC are also intended to reflect the design guidelines developed by the Downtown Boone Development Association (DBDA) for its Façade Incentive Grants Program, which also follow the Secretary of the Interior's Standards for the Rehabilitation of Historic Landmarks (see below). The design guidelines of the HPC are intended to:

- Encourage compatible and sensitive designs.
- Increase public awareness of the value of historic architecture.
- Help reinforce the character of historic areas in Boone and protect its overall appearance.
- Preserve the integrity of designated historic areas.
- Assist property owners and architects in making preliminary design decisions.
- Improve the quality of development.
- Explain, expand, and interpret general design criteria in the local preservation ordinance.
- Educate the public on the importance of good design and historic preservation.
- Protect the value of public and private investment.

These guidelines are NOT intended to:

- Limit growth or regulate where growth takes place. Guidelines address only the visual impact of individual work projects on the character of a local historic district.
- Control how space within most buildings is used. In most cases, these guidelines deal only with the exterior, publicly visible portions of the buildings and grounds of historic properties or properties within historic districts.¹

¹ The owner of a privately owned historic property may choose to consent to an interior review of his/her property, which is thereafter binding on all future owners of the property, provided that the designation

- Guarantee that all new construction in the town of Boone will be compatible with a historic area.

The Design Review Process

In order to assist property owners with the proposed changes to historic landmarks or properties located within local historic districts while also meeting the requirements of the ordinance, the Commission has initiated a design review process intended to insure that changes to historic properties are within the spirit and character of the historic property or district. In order to determine whether to issue a Certificate of Appropriateness for proposed work, the Commission reviews proposed changes in light of these design guidelines. While the guidelines themselves are intended to guide, rather than mandate, the ways in which changes to historic properties can and should be accomplished, the decision of the Commission in interpreting these guidelines and making a determination about the issuance of a Certificate of Appropriateness is binding upon the property owner.

All owners of any residence or commercial establishment within the Town of Boone should be aware that there may be significant legal consequences for failing to comply with these Design Guidelines, especially in contradiction to a determination of the Historic Preservation Commission. NC GS 160A-400.11 provides for remedies in such instances: "In case any building, structure, site, area, or object designated as a historic landmark or located within a historic district designated pursuant to this Part is about to be demolished whether as the result of deliberate neglect or otherwise, materially altered, remodeled, removed, or destroyed, except in compliance with the ordinance or other provisions of this Part, the city or county, the historic preservation commission, or other party aggrieved by such action may institute any appropriate action or proceedings to prevent such unlawful demolition, destruction, material alteration, remodeling, or removal, to restrain, correct or abate such violation, or to prevent any illegal act or conduct with respect to such building, structure, site, area, or object. Such remedies shall be in addition to any others authorized by this Chapter for violation of a municipal ordinance."

In addition to these consequences, the Town of Boone may set additional penalties for failing to comply with the Commission's decisions or willfully violating these Design Guidelines. Residents and business owners contemplating modifications to their property should consult the UDO for additional information.

Legal Overview of Historic Preservation Legislation

has been appropriately recorded with the local Register of Deeds. In addition, publicly owned landmarks (except North Carolina state property) are also subject to interior review. The Town of Boone is committed to protecting historically significant interior spaces to the extent permitted under NC GS 160A-400.9(b).

National Historic Preservation Act (NHPA):

The National Historic Preservation Act, passed in 1966 and amended in 2006, serves as the legal justification for the importance of preserving historic landmarks and districts in the United States. The NHPA provides guidelines for historic preservation on the national level as well as stipulates that each state should have a State Historic Preservation Office, the responsibility of which is to focus on identifying historic elements statewide. The NHPA also requires that the Federal Government assist in the acceleration and growth of federal, state, and local preservation programs.

Historic Preservation Enabling Legislation in North Carolina:

The North Carolina General Statutes (160A-400.1, et seq.) provide for communities to conserve and preserve historic districts and landmarks for the purpose of stabilizing and increasing local property values and to strengthen the overall economy of the State. The relevant statutes can be viewed here:

<http://www.ncga.state.nc.us/gascripts/statutes/StatutesTOC.pl?chapter=160A>.

The Statutes describe the method of establishing such preservation programs and their operation. The primary administrative entity that identifies and enforces a community's historic district or districts is the local Historic Preservation Commission (HPC).

The State Historic Preservation Office (SHPO):

The purpose of the North Carolina State Historic Preservation Office (NC SHPO) is to aid citizens, organizations, local governments, and state and federal agencies with the protection of significant historical landmarks and areas in North Carolina. The duties of the SHPO are as follows:

- Investigate nominations of historic sites to the National Register
- Conduct an environmental review of state and federal actions that may impact historic landmarks
- Provide technical assistance (including the administration of the Certified Local Government program)
- Grant assistance
- Education
- Training for local preservation organizations and citizens in order to increase involvement in preservation programs.

The Certified Local Government Program (CLG):

Created in 1980, this program was an amendment to the National Historic Preservation Act. The Certified Local Government Program (CLG) stipulates that each state must create a procedure that certifies local governments to participate in historic preservation

programs on the national level. The benefits of such a program include the ability for local governments to be considered for federal funding for preservation programs. Just as the requirements of each SHPO vary slightly from one another, so do the requirements of the CLG. In North Carolina, the requirements for certification are as follows:

- Each local government must be equipped with an active HPC that abides by the legal regulations for the formation of such a commission. This commission must have a paid staff member.
- Local governments must follow state or local laws when designating and protecting historic areas.
- Each local government should have a regularly maintained survey in order to keep an inventory of historic landmarks and districts that is consistent with the statewide survey.
- There must be adequate public participation in the local historic preservation program, and historic landmarks must be nominated to the National Register of Historic Places.
- Finally, local governments should adhere to the responsibilities required of them under the National Historic Preservation Act, as amended.

Façade Incentive Grant Program

The purpose of the Downtown Boone Development Association (DBDA) Façade Incentive Grant Program is to encourage property owners and lease holders in the municipal service district of Boone to improve the appearance of downtown buildings. Buildings that are thirty (30) years old or older should be renovated according to the Secretary of the Interior's Standards for Rehabilitation, reproduced below. Projects seeking funding under the Façade Incentive Grant Program must also follow the guidelines that apply to construction methods and materials for properties within the Town of Boone municipal service district and the standards of the Community Appearance Commission, available through the Town of Boone Planning and Inspections Department. A sample Façade Grant application is available from the Town of Boone Cultural Resources Department.



Some properties within Boone's historic districts have lost their integrity as historic properties because of later alterations to the building façade. The Façade Incentive Grant Program helps property owners remove non-historic components and restore facades to their historic appearance. Photo courtesy of Eric Plaag, 2013.

The Secretary of the Interior's Standards for Rehabilitation

The US Department of the Interior developed national standards for the preservation of historic buildings in 1976. These standards, often referred to as the Secretary's Standards, are widely used within the preservation profession in determining the appropriateness of proposed changes to historic buildings. For this reason, the Town of Boone Historic Preservation Commission also uses these ten standards in developing the design guidelines contained within this document and in considering proposed

changes to historic properties and properties within identified historic districts. The most recent edition of the Secretary's Standards reads as follows:

1. A property shall be used for its historic purpose or be placed in a new use that requires minimal change to the defining characteristics of the building and its site and environment.
2. The historic character of a property shall be retained and preserved. The removal of historic materials or alteration of features and spaces that characterize a property shall be avoided.
3. Each property shall be recognized as a physical record of its time, place, and use. Changes that create a false sense of historical development, such as adding conjectural features or architectural elements from other buildings, shall not be undertaken.
4. Most properties change over time; those changes that have acquired historic significance in their own right shall be retained and preserved.
5. Distinctive features, finishes, and construction techniques or examples of craftsmanship that characterize a property shall be preserved.
6. Deteriorated historic features shall be repaired rather than replaced. Where the severity of deterioration requires replacement of a distinctive feature, the new feature shall match the old in design, color, texture, and other visual qualities and, where possible, materials. Replacement of missing features shall be substantiated by documentary, physical, or pictorial evidence.
7. Chemical or physical treatments, such as sandblasting, that cause damage to historic materials shall not be used. The surface cleaning of structures, if appropriate, shall be undertaken using the gentlest means possible.
8. Significant archeological resources affected by a project shall be protected and preserved. If such resources must be disturbed, mitigation measures shall be undertaken.
9. New additions, exterior alterations, or related new construction shall not destroy historic materials that characterize the property. The new work shall be differentiated from the old and shall be compatible with the massing, size, scale, and architectural features to protect the historic integrity of the property and its environment.
10. New additions and adjacent or related new construction shall be undertaken in such a manner that if removed in the future, the essential form and integrity of the historic property and its environment would be unimpaired.

Historical Influences on Boone's Architecture

Beginnings of Boone

Since its official founding in 1875, several factors have had an impact on the growth and architectural style of Boone, North Carolina. These include location, climate, economic means and the availability of materials, and the influence of Appalachian State University.

Although named for Daniel Boone, Boone was originally a hunting ground for the Cherokee Indians and later Ben Howard, for whom Howard's Knob was named. Daniel Boone first visited the area in 1760 and stayed in Ben Howard's cabin during hunting expeditions. A statue of Daniel Boone and an accompanying commemorative plaque are placed at the location of Howard's cabin, located along Rivers Street.

The settlement that would later become Boone was originally known as Council's Store in 1800, named for a mercantile that provided dried fruit, meat, hides, butter, beeswax, and tallow by wagon from as far away as Charleston, South Carolina. The store also served as the hub for trade and communication for surrounding villages. Council's Store and the surrounding residences (then a single row of houses) were renamed Boone in 1850. At that time, the store was renovated to include the Boone Post Office, and Boone served as the seat for Watauga County, although Valle Crucis, Shulls Mills, and Beaver Dam also competed for this position. When Boone was officially chartered in 1875, the population was approximately 850.

The Railroad and Expanding Markets

Boone provided over 800 men to the Confederacy during the Civil War. The majority of the population affiliated themselves with the South, although there were some who joined the Union Army. During Reconstruction, better roads were built and markets expanded. Markets continued to grow with the construction of the Eastern Tennessee and Western North Carolina Railroad, which was completed in 1919. The railroad provided a four-hour trip from Johnson City to Boone and was nicknamed "Tweetsie" after the sound the whistle made when echoing through the mountains.



This former lumber storage building located on the former Southern States property has long been rumored to have once been part of the Tweetsie Railroad complex of buildings. In reality, it likely served as lumber storage for the Gragg & Loizeaux Lumber Company and later the Boone Furniture and Lumber Company. The HPC continues to research the origins of this building. Photo courtesy of Eric Plaag, 2013.

Appalachian State University

An additional influence on Boone's growth was Appalachian State University, which was found by brothers B. B. and D. D. Dougherty as the Watauga Academy in 1899. The Dougherty brothers founded the Academy to educate teachers in Watauga County so that overall education in the community could improve.

In 1903, the Watauga Academy became the Appalachian Training School (ATS) and was granted a charter by the North Carolina General Assembly. In 1925 the name was changed to Appalachian State Normal School and four years later to Appalachian State Teachers College when the legislature designated the school as a four-year college. It transformed into Appalachian State University in 1967 and joined the University of North Carolina system in 1972.

The Tourism Industry

In 1923, Boone was identified as the “Queen City of the Mountains,” and many Charlotte locals began building summer homes in the growing town, which boasted “city conveniences without the dust, smoke, and noise of the business district.” In the 1940s, flooding greatly affected the town, resulting in several casualties, crop and building destruction, and the washing out of several of the railroad lines. While the railroad was never reconstructed, the tourism industry continued to grow in the years after World War II. With the completion of the Tweetsie Railroad theme park in 1956, Boone became a tourist destination.



West King St., looking southeast, with Appalachian Theatre on the right, 1947. Image courtesy of The Appalachian Theatre of the High Country.

Boone did not become a major tourist center until the 1960s with the introduction of skiing. The tourism industry became, and remains, a central contributor to the town's economy. As a result, hotels and vacation homes became increasingly prevalent in the area, adding greater diversity to the architectural details of the town.



The Daniel Boone Hotel, from postcard by Color King, image by Ed Carver. Private collection.

Why Preservation Matters

With increased traffic in the area creating the necessity for growth, the struggle to maintain Boone's historic landmarks has become increasingly important. Some prominent structures have already been demolished in order to make room for newer developments. One such property, sadly, was the Daniel Boone Hotel, constructed in 1926. Originally, the hotel accommodated tourists, traveling salesmen, visiting court officials, and new faculty at the Appalachian Normal School. The hotel eventually went bankrupt as a result of the Great Depression and was auctioned in 1935. After the Depression finally ended and the hotel reopened, it became the social center of Boone, boasting a legendary Sunday feast. The hotel eventually began losing business, however, when roadside motels were constructed in Boone. The Daniel Boone Hotel permanently closed in the late 1970s.

The hotel was listed on the National Register of Historic Places in 1982, but this did not prevent its demolition by the Daniel Boone Condominium Company, who purchased the property in the early 1980s. Its destruction demonstrates that NRHP designation alone is not sufficient to protect the historically significant properties and the historic character of Boone.

Remnants of the once great hotel have been relocated to other areas of town. Two examples include the hotel's sign, which was previously located on the lawn and for a long time could be seen in the downtown Boone Drug on West King Street, and the ornamental columns that once supported the entrance to the hotel's veranda; these latter features were incorporated into the chapel in the Watauga Medical Center during construction of that facility.

While many Boone residents appreciate the salvaging and repurposing of the hotel's artifacts, the demolition of the historic hotel is a cautionary tale regarding the long-term value of historic preservation and the costs of missed opportunities. As Boone struggles to identify a location for its next government center, many regret the disappearance of the hotel, which would have been an ideal site for adaptive reuse as a home for Town government. Such a project likely would have saved millions of taxpayer dollars and provided the Town of Boone with a centralized, downtown government center that would have met many of its office needs for decades to come.



West King Street, looking southwest from intersection with Grand Boulevard. Downtown Boone retains many historic properties, although changes to some of them (many of them reversible changes) have had a negative impact on the historical integrity of the downtown historic district. Image courtesy of Eric Plaag, 2013.

The Architectural Character of Boone

A variety of architectural styles have been exhibited throughout Boone's history as a result of demographic variation within the town's population over time. Many of the remaining historic buildings in the area were constructed more for function than visual appeal. However, there were several phases in the town's history that yielded more creatively designed structures.

Unfortunately, many of the unique structures that have existed in Boone over the years have been demolished, which further emphasizes the importance of establishing historic preservation guidelines in order to protect properties that are essential to the town's history.

Through the examination of Boone's buildings, both past and present, one can understand the trends in the architecture of the town over time. As a result of renovations made to potential historic properties, Boone's modern appearance disguises the traditional character of the community. Yet these changes provide a better, more fact-based template for historic preservation. The following are descriptions of the architectural styles typically found within the town's jurisdiction (descriptions of architectural terms are located in the "Glossary of Architectural Terms" section of this document).

Queen Anne Style (late 1800s to early 1900s):

Prior to the influx in funding available to Appalachian State University as a result of the New Deal, the campus as well as the town of Boone originally contained buildings designed in reference to the Queen Anne style. While the majority of these structures were eventually torn down, a perfect example of the style is expressed in the Jones House, which remains at 567 West King Street in downtown Boone and is listed on the National Register of Historic Places.

The Queen Anne style is a particularly elaborate variation on Victorian architecture; as such, homes influenced by this style are typically referred to as "Victorian" and characterized by liberal ornamentation and a variety of planes and textures.

The dominant feature of Queen Anne homes is their rambling, asymmetrical forms. They are typically two to three stories tall and have large porches. The exterior usually consists of a variety of materials, textures, and colors that are particularly apparent on the main façade. Numerous dormers, gables, turrets, towers, and bays are often incorporated.

The roof is typically pitched, hipped, or gabled; these roof designs often are incorporated on intersecting roofs with a dominant front-facing gable. Roofs usually are accentuated by various dormers with pyramidal, conical, and, occasionally, domed roofs topping polygonal and cylindrical towers. Tall, thin, brick chimneys, sometimes with corbelling or flared at the top with large caps, are common. They can be constructed of brick and tile used in elaborate, intricate patterns.

The windows on Queen Anne houses are generally double-hung, although there are often casements in upper stories. Primary windows are usually tall and rectangular with smaller windows in dormers. Upper sashes may have decorative muntin patterns or be bordered by smaller, multi-colored panes. Sashes are often painted a contrasting dark or bright color.

Generally, Queen Anne houses are characterized by wood siding with varying textures, including imbrications (decorative shingles overlapping to create a pattern) with sawtooth, scallop, or fish scale shingles or circular siding, as well as other ornamentation.

Originally, these homes often utilized bold color combinations featuring contrasting colors for the body and trim. Several different colors were often used and coordinated to highlight the varied texture of the walls and architectural details. Typically, a medium to light shade would be used for the body with darker or brighter contrasting colors on the trim. In some cases, the opposite may be seen with a dark body color and white or off-white trim. The appropriateness of the palette is less dependent on the colors than on how they are applied.

Colonial Revival Style (1880-1955):

The completion of the railroad in 1919 provided Boone with access to materials the town was previously unable to obtain due to the difficult mountain terrain. The New Deal provided the Appalachian campus with several significant buildings in the Colonial Revival style, epitomized in Smith-Wright Hall, the three-story science building erected in 1939. A second example of the Colonial Revival style is the United States Post Office located in downtown Boone. Begun in 1938 by the Works Progress Administration, the post office is an outstanding example of the Colonial Revival style as promoted by the federal government during the New Deal era. The post office is listed on the National Register of Historic Places.

An early and important surviving example of Colonial Revival style in Boone is the old Watauga County Jail, located at 142 South Water St. and now home to a restaurant. Built in 1889, the former jail alludes to the Federal style with its long windows and hipped roof, a tribute that was not uncommon in the Colonial Revival movement, particularly during the 1890s. Indeed, were it not for its Craftsman-style porch, which was a later addition, the brick, two-story jail would be a nearly pristine example of early Colonial Revival architecture.

Colonial Revival structures usually had a simple, rectangular plan and were one and a half to two stories tall. These structures typically had medium pitch gambrel roofs with little to no overhang. Gabled and hipped roof forms were also used. Some homes constructed in the Colonial Revival style featured large brick chimneys along the sides or in the center of the roof.

Horizontal weatherboard and uniform clear shingles were common materials, although brick and stucco were also used at times. Masonry or stone were the primary materials used in the construction of the majority of the Colonial Revival structures in Boone. Colonial Revival buildings that had wood siding were most often painted white or another pale shade with a second shade for trim and black or dark shutters as contrast.



The former Watauga County Jail (1889) is an excellent example of Colonial Revival architecture in Boone and retains many original historic features. Photo courtesy of Eric Plaag, 2014.

Colonial Revival windows were usually rectangular and proportional to the building with double-hung sashes and six, eight, or more panes. Equally common were multi-pane upper sashes over single pane lower sashes, as well as Palladian windows.

Vernacular Style:

In the late nineteenth and early twentieth centuries, most of Boone's buildings, whether domestic, institutional, or commercial, were vernacular in design. These were structures created simply to meet a purpose, and while some may have displayed an awareness of a particular style, they were usually simplified variants. Boone's downtown business district, located primarily along what is now King Street, began to grow significantly during the 1920s, and very few buildings erected during this period deviated from the vernacular style.

The vernacular style is not a unique architectural style per se; rather, it describes architecture that references the popular styles of the area or time. Boone's business district tends to primarily consist of simple one- and two-story brick buildings of the

1920s, 1930s, and 1940s, some with ornamental brickwork or classic detail, and many with late twentieth century, “mountain rustic” storefronts that were much later additions.

Art Deco Style (1930s-1940s):

Art Deco was popular during the 1930s and early 1940s, although the style was rarely seen in Boone. The only example of the Art Deco style in Boone is the Appalachian Theatre, which was constructed in 1938 and is located on King Street. The theatre, as originally constructed, featured a boldly striped façade, rendered in plates of structural glass, and a projecting marquee adorned with neon and incandescent lights. The Art Deco features were removed or covered over in a series of late twentieth century renovations. Recent rehabilitation efforts herald the likely return of many of the structure’s original defining features.

Art Deco buildings were rectangular and blocky, often arranged in geometric fashion, which was broken up by curved ornamental elements. Buildings of this style were constructed with stucco, concrete, smooth-faced stone, or terra cotta. Steel and aluminum were often used along with glass blocks and decorative opaque glass.

Art Deco roofs tended to be flat and adorned with parapets, spires, or tower-like constructs to accentuate a corner or entrance. In residential buildings, chimneys were often added to enhance the design. Art Deco windows usually appeared as square or round openings and were often arranged in continuous horizontal bands of glass in order to maintain a streamlined appearance. In order to maintain the industrial, geometric feel, decorative materials were often black, white, and metallic, although the use of some pastel colors in structural glass and bold colors in neon lighting was not uncommon.

Bungalow and Craftsman Bungalow Styles (1905-1930s):

The Bungalow and Craftsman Bungalow styles were particularly popular for residential construction in the area for over twenty years. The majority of homes in Boone, particularly those of professors who relocated to the town, were constructed in the Bungalow style.

Bungalows are typically low, simple, and horizontal, with broad, low-pitched roofs featuring large overhangs, exposed ridge beams, and rafter tails or knee braces in the eaves. Stout posts that often rested on massive piers beginning at ground level and extending above the porch floor usually supported these rooflines. These porches usually had solid railings attached. A variety of natural materials, including German siding (a drop siding with a grooved bottom edge that fit over the concave top edge of the board beneath), wood shingles, stucco, and pebbledash (a coarse plaster mixed with pebbles, gravel, or shells), were commonly used in construction.



The Doris Church House on Junaluska Rd. (1930) is an excellent example of Craftsman bungalow architecture in the Boone vicinity. Photo courtesy of Eric Plaag, 2013.

Windows tended to be double-hung, often with the upper sash divided. Bungalows were usually painted in multiple earth tones, with a darker color used for the body and somewhat lighter, medium, or brighter shades for trims and details. Common color combinations included a brown, green, burgundy, or mustard yellow body with tan, yellow, green, and red accents.

Tudor Revival Style (1890-1940, especially after 1918):

Tudor Revival is a style derived from the architecture of medieval and early modern England and characterized by asymmetrical compositions and often false half-timbering along the façade. Boone's residents incorporated minimal Tudor Revival homes in the pre-World War II era, which is fully elaborated in the Holshouser House (1934) at 221 Orchard Street, a property once owned by the father of former Governor James E. Holshouser, who served from 1973-1977.

Exterior walls were usually stucco, weatherboard, or shingle, although some versions employed stone with a decorative stone trim (as in the case of the Holshouser House). The most prevalent building material was brick, frequently laid out in an elaborate pattern

on the first story with a second story of stucco or wood and false timbering in a decorative pattern.

Roofs were typically steeply gabled and clad with slate tiles, and many rooflines were punctuated with small dormers. Main gables often had a secondary side or cross gable. Gable ends were often decorated with vergeboards (ornate trim under the eaves of gables) whose decoration ranged from simple to highly carved. A few variants had gables with parapets, in the English style.

Casement windows were grouped in rows of three or more and framed in either wood or metal. Double-hung windows were less common. Windows were often divided into six or eight panes and were often arranged in either rectangular or diamond patterns.

Potential Historic Districts in Boone

The Town of Boone's HPC initially identified three potential historic districts, which are described below. Upon completion of its architectural survey of historic properties within the Town of Boone, it is likely that additional potential historic districts and individual historic properties will be identified for designation.



Map of the Town of Boone Municipal Service District showing dates of the various district properties.

Downtown Boone Historic District:

Downtown Boone has been the hub of culture and commerce for the Town since before the Town received its official charter in 1875. According to the Boone 2030 Study, "Downtown Boone has a small town flair and metropolitan spirit that includes an eclectic mix of shops, restaurants, and services. This high country downtown is full of people who are devoted to its survival and revitalization and are a passionate and enduring population."



The Frank Linney Law Office (1920s) on West King Street retains a remarkably high level of integrity for a downtown Boone property of its age and is an excellent example of authentic stone construction in the downtown area. Photo courtesy of Eric Plaag, 2013.

Due to various fires, flooding, and new construction, few of the nineteenth-century structures from Boone's early days remain in its downtown area. Indeed, no building erected prior to the American Civil War remains in this district. Instead, the vast majority of the Downtown Boone Historic District consists primarily of brick commercial and institutional properties constructed between 1910 and 1950, including the Carolina Hotel block (1920), Farmers Hardware (1922), the Watauga County Bank (1922), the Hagaman Building (1935), the old Hunt's Department Store building (1910/1930), the Daniel Boone Motor Company (ca. 1920), the Appalachian Theatre (1938), and the Rivers Printing Company/Watauga Democrat building (1933), punctuated with the occasional stone commercial or institutional building, such as the Advent Christian

Church (1920s), the Frank Linney Law Office (1920s), the former Watauga County Library (1938), and the United States Post Office (1938). In addition, a handful of frame residences from an earlier period in Boone's history also survive in the district, including the J. W. and Mattie Jones House (1908) and the Frank and Hessie Linney House (ca. 1900). Another notable building in the district is the former Watauga County Jail (1889).

Among these, several are either presently listed in the National Register of Historic Places or would likely be considered eligible for listing, including the J. W. and Mattie Jones House (NRHP-listed), the Frank and Hessie Linney House, the Watauga County Jail, the Watauga County Bank, the United States Post Office (NRHP-listed), Farmers Hardware, the Advent Christian Church, and the Frank Linney Law Office.

Because these properties, taken together, attest to and are representative of the significance of Boone's commercial development during the early twentieth century, their preservation is immensely important to maintaining a sense of cohesion and connection to Boone's historic past within the downtown area.



The Watauga County Bank building on the southwest corner of West King Street and Depot Street retains many of its principal exterior architectural features despite its transformation into a retail establishment. Photo courtesy of Eric Plaag, 2013.

Junaluska Neighborhood Historic District:

Although it is difficult to discover the specific date of Junaluska's founding, due to the scarcity of early records, Junaluska is definitely one of the oldest continuously occupied African-American communities in western North Carolina and the last remaining one in Watauga County. It has been reported that Junaluska was originally known only as "The Hill," and it wasn't until the 1970s or 1980s that the neighborhood adopted its official name. The Junaluska History Project began in 2011 in order to further understand and preserve the history of the neighborhood.

The area is comprised of an estimated 75 structures, including several historic homes and the Mennonite Brethren Church (1917), which is the only church in the Junaluska area that is still in use and the only historically African-American church in Watauga County. The church was a prominent fixture of the town, and many well-respected members of the community led the congregation, including Reverend Rhondo ("Ronda") Horton, who served as pastor from the early 1930s until 1984.

An additional historic structure in the area is the former Junaluska School, which was the segregated school for Watauga County and is now home to the Western Youth Network. An earlier school building is located diagonally across Church Street from the Mennonite Brethren Church and is currently used as rental property.

Map of the Grand Boulevard Neighborhood showing construction dates of the various properties

Grand Boulevard Historic District:

Grand Boulevard was originally named Daniel Boone Park and was Boone's first planned residential neighborhood. Original residents of the homes in this area were primarily the owners of businesses in downtown Boone, and it resembled a service community due to its proximity to downtown. Gradually, individuals associated with ASU began to recognize the value of this neighborhood and appreciated its proximity to the campus as well. The Grand Boulevard neighborhood includes a number of historic properties, including stone bungalows from the 1920s and 1930s.



The James and Virginia Holshouser House on Orchard St. is an excellent example of a well-preserved residence in the Grand Boulevard Historic District and incorporates one of the first integral garages built in Boone. Photo courtesy of Eric Plaag, 2013.

One example of a typical home constructed by a local business owner is the Joseph Davis House, located at 224 Grand Boulevard. Joseph Davis owned a clothing store on King Street and constructed his home in 1920. The house is one and a half stories tall and continues to be used for residential purposes. No significant structural changes have been made to the house since its original construction.



The house at 224 Grand Blvd. as it appeared in 1939. Detail from historic 1939 image of Boone, courtesy of Robert Snead and the Town of Boone Cultural Resources Department.

Individual Historic Properties:

In addition to the historic districts proposed above, the Boone Historic Preservation Commission has preliminarily identified a number of individual properties for designation as historic properties within town limits. The guidelines outlined for historic properties within this handbook apply equally to individually designated properties.



Not all historic properties in Boone are located within proposed historic districts. The Boone Advent Christian Church (1926) is located east of the proposed downtown historic district and adjacent to a shopping plaza. Photo courtesy of Eric Plaag, 2013.



Some of Boone's most important historic properties are hiding in plain sight beneath unfortunate modern surface treatments and additions and threatened by recent commercial development. The Watauga Handicrafts Center, a 1938 WPA project, lies in the midst of modern commercial sprawl and the expanding Appalachian State University campus. Photo courtesy of Eric Plaag, 2013.

Commission Procedures

Organization of the Town of Boone Historic Preservation Commission

The Boone Historic Preservation Commission (HPC) is responsible for helping to preserve any districts or landmarks therein that embody important elements of the Town of Boone's culture, history, architectural history, or prehistory and to promote the use and conservation of such districts or landmarks for the education, pleasure, and enrichment of the residents of the Town and the State.

Pursuant to the provisions outlined in Article III, Section 34 of the Town of Boone UDO, the Commission must consist of seven (7) members who are appointed by the Town Council, two of whom shall be Town Council members. All members must reside permanently within the planning jurisdiction of the Town of Boone or its extraterritorial planning jurisdiction, and up to two members may be residents of the Town's ETJ. HPC members shall be appointed for three (3) year terms, but members may continue to serve until their successors have been appointed.

Members of the Commission shall have demonstrated special interest, experience, or education in history, architecture, archaeology, or related fields, and to the extent persons may be found with the stated qualifications, the Town Council shall seek to appoint two persons with significant experience or knowledge in building construction, and one person with significant experience or knowledge in architecture.

Design Review Process

Certificate of Appropriateness:

In an effort to protect the integrity of Boone's Local Historic Districts, all proposed exterior changes to a building are closely monitored. Approval to change the appearance of, restore, alter, move, or demolish a building within a district or an individually listed property is contingent upon the issuance of a Certificate of Appropriateness (COA) by the Historic Preservation Commission (HPC). A COA is *required* before any exterior work can begin. The issuance of a Certificate of Appropriateness indicates that, in the opinion of the HPC, the proposed alterations, improvements, or demolition is consistent with the Town of Boone guidelines and reflects the historic character of Boone's historic districts and/or landmarks. Some landscaping, streetscaping, and archaeological projects also require a Certificate of Appropriateness.

A Certificate of Appropriateness is NOT required for routine maintenance, which includes repair or replacement where there is no change in the design, materials, or general appearance of elements of the structure or grounds. Any repair or replacement that involves a change in exterior design, materials, or general appearance is defined as an *alteration* and requires an approved COA before work can begin. In addition, properties that are subject to interior review (either publicly owned properties or those whose owners have requested a prior review of interior historic features) must also

have an approved COA before alterations affecting historically significant interior features can begin.

Individuals or businesses contemplating making exterior changes to existing buildings or landscapes within local historic districts or to individually designated properties elsewhere in Boone, or contemplating construction of new buildings or structures within a Local Historic District, should contact the Town of Boone Planning and Inspections Department in order to determine if a COA is required. Applications for a COA and copies of these Design Guidelines are also available from the Town of Boone Planning and Inspections Department.

Evaluation Criteria for Proposed Construction

The HPC's jurisdiction extends over an entire property site. Exterior changes are evaluated in terms of their impact on the property and the surrounding area. Each property site has three (3) Areas of Visual Concern (AVC), defined as follows:

1. **Primary AVC:** This AVC is the area located directly adjacent to a street right-of-way and is therefore most visible. Inappropriate changes in this area can severely alter the character of a building or site and compromise the integrity of an entire streetscape. Thus, great care must be taken to ensure appropriate site development.
2. **Secondary AVC:** This AVC includes the side elevations of structures, side yards, and additional non-façade and non-posterior exterior features and is also visible from the public right-of-way. It is therefore inappropriate to make changes to these areas that will severely alter the character of a building or site and/or compromise the integrity of an entire streetscape.
3. **Tertiary AVC:** This AVC includes aspects of the property not visible from the public right-of-way. These typically include posterior exterior elevations, features, and land area.

Types of Exterior Projects

Exterior work items are divided into three (3) categories: routine maintenance, major work, and minor work. Each category is defined in greater detail below. If you are unsure whether a proposed action requires Commission review and a COA application, please consult with the Office of Planning and Inspections.

Routine Maintenance:

Routine maintenance of any exterior architectural feature does not involve a change in material or design of a building or site, and it does not require a COA. The property owner may make changes that fall into the following categories without application to the HPC:

- Maintaining existing paint (changes to masonry are not considered routine maintenance)
- Replacement of window glass only with like kind and quality
- Caulking and weather-stripping
- Replacement of small amounts of missing or deteriorated original or existing siding, trim, roof coverings, porch flooring, steps, etc., as long as replacement materials match the original or existing materials in detail and color.

Minor Work:

Minor work items include those changes to a structure or a site that are judged not to have a significant impact on the property (consistent with HPC-established architectural guidelines). While minor work does not require a review by the Historic Preservation Commission, property owners still must submit a COA application for review of the proposed minor work by Planning and Inspections Department staff. If the Planning and Inspections Department staff find that the proposed work does not meet the limitations of Minor Work as defined by the Design Guidelines, the COA application will be forwarded to the HPC for review as Major Work.

Minor work includes:

- Removal of dead or diseased tree and shrubbery plantings, as well as replacement of tree and shrubbery plantings with plantings that are historically appropriate to the property (IMPORTANT: See section on historic landscapes in the Design Guidelines)
- Pointing of masonry
- Installation of mechanical systems, air conditioning units, vents, and related equipment in secondary and tertiary AVCs that does not involve alteration to the building
- Installation of patios and sidewalks in secondary and tertiary AVCs
- Change of roofing materials on flat or low-slope roofs not visible from the street
- Fence installation in secondary and tertiary AVCs
- Installation of skylights within tertiary AVCs
- Installation of storm windows and doors where divided mullions of storm windows and doors align with windows and doors behind
- Temporary signs as permitted under Boone's land use ordinance and/or approved historic house markers²
- Removal of synthetic siding where original siding exists underneath

² Regulations for temporary signs are outlined in the Town of Boone UDO.

- Installation of new doors, door frames, and associated door sill in tertiary AVCs when new materials are compatible with the original in terms of size, design, and material.



The recent restoration of the 1938-40 United States Post Office on West King Street in Boone is an excellent example of outstanding preservation work that preserves both form and function while also updating the building for modern uses. Photo courtesy of Eric Plaag, 2013.

Major Work:

Major work items include substantial alterations to an existing building or site such as new construction or demolition. Major work projects require both a COA application and HPC approval. Examples of major work items include:

- New construction or additions to buildings
- Reconstruction of buildings once located on the site but demolished or moved at some previous time
- Restoration or rehabilitation of an historic property to its historic appearance
- Demolition of any part of a building or structure

- Work that is likely to disrupt or damage known or discovered archaeological resources on the site³
- Work that significantly alters the terrain, landscape, or streetscape
- Moving of buildings
- Construction of parking lots (other than standard driveways)
- Replacement of architectural details when there will be a change in design or materials from the original or existing details
- Changes to rooflines
- Establishment of exterior fire exits
- Exterior modification of existing buildings for ADA compliance
- Painting or stuccoing of buildings not previously painted or stuccoed
- Installation of mechanical systems, air conditioning units, vents, and related equipment in primary AVCs that involves alteration to the building façade
- Location of satellite dishes, solar panels, and other roof attachments to the front roof façade of a building if they are not effectively screened or are visible from a public street
- Interior alteration of a privately owned property previously designated for the historical significance of its interior
- Interior alteration of a publicly owned landmark (other than NC State property)

Completing the COA Application

After obtaining a COA application from the Town of Boone, it is important that the form be filled out completely. Proposed changes must be clearly defined, described, and presented in detail with accompanying photographs, plans, site/plot plans, sketches, and historical documentation, as required on the COA application. New construction, additions, and accessory buildings always require scaled elevation drawings along with a site plan and a landscape plan. Changes to or improvements of parking areas, driveways, walks, fences, patios, and decks must be shown on a survey or measured diagram of the property. These supplementary materials are important in assessing the scope of the proposed project, will help avoid confusion, and often expedite the approval process. Requirements for the approval of a COA application are outlined in the following sections.

To be considered at the next regularly scheduled meeting of the HPC, property owners must submit applications, including all required documentation, at least thirty (30) days prior to the next regularly scheduled meeting of the HPC. A pre-application review is recommended so that Planning and Inspections staff can confirm that the application is complete and request any missing documentary material.

³ Archaeological guidelines are outlined in the section "Design Guidelines for Historic Streetscapes, Landscapes, Cemeteries, Monuments, and Other Resources" that appears later in this document.

Pre-Application Review:

A pre-application review by the HPC is encouraged for property owners contemplating projects within designated historic districts or that might affect other designated properties elsewhere in Boone. This free pre-application review can help applicants avoid delays in the COA approval process. During the pre-application review, applicants may request technical advice, design assistance, and color consultations from the Planning and Inspections Department prior to the submission of an application for a COA. Informal meetings to become familiar with the Commission's standards of appropriateness and design may be arranged by contacting the Office of Planning and Inspections.

Pre-application reviews are typically held during the Commission's regularly scheduled monthly meetings. The following information should be prepared and submitted to the Planning and Inspections Department by the applicant thirty (30) days prior to the next scheduled meeting date:

- Plot plan of site
- Preliminary drawings indicating desired changes. Provide photo simulations if available.
- Photographs of existing conditions.
- All available historical documentation regarding the property.

A separate pre-construction conference with the Office of Planning and Inspections is required prior to the issuance of a building permit for additions and new construction. Zoning permits are typically required prior to the pre-construction conference. Contact the Office of Planning and Inspections for more details on permit requirements.

Application Submission and Review:

Once the COA application has been completed, it must be submitted with all accompanying materials to the Town of Boone Planning and Inspections Department at least thirty (30) days prior to the Historic Preservation Commission's next regularly scheduled meeting so that it may be placed on the agenda. Applications not received by the Office and Planning and Inspections by 3:00pm on the 30th day prior to the next regularly scheduled meeting of the HPC will be postponed until the next scheduled meeting of the HPC. Applications lacking required documentation will be held until such time as all required documentation is received, then scheduled for the next regularly scheduled meeting of the HPC that is at least thirty (30) days in the future.

Required accompanying materials for all COA applications (both major and minor work) include the following:

- *Written Description of the Proposed Work:* Describe in detail the scope and nature of the proposed project, including exact material types, colors,

and dimensions for materials to be used (e.g., width of siding, color of window trim, type of roofing materials, etc.).

- *Design Guidelines References:* Cite the applicable sections of the Design Guidelines related to and/or reflected in the proposed project.
- *Photographs of Existing Conditions:* Provide current photographs showing the present conditions of the area where the project will be completed.
- *Site Plan/Plot Plan:* Provide scaled drawings showing the relationship of all buildings, secondary structures, driveways, sidewalks, fences, drains, lighting, and trees to the property line. Clearly identify the location of any and all proposed changes. Caliper of trees should be indicated as measured from four (4) feet above the earth's surface. (Not required for minor work, unless the proposed minor work involves modifications to landscaping, fencing, sidewalks, mechanicals, or other elements of the present "footprint" of the site.)
- *Historical Documentation:* If available, provide copies of historic photographs of the property in question, along with a list of any known previous alterations to the property (and the approximate date of those alterations). If the property is already listed on the National Register of Historic Places, include a copy of the nomination text for the property.
- *Owner Disclosure Form:* Applicants who are not the owner(s) of the property under consideration must submit an Owner Disclosure Form. Owner Disclosure Forms are available from the Office of Planning and Inspections.

IN ADDITION TO THE ABOVE DOCUMENTATION, all COA applications for major work must include the following accompanying materials:

- *Elevation Drawings:* Provide architectural drawings showing all elevations where proposed work will occur. Include scale.
- *Plan Drawings:* Provide architectural plans showing proposed work. Include scale.
- *For Projects Involving Demolition or Relocation:* Describe the structure, the reason for its demolition or relocation, the proposed reuse of the site, as well as plans for new landscaping at the site.
- *For Projects Involving Interior Alteration of a Publicly Owned Landmark or a Property Previously Designated for the Significance of Its Interior:* Include a copy of the recordation with the Watauga County Register of Deeds indicating this designation (for private properties), as well as documentation of the property's previously determined historic and/or landmark status. A site plan is not required if no exterior work is proposed for the property.

In addition to the documentation required for the COA application, the Office of Planning and Inspections may require additional documentation, including a soil survey, a steep slope study, and other reports or permit applications. Applicants should contact the Office of Planning and Inspections to determine additional permit requirements.

Applicants must attend the meeting at which their application will be considered or send a representative to appear who can speak for and legally bind the applicant. During the meeting, the application will be reviewed for compliance with all applicable ordinances and codes. Applicants, their representatives, and any adjacent property owners will be given the opportunity at the meeting to make brief comments or to ask questions. Applicants should note that additional permits may be required in order to undertake the proposed construction. Upon approval of a COA application, applicants are also required to undergo a zoning review prior to construction. In addition, copies of the COA application and accompanying materials will be retained in the archives of the Planning and Inspections Department and the Town of Boone Cultural Resources Department.

Upon receipt of the COA application, the Office of Planning and Inspections will forward the application to the HPC for review and action. Notification of the meeting date and time will be sent to the applicant and adjacent property owners by postal mail. Attendance at the meeting is required of applicants (or their legally authorized representatives) and recommended for adjacent property owners. Any resident of the community is welcome to attend the meeting or to review the application and accompanying materials in the Planning and Inspections Department office prior to the scheduled HPC meeting.

The Historic Preservation Commission must issue or deny a COA within sixty (60) days after the filing of a completed application, except when the time limit has been extended by mutual agreement between the applicant and the Commission. Once an application has been approved, a formal mailed notice and a large COA permit placard will be issued. The placard should be posted in a window or elsewhere on the property where it is visible from the street for the duration of the project.

FLOW CHART FOR THE CERTIFICATE OF APPROPRIATENESS PROCESS

Design Guidelines for Residential Properties

***Guidelines for Residential Historic Landmarks
and Residences within Historic Districts***

1. Architectural Components and Details

Exterior architectural components, including door and window casings, columns, brackets, porch railings, soffits, fascias, roof configurations, trim details, architectural flourishes, and various joinery and surface patterns, all contribute significantly to the character and integrity of historic properties and properties located within historic districts. Because many of these components are either irreplaceable or very expensive to reproduce, they should be maintained and valued in the same way that one might consider an important family heirloom or expensive antique furniture. In many cases, missing or damaged architectural details can be replaced with like items from salvage yards, antique shops, or mail order companies that specialize in replacement of historic architectural components. If such items cannot be replaced, many construction supply companies stock simulations of period architectural components that are approved by the Secretary of the Interior and the National Park Service as suitable historic replacements. In any event, before replacing any exterior architectural component, property owners should familiarize themselves with the architectural style and historic characteristics of their building to avoid introduction of inappropriate elements.

- 1.1. It is important to preserve historical architectural features of exterior walls, such as cornices, friezes, medallions, sunbursts, brackets, bays, turrets, fascias, and decorative moldings. Original architectural details should always be retained if structurally feasible.
- 1.2. It is NOT appropriate to remove rather than repair or replace in kind such features when they are deteriorated. If replacement is necessary, the new materials should match the materials being replaced in composition, design, texture, color, and other visual qualities.
- 1.3. It is NOT appropriate to cover or replace historic materials with substitute materials, such as aluminum, vinyl, hard board siding, or plywood panels. Architectural details that are not appropriate to the historic context and character of a building should never be added. At the same time, property owners should never use details from an earlier period to try to make a building look older than it is.



The Edward F. Lovill House on Old Bristol Road retains many original architectural features, although recent updates have removed some original elements and grafted other architectural components (such as the Craftsman-style porch posts) into the mix that do not fit with the original architectural character of the house. Photo courtesy of Eric Plaag, 2013.

2. Foundations

For most property owners, the foundation of their historic property will consist of either piers of masonry or a complete masonry wall on the perimeter of the structure as well as interior piers for support and a sill plate connecting the perimeter wall with the rest of the house. In some cases, masonry walls have been added between original masonry piers on the perimeter of the foundation.

Settling—sometimes of an inch or more—is quite common and should be expected in a historic property, often in an uneven or disproportionate manner along the entirety of the foundation. Settling also typically cracks mortar joints. For this reason, it is part of routine maintenance to periodically repoint mortar joints and inspect for more severe settling problems. In some cases, property owners will need to consult with a masonry contractor or civil engineer to correct serious settling problems. A number of less expensive and fairly common repair tricks are inappropriate for historic properties and can actually cause further damage to the historic fabric and integrity of the property.

- 2.1. Whenever a foundation requires repairs, always use the original bricks or stones if possible. If these materials are damaged beyond repair, replace them with bricks or stones similar in size, color, and surface texture to the originals. If using recycled bricks, always put the weathered side to the exterior in order to maintain the historic appearance of the foundation walls and/or piers.
- 2.2. In repairing or reconstructing a foundation, the historic bond patterns and mortar treatments should always be replicated. Brick header rows, bandboards, and other horizontal design elements should match and align with the existing historic elements.
- 2.3. Sandblasting, painting, waterproofing, and parging—a technique of applying a cement-like coating to a deteriorating foundation in order to avoid repairs—should never be employed on the exposed portions of foundation exteriors, as all of these treatments damage original masonry and mortar treatments. In addition, non-porous applications trap moisture that can freeze, cause further damage to masonry, and result in damage to the interior of the home.
- 2.4. Exposed concrete block and framed concrete are strongly discouraged, unless these components are already part of the historic context of the property in question.
- 2.5. If closing in the openings between brick piers, use matching masonry materials or lattice that is slightly recessed from the façade plain of the historic masonry. Note that foundations need to be vented. Vents should be painted a color that blends with the existing foundation color.
- 2.6. Access doors to basements or foundation crawlspaces should always be located in an area not visible from the street unless a different historic configuration that aligns with the building's historic context already exists.

3. Masonry

Many residences in Boone are composed of brick or stone masonry, and it is imperative that original masonry materials—many of which have a weathered appearance reflecting the history of the building—remain preserved whenever possible. For this reason, masonry should never be cleaned unless it is determined that perceived “dirt” is actually accumulated deposits and not the effects of weathering. In addition, while repointing is sometimes necessary when mortar is missing or moisture problems have developed, it should only be completed in a manner that avoids smearing the mortar onto the surface of the masonry.

- 3.1 It is NOT appropriate to paint masonry materials, such as brick, concrete block, or stone, that were historically unpainted. If there is historic

precedence for painting, it should be completed using colors that generally reflect the natural color of the masonry in question.

- 3.2 Whenever feasible, historic masonry should be repaired rather than replaced or covered. When replacement is necessary, it should always be completed using traditional materials of like kind and quality to the originals that are being replaced.



Even the smallest architectural flourishes, such as the arched vent and glass block detail shown on this otherwise modest Grand Boulevard home, add character to historic residential neighborhoods and should be retained whenever possible. Photo courtesy of Eric Plaag, 2013.

- 3.3 Repointing of masonry should also be completed using materials that duplicate the existing mortar in appearance, texture, and color. Colored sands or mineral pigmented mortar can be used to achieve a match with the existing mortar. Portland cement should be avoided in mortar, as it may produce a mortar that is stronger than the surrounding masonry, potentially causing the masonry to crumble.
- 3.4 Unless there is a specific reasons for using waterproof or water-repellent coatings (e.g., brick that has previously been sandblasted, creating a

porosity problem), these treatments should be avoided, as they can accelerate deterioration of historic masonry.

- 3.5 When repairing or replacing masonry or mortar, take care to maintain the alignment, bond pattern, joint spacing, color, texture, and size of the original masonry.
- 3.6 Unless there is historic precedent for its use on the building in question, stucco should never be applied to existing masonry walls. If existing stucco is being repaired, the stucco mixture should duplicate the original appearance, color, and texture as closely as possible.
- 3.7 Masonry should never be treated with abrasive stripping methods, sandblasting, or high-pressure water cleaning, as these methods almost always immediately damage the "skin" of the brick and the mortar joints, and they can make the masonry more susceptible to spalling, or flaking of the masonry surface as a result of the introduction of moisture. Masonry should only be cleaned using the gentlest method available, including low-pressure water, soft natural brushes, and, if necessary, non-abrasive, non-toxic chemicals that will not damage the masonry being treated.
- 3.8 All historic masonry architectural features, including cornices, moldings, chimneys, and other decorative flourishes, should be retained as they are integral to the architectural character and integrity of the building.
- 3.9 Deteriorated masonry chimneys should never be shortened or covered with parging. Instead, the original chimney configuration should be restored on historic properties using historically appropriate masonry and mortar materials. In addition, the design of the original chimney should be maintained, including corbelling, clay chimney pots, and other original decorative features. Metal chimney caps may be added if they are unobtrusive and do not alter the design of the chimney, but metal vent pipes that protrude through the top of the chimney are not appropriate. Wooden box chimneys and chimneys made of simulated brick or stone are also inappropriate.

4. Siding and Trim

Wooden siding is probably the most commonly found material in Boone's residential historic districts. Traditional historic forms of siding include clapboards, drop siding, flush siding, and board-and-batten siding. In some rare cases, wood shingles are also found in Boone's residential historic properties.

Maintaining wood siding is essential to the preservation of the historic properties on which it appears. In addition to repairing and/or replacing damaged siding members, it is imperative that a regular maintenance program be in place in order to protect the

integrity of historic properties that feature siding. This program should include routine caulking and sealing, cleaning, and painting.

- 4.1 The use of artificial siding (vinyl, aluminum, asphalt, asbestos, Masonite, pressboard, etc.) to cover original siding is not permitted in historic districts or on locally designated historic properties because it destroys the integrity of historic properties. Beyond covering up original architectural details, its installation damages the historic materials underneath, and the artificial siding itself often traps moisture that can lead to further damage of the historic materials. Because it covers historic natural materials, it can also hide the natural critters—termites, carpenter ants, and fungus—that can damage those historic natural materials.
- 4.2 The original form, details, and materials of exterior walls and trim should be preserved whenever feasible. If damage is present, repair using existing historic materials is always preferable over replacement. If replacement is necessary, replacement materials should duplicate the form, details, texture, size, shape, color, pattern, and composition of the historic wall surface and should be obtained from salvage or antique suppliers. Only the portion that requires replacement should be replaced. The Commission will consider the use of substitute materials ONLY if the historical material is not technically feasible or is no longer available.
- 4.3 Because its use is not historic to Boone’s residential historic districts, artificial bark siding is strongly discouraged.
- 4.4 Wood elements that were traditionally stained, such as cedar shingles, should never be painted, as this destroys the historic appearance and integrity of the building.
- 4.5 Whenever possible, the removal of non-historic artificial siding and trim materials to uncover or facilitate the restoration of original historic siding and trim details is strongly encouraged.
- 4.6 Historic architectural metals, such as pressed tin, aluminum, and cast or wrought iron, should always be retained. If these items are not repairable due to rust or other deterioration, replacement materials should duplicate the form, details, texture, material, size, shape, color, pattern, and composition of the original. When cleaning of architectural materials is necessary, use the gentlest methods possible, such as water, a gentle, non-caustic soap, and soft bristle brushes.

5. *Windows, Doors, and Awnings*

The arrangement of doors and windows on an historic property is one of the most important elements of building design. It is imperative that these arrangements be

preserved in order to maintain the integrity of individual historic properties and the integrity of historic districts. Because older windows and doors were not always designed with heating and cooling efficiency in mind, it is often tempting to property owners to replace these features with modern doors and windows. Despite the apparent advantages of doing so, replacement with modern doors and windows is often far more expensive than repairing existing historic doors and windows, and their use often completely destroys the integrity of the historic property in question. Furthermore, many companies are now producing “modern” wood replacement windows that replicate the appearance of their historic antecedents with fixed muntins but feature double-pane glass to assist with heating and cooling efficiency. The Commission reviews proposals for the use of modern wood replacement windows carefully to insure that muntin thickness aligns with the muntin dimensions of historic windows.

- 5.1 The pattern, arrangement, location, size, and shape of windows and doors contribute significantly to a building’s historic character, and their consistency within the district helps unify the buildings in context to one another. For this reason, it is always preferable to repair damaged windows and doors rather than replacing them. Furthermore, it is imperative that the fenestration pattern of the door and window openings on the building and of the doors and windows themselves (muntin width, number of lites per sash, etc.) be maintained when repairs to or replacement of elements is underway. It is never appropriate to introduce new features, such as vents, bays, windows, or door openings, in exterior walls if they diminish the historic character of the wall or damage historic materials.
- 5.2 Whenever possible, the original window and door hardware should be preserved and maintained, as these components are also vital elements of historic properties.
- 5.3 Whenever possible, other original window and door elements, such as sashes, glass, sills, frames, casings, weather-stripping, lintels, architraves, and shutters, should be repaired rather than replaced. This includes sidelights and fanlights on both doors and windows, which are vital architectural elements that help identify the style and period of a particular property. Snap-in muntins are not historically accurate and should always be avoided.
- 5.4 Unless restoring the appearance of a building to its original, historic context, the pattern, arrangements, and dimensions of doors and windows on principal elevations should be retained. On elevations not visible from the street, new door or window openings should be proportionate to existing ones and include matching design elements.

- 5.5 Reflective or tinted glass is not historically accurate to Boone's residential historic districts or historic properties and should never be used if visible from streets or public rights of way.
- 5.6 If a building did not historically possess shutters, they should not be added. Similarly, historic shutter elements should be repaired and retained. Existing shutters should never be replaced with materials that are not historic to the property (metal, vinyl, or plastic shutters, for example), nor should they be replaced with shutters of a different size or configuration, especially those that do not fit the window opening and are attached to existing siding or masonry.
- 5.7 Shutters should be attached to the window casing, not the siding or masonry, unless the original historic context of the property featured shutters attached to the siding or masonry.
- 5.8 It is appropriate to have original windows repaired and storm windows added to historic properties. This approach is preferable to replacement of original windows. Storm windows protect original windows, reduce heat loss, and are not a permanent change to a structure when installed properly. Original window and door elements should never be destroyed when storm windows or doors are installed on historic properties. Storm windows and doors should blend with the historic property, rather than appearing to be tacked on as an afterthought. Storm doors should have full glass with no meeting rails or muntins, while storm windows should have a meeting rail that aligns with the meeting rail of the window.
- 5.9 Raw metal storm windows and doors are not appropriate. When possible, interior storm windows are encouraged. If exterior storm windows and/or doors are installed, frames should be painted wood or painted or baked enamel finish aluminum.
- 5.10 Awnings are never appropriate on residences where there is evidence of historic use of shutters.
- 5.11 Awnings should be composed of canvas or acrylic. Metal awnings are never appropriate, except for historic properties erected after World War II that historically had metal awnings at the time of their construction.
- 5.12 Awnings on windows, entryways, and porches should be appropriate in design, proportion, scale, and color to the architectural style and period of the property. Awnings should be mounted within the window or entry opening, directly on the frame. If this is not possible, they should be attached just outside the opening. If attached to a masonry building, attachments should be made in mortar joints and never in the brick itself.

6. Roofs:

Among the most significant and important of the distinguishing characteristics of historic properties are the roof form and pitch, which are often essential to identifying the architectural style of a building. For this reason, it is imperative that every effort be made to preserve and maintain the original roof configuration and materials on historic properties, including dormers, turrets, balustrades, etc. While historic roofing materials should always be preserved whenever possible—especially if they consist of specialty roofing materials such as slate or tile—many roofing elements will require replacement due to deterioration and age. Note that North Carolina's Building Code prohibits that application of more than two layers of roofing materials on a residence at any given time.

- 6.1 Significant changes to roofs of historic properties are not permitting, including the raising or lowering of pitch, the removal or alteration of widow's walks, dormers, turrets, balustrades, bargeboards, quarter round, cornices, coping, dentil moldings, brackets, eaves, rafter tails, weather vanes, or lightning rods, the cutting back of roof overhang, and the replacement of historic roofing materials with modern materials that do not replicate the original appearance of the historic property's roof. Specialty roofing materials, such as tile or patterned slate, should never be replaced with composition shingles.
- 6.2 Whenever possible, deteriorated soffits, fascia, moldings, brackets, eaves, rafter tails, cornices, coping, and other important roof components should be repaired. If replacement is necessary, it should be completed using historic materials if possible, and at minimum with equivalent materials that replicate the appearance, configuration, size, scale, and composition of the original historic materials. Underlying roofing components are just as important. For example, tongue-and-groove soffit lumber should never be replaced with plywood, and whenever possible, roof decking should be replaced with similar materials rather than modern materials that are not historically appropriate to the house.
- 6.3 Dormers and gables should never be added to the principal elevations visible from the street (unless replacing an historic element that had been previously removed) and should be added to rear elevations only when it can be shown that they are appropriate for the house style. Skylights, solar panels, power ventilators, and mechanical equipment should always be restricted to the rear slopes of the roof and hidden from the street.
- 6.4 It is important to provide adequate ventilation for roofing components, as excessive heat buildup under the roof can shorten the life of shingles. Ventilators should be located in an inconspicuous place, preferably on rear roof slopes not visible from the street, and low-profile mechanical or power ventilators are best. Soffit vents are permissible as long as the

original soffit lumber is retained. On historic properties that already possess louvered wood gable vents, these should never be covered or replaced with metal louvers.



The use of tar as a flashing material, as seen around the second story porch of this historic and otherwise very attractive Boone residence, can damage original masonry and is unsightly. Photo courtesy of Eric Plaag, 2013.

- 6.5 Tar or roofing cement should never be used as a substitute for properly installed flashing. In most instances, metal flashing is always preferred over asphalt shingle weaving, particularly in valley flashing situations.
- 6.6 Deteriorated roof coverings should be replaced with materials that are compatible with the old in composition, size, texture, pattern, and color once the structural integrity of the roof decking is assured. If at all possible, the use of historic replacement materials for slate, clay tile, terra cotta, pressed metal shingle, and wood shingle roofs is always preferred over new materials. Unless historically appropriate to the building in question, white or very light shingles are not permitted. Exposed tarpaper rolls are also not permitted as a roofing material.

- 6.7 Metal gutters, downspouts, and other drainage devices are common on historic residences and should always be retained whenever possible, as they provide important protection for both the roof and the foundation of the property. Built-in gutters that are an important part of the architecture of the building should always be repaired rather than replaced if they become deteriorated. When metal finishes must be replaced because of rust or other deterioration, replace ONLY deteriorated material or detail with new materials that match the previously existing historic material in composition, size, shape, texture, pattern, color, and detail. Replacement gutters and downspouts should never conceal or interfere with architectural trim details. It is not appropriate to paint metal finishes, such as metal downspouts or copper trim, if these items were historically unpainted.
- 6.8 Flashing materials should blend in color with the roof or chimney color. Whenever possible, historically appropriate splash blocks at the base of downspouts should be used to direct water away from the building's foundation. (Please note that the Town of Boone's storm water detention requirements may apply to the use of splash blocks.)

7. Entrances, Porches, and Balconies:

One of the most significant and defining characteristics of domestic architecture is the main or front entrance, including any porches that surround or frame that entrance. In Boone, the front porch was also often one of the most socially important areas of a home—a place where hosts greeted their guests and where neighbors often exchanged news and stories with one another. Unfortunately, main or front entrances are also often the most altered elements of historic properties.

Many historic entrances, porches, and balconies contain architectural elements that are essential to communicating the architectural style of the home. Machine-carved balustrades, spindles, brackets, and posts were common in many of Boone's historic homes, but hand-worked elements are also not uncommon. Preserving these details is vital to preserving the appearance and integrity of Boone's historic domestic architecture.

- 7.1 Entrances, porches, and balconies, as used in this section, include front, back, and side porches, mudrooms, porticos, sleeping porches, balconies, pergolas, terraces, widow's walks, and entrances. Components of porches include steps, balustrades, columns, trellises, skirt boards, fascias, brackets, and various ornamental details. Most original porches and balconies were built with a slight pitch away from the residence to facilitate the runoff of rainwater.
- 7.2 Because of their architectural significance, porches, balconies, and entrance configurations—especially those on the front or main elevation—

and all of their architectural details (steps, balustrades, brackets, spindlework, columns, roofs, etc.) should be preserved in their original form and detail whenever possible. It is inappropriate to enclose porches and balconies on the front or main elevation for use as an interior space. In addition, the original pitch of porches and balconies should be maintained in order to facilitate the runoff of rainwater and snowmelt. Porches and balconies must be properly maintained and repaired as necessary, as they are exposed to the weather and will deteriorate if regular maintenance is not conducted.



Original entrance configurations and porches should never be closed in or obscured by additions to historic properties, as has occurred with this otherwise attractive and significant Grand Boulevard home. Photo courtesy of Eric Plaag, 2013.

- 7.3 If an historic porch or balcony is completely missing (or if architectural elements associated with the porch or balcony are missing), it should be replaced with a reconstruction based on accurate historic documentation or a new design that is appropriate for the structure in terms of architectural style, materials, roof form, details, scale, size, and ornamentation. Adding details that are not historical to create a false historical appearance is never appropriate.

- 7.4 If an historic porch or balcony requires repairs, use only materials that are compatible with the original materials associated with the porch or balcony. These replacement materials should match the previously existing historic materials in composition, size, shape, texture, pattern, color, and detail.
- 7.5 Whenever possible, existing infill on historic porches and balconies should be removed and the original appearance of the porch or balcony restored.
- 7.6 Side porches or porches not located on the main elevation may be enclosed for interior space, provided that the proposed design of the enclosure is compatible with the architecture of the historic property. Side porches and porches not located on the main elevation may also be screened, provided that framing for the screening and the screening itself is placed behind columns or balustrades. Any such enclosures or screening should be designed so that they can later be removed without damage to the integrity of the historic structure.
- 7.7 Original porch steps should always be retained. If repair or replacement of porch step materials is necessary, the design, configuration, dimensions, and materials should match the original as closely as possible. In addition, historic stairways and walkways in front of a building—even though not technically part of the building's architecture—are nevertheless an important part of the landscape that accompanies the property and often inform the architectural style and patterns of the property. These elements should always be retained and repaired with appropriate materials whenever possible.
- 7.8 Decks may be added on the rear elevation of a historic property, provided their addition does not require the removal of large, healthy trees, and their design is compatible in scale with the historic property. They should always be designed and installed in such a manner that they may be removed without damage to the historic building. Removal of historic building materials to facilitate the installation of a deck is never acceptable.
- 7.9 Vegetative screening should be employed to obscure the visibility of decks from the street. The underside of decks should also employ latticework or vegetative screening to incorporate the deck element into the general whole of the property in question.
- 7.10 Floor coverings, such as artificial turf, indoor/outdoor carpeting, linoleum, and other similar materials (aside from a small doormat near an entrance) should never be installed on porch, balcony, or deck floors, as these materials can trap water and damage the historic architectural elements below.

8. Paint and Paint Color:

Determining the original colors associated with historic properties, especially those built before World War II, is very difficult because of the rarity of color photography during the pre-World War II period. While color chronology tests can help to determine original paint colors (contact the State Historic Preservation Office for assistance), this process is difficult, sometimes inconclusive, and often expensive.

Instead, the architectural style of a building can often be a guide to historic colors. Victorian domestic architecture, especially Queen Anne style homes—often known colloquially as “painted ladies”—were usually painted in a variety of bold, contrasting colors that might seem gaudy to modern eyes. By contrast, Depression era homeowners often relied on basic white paint or whitewashing, as it was believed that houses painted white would sell more quickly; as a result, more traditional or historic paint colors may have been covered up through these practices.

While the Boone Historic Preservation Commission does not regulate paint colors per se, property owners are advised to seek assistance from the HPC and/or the State Historic Preservation Office when considering paint schemes for historic properties. Beyond this, some general guidelines are applied by the HPC when considering paint in relation to historic properties.

- 8.1 It is NOT appropriate to apply paint or other coatings to unpainted wall materials and surfaces/finishes that were historically left unpainted, including masonry, stonework, wood shingles, stained wood surfaces, and metal.
- 8.2 It is NOT appropriate to use abrasive techniques for cleaning or removing paint from exterior walls and trim, such as sandblasting, high-pressure waterblasting, or other methods that may damage the surface. In general, old paint should not be removed unless there is a compelling reason to do so, such as revealing an obscured architectural detail or correcting a severe peeling or cracking problem in existing paint.
- 8.3 Select paint colors that are appropriate for the building’s architectural style and that are complementary to neighboring buildings. In general, color should function as a method of contrasting among different materials and architectural elements that make up the house. Typically, trimwork—including window and door casings and surrounds, soffits, fascia, and other elements—is often painted with a contrasting or lower value hue than the weatherboard or siding, especially on Victorian-era properties. Wood shingles are usually stained a dark color and often darker than any associated wood siding.

- 8.4 Wooden steps should always be painted to match the color of a wooden porch floor.

9. *Utilities and Energy Retrofit:*

Updating utilities and energy systems in historic homes is a common and natural event in the life of a house. As technology improves and environmentally friendly mechanical systems become available, many homeowners will desire to improve the efficiency of their historic homes. The Boone HPC encourages the installation, rehabilitation, or replacement of mechanical systems—in compliance with local building codes and utility company standards—that will improve the overall efficiency of those properties. That said, these mechanical systems, when installed in or on an historic property, must comply with certain essential guidelines.

- 9.1 Install utilities and mechanical equipment in areas and spaces that will require the least possible alteration to the plan, materials, and appearance of the building. Installation at the rear of the structure, if feasible, is preferred.
- 9.2 It is NOT appropriate to locate mechanical equipment farther forward on the property than the midpoint of the primary structure.
- 9.3 Ductwork, piping, fuel tanks, plumbing vents, solar collectors, and satellite dishes should not be visible from the street. Equipment that can be seen from the street should be screened with shrubbery or fencing.
- 9.4 If an interior location is not feasible, place utilities and mechanical equipment in inconspicuous locations and/or conceal with architectural elements such as downspouts.
- 9.5 The location of solar collectors or solar panels should be aligned on the building's roof in the direction of greatest effectiveness with a minimized view of such equipment from the primary façade of the structure.

10. *Accessibility, Health, and Safety Considerations:*

Modern building codes and/or the needs of the families who own and live in historic properties often mean that a variety of accessibility and safety elements must be installed in those properties. Careful planning insures that the integrity of historic properties can be maintained in spite of the addition of these non-historic elements.

- 10.1 New exterior fire escapes are not permitted on historic properties unless more adequate exit facilities cannot be provided. If they must be installed, fire escapes generally should be located at the rear of the building and never along an exposed elevation.



The J. W. and Mattie Jones House, listed on the National Register of Historic Places and presently used by the Town of Boone as a community center and the home of some town offices, is an excellent example of the preservation of domestic architecture within the downtown historic district area. To achieve its accessibility requirements, access facilities were located at the rear of the building, thus minimizing the impact on the historic integrity of the property. Photo courtesy of Eric Plaag, 2013.

- 10.2 Introducing items such as wheelchair ramps, fire exits, and fire stairs without damaging the character of a historic structure requires careful planning. Owners should introduce fire exits, stairs, landings, and ramps on rear or inconspicuous side locations. If access ramps must be installed in a manner that makes them visible from the public right-of-way, they should be constructed in a manner that makes them as simple and compact as possible and limits their projection from the building.
- 10.3 Construct fire exits, stairs, landings, and ramps in such a manner that they do not damage or significantly obscure historical materials and features. Such additions should be designed to be complementary to the architectural style, materials, scale, and function of the historic property.

- 10.4 Whenever possible, existing exterior fire escapes and stairways that are not original to historic properties should be relocated from front or exposed elevations to a rear or unexposed elevation.

11. Additional Guidelines on Artificial Materials:

Over the years, many clapboard houses in Boone were covered with aluminum or asbestos siding. Due to the loss of both historic character and original materials inherent in the application of such substitute materials, the damage caused during installation, and the potential for undetected insect infestation and moisture damage, the practice is not acceptable for a historic residential property. The removal of previously installed substitute siding is strongly encouraged. Previously installed vinyl windows and snap-in muntins are examples of inappropriate replacements for wood windows and should also be removed and replaced with more historically appropriate materials whenever possible.

12. Additions to Existing Buildings:

The completion of an addition to a historic property may improve the functionality of an existing building, but it also has the potential to seriously damage the historic integrity of that property. Generally speaking, additions accordingly should be kept to a minimum and always be reversible without resulting in permanent damage to the essential form and integrity of the historic property.

- 12.1 New additions should be compatible with the original building in scale, placement, proportion, and design, including roof shape, materials, color, location and design of windows and doors, cornice heights, and other design elements.
- 12.2 New additions should NOT imitate an earlier historic style or architectural period, but they also should not differ from the earlier historical style so much as to be a distraction from or incompatible with the historic design.
- 12.3 Additions should be differentiated from the original by the use of setbacks or other devices. Whenever possible, additions should be located to the rear or in an inconspicuous location on the side of the original building. They should never be attached to the front of the historic property.
- 12.4 An addition should NOT obscure the original form and proportions of the main building or of other historical additions.
- 12.5 Additions should be constructed on a smaller scale than the historic structure and not overpower it.



Additions like the one shown on the left side of this Grand Boulevard home should incorporate their own architectural style while also remaining harmonious with the historic part of the building. The use of a roofline distinction also helps communicate that the addition was not part of the original house without distracting from the architectural character of the original section. Photo courtesy of Eric Plaag, 2013.

- 12.6 Construction should be carried out in a manner that avoids removal or loss of historic materials and damage or destruction of significant original architectural features.
- 12.7 Construction should impact the exterior walls of the original building as minimally as possible using existing door and window openings for connecting the addition to the original building.

13. New Construction of Residential Buildings within Historic Districts:

It is inevitable that new buildings will be constructed within existing historic districts. The intention of these design guidelines is not to prevent such changes but to ensure that new construction is compatible with and complementary to the integrity and architectural character of Boone's historic neighborhoods. While new buildings should not attempt to replicate existing historic properties, they should mesh with and support the historic design principles of the neighborhood in which they are built. These guidelines are

intended to preserve the integrity of Boone's neighborhoods while also encouraging sensitive and appropriate new construction.

- 13.1 New construction within historic districts should not seek to duplicate historic buildings in the district or mimic their appearance. That said, new construction should strive to be sensitive to and compatible with the character-defining features of an existing historic district. Thus, new construction should employ architectural design that reflects its current time, place, use, and culture, provided that this design is compatible with the character of the historic district.
- 13.2 The appropriateness of the site for a new construction project will be evaluated based upon its compatibility with the district context in terms of setback, spacing, orientation, topography, height, and landscaping. New buildings should have setbacks, orientation, lot coverage, and spacing that align with existing historic properties and comply with the provisions of the Town UDO.
- 13.3 New construction should respect the existing topography and vegetation on the site. Large-scale grading to level or otherwise dramatically alter the natural slope of a lot is destructive to the historic landscape and is not appropriate. Whenever possible, existing trees and historic landscape features should be incorporated into the design for a new property. If large trees must be removed, they should be replaced with trees similar in type and species. During construction, any mature tree that will not be removed should be protected with appropriate fencing around the tree's canopy area that will eliminate construction parking, material storage, and concrete washout that could harm the mature tree.
- 13.4 The appropriateness of a proposed new building will be evaluated based on compatibility in terms of scale, height, form, massing, materials, openings, roof pitch, roof type, and other details with the district context.
- 13.5 Incorporate architectural elements and details into new construction that provide human scale, such as porches and trim.
- 13.6 Oversized and monumental scale architecture is not appropriate, and the overall height and width of the new buildings should be compatible with neighboring structures and Town UDO requirements.
- 13.7 Design new buildings using exterior materials typical of historic buildings in the district, including brick, wood, and stone.
- 13.8 It is NOT appropriate in new construction to use contemporary substitute materials such as vinyl or aluminum siding or artificial stacked stone in place of traditional materials.

14. Minimum Spacing and Height Requirements for Residential Structures:

For details on the minimum spacing and height requirements for residential structures in the Town of Boone, please consult the Town of Boone UDO.

Design Guidelines For Commercial Properties

***Guidelines for Commercial Historic Landmarks
and Commercial Properties within the Downtown Boone Historic District***

1. Storefronts, Upper Facades, Side Elevations, and Rear Elevations

Downtown Boone is dominated by historic properties that reflect the commercial block architecture that was so common and influential during the period from 1910 to 1960 in many American towns and cities. In the case of Boone, NC commercial block development began around 1919 to the early 1960's. Central to this architecture is the importance of the storefront itself, whose familiar architectural details—large display windows, transom bars and windows, clerestory recessed entries, and prominent cornice and corbelling work—frequently signaled to customers not only the function of a business but also the quality of its wares. Many other elements—including projecting, flat awnings anchored to the façade with cables or steel rods, or fabric awnings amounted on metal frames, hinged or unhinged—provided customers with shelter from the elements while window shopping or otherwise enhanced the shopping experience. After 1950, many of these architectural details were removed, either in response to decay of these features or in an effort to “update” a building to the stylistic preferences of a later time. One such example is the Appalachian Theatre on West King Street, whose original Art Deco marquee and structural glass were removed during the late 1970s in response to safety concerns. Other elements—most notably transom bars and windows, as well as the details of upper facades—were simply covered over and may still survive today underneath modern additions to the facades of many of Boone's historic downtown properties.



This West King Street building is an outstanding example of successful façade restoration and preservation that uncovered numerous original storefront details, including the clerestory windows above the shop windows and entrance. Photo courtesy of Eric Plaag, 2013.

Similarly, side and rear elevations of many of Boone's historic commercial properties are vital to the character and integrity of its downtown commercial district. Often, these contributing side and rear elevations are located on corner buildings adjacent to two or even three streets, but sometimes such details are visible on mid-block buildings separated from nearby buildings by an alleyway or a vacant lot. Many of these buildings retain original fenestration, entrances, brickwork, and/or advertisements (some of the "ghost ad" variety) that contribute in their own significant way to the architectural character of the downtown historic district. Similarly, rear elevations can possess many of these same characteristics and also reveal much about the history of a property because of their frequently utilitarian design intended for the workers, owners, and residents who most often saw these rear elevations.

In an effort to preserve what remains of Boone's historic commercial architecture and encourage the reconstruction or rehabilitation of elements that have been removed or covered over, the guidelines for storefronts, upper facades, and other elevations are

intended to facilitate preservation and reconstruction wherever possible while also addressing new construction and its compatibility with commercial historic districts.

- 1.1 Whenever possible, historic storefronts and storefront features such as entrance configurations, display windows, doors, clerestory windows, transom bars and windows, corbelling, cornice work, windows, stonework, stringcourses, structural glass, and other architectural flourishes should be retained and preserved. When repairing these features, retain and preserve in place original elements as much as possible. If repair is not possible, replace damaged elements with materials that match the originals in composition, design, texture, color, and other visual qualities.
- 1.2 When reconstructing an historic storefront, upper façade, or other elevation, use historical research and evidence as the basis for the design. Reconstructed storefronts should incorporate original dimensions, proportions, and architectural elements.
- 1.3 In making changes to storefronts or other elevations to comply with code or accessibility requirements, avoid destroying historic materials and features and select configurations that have minimal intrusion or impact on the character-defining aspects of the property in question.
- 1.4 When original or early storefronts or upper facades no longer exist, are too deteriorated to save, or cannot be reconstructed based on the available documentary evidence, retain the commercial character and any salvageable architectural details through a contemporary design that is compatible with the scale, materials, color, style, design, and texture of the surviving and surrounding historic buildings.

Sometimes past owners have completely removed the defining characteristics of an historic property's façade, as in the case of the Appalachian Theatre on West King Street. The non-profit group that purchased this building in 2013, recently rehabilitated to resemble it's original, historic appearance using historic documentation. This temporary faux façade is intended to improve the appearance of the building while the rehabilitation of the façade is funded and planned. Photo courtesy of Eric Plaag, 2018.



This building on West King Street is an example of both “good” and “bad” preservation decisions. While much of the original brick detailing, corbelling, and ornamentation of the façade has been preserved, this upper façade’s windows were replaced, with modern materials and the prominent, ornate cartouche that once appeared between these windows has been removed in favor of modern signage. As of 2018, this building is undergoing another rehabilitation. Photo courtesy of Eric Plaag, 2013.

- 1.5 Original upper façade windows should not be removed and replaced with modern materials, nor is the enclosing or bricking in of upper façade windows appropriate. When upper floor windows must be replaced, use new windows that match the original windows in configuration, appearance, and materials.
- 1.6 It is never appropriate to cover an historic upper façade. Whenever possible, non-historic coverings of upper facades, including metal, stucco, or faux mountain village fronts and porches, should be removed and underlying original architectural elements repaired and restored.



Historic “ghost ad” on the upper portion of a Downtown Boone building. Such elements are essential to the history and character of commercial historic districts and should be preserved whenever possible. Photo courtesy of Eric Plaag, 2013.

- 1.7 Historic painted advertisements are a significant element of the architectural and commercial history of downtown Boone, and their preservation and restoration are recommended whenever feasible, even if the product or store advertised is no longer available or in business.
- 1.8 Façade details of side and rear elevations should always be retained and preserved if possible. When repairing these features, retain and preserve in place original elements as much as possible. If repair is not possible, replace damaged elements with materials that match the originals in composition, design, texture, color, and other visual qualities. If there is evidence of a rear public entrance that is no longer extant, use historical research and other evidence to reconstruct or provide an equivalent rear entrance whenever possible.
- 1.9 Utility lines, mechanical equipment, pipes, garbage receptacles, and other service items on rear and side elevations—whether old or new—should be screened from public view whenever possible. Unnecessary or out of

service elements should be removed unless they are essential to the historic character of the property.

2. Architectural Components and Details

Exterior architectural components, including door and window casings, storefront configurations, cast iron ornamentation, stone relief, cornices, columns, brackets, porch railings, soffits, fascias, roof configurations, trim details, architectural flourishes, and various joinery and surface patterns, all contribute significantly to the character and integrity of historic properties and properties located within historic districts. Because many of these components are either irreplaceable or very expensive to reproduce, they should be maintained and valued in the same way that one might consider an important family heirloom or expensive antique furniture. In many cases, missing or damaged architectural details can be replaced with like items from salvage yards, antique shops, or mail order companies that specialize in replacement of historic architectural components. If such items cannot be replaced, many construction supply companies stock simulations of period architectural components that are approved by the Secretary of the Interior and the National Park Service as suitable historic replacements. In any event, before replacing any exterior architectural component, property owners should familiarize themselves with the architectural style and historic characteristics of their building to avoid introduction of inappropriate elements.

- 2.1 It is important to preserve character-defining, historical, architectural features of exterior walls, such as cornices, friezes, medallions, sunbursts, brackets, bays, turrets, fascias, quoins, columns, brickwork, string courses, and decorative moldings. Original architectural details should always be retained if structurally feasible. If original details are missing, design replacement features based on historic photos and other documentation.
- 2.2 It is NOT appropriate to cover or remove rather than repair or replace in kind such features when they are deteriorated. If replacement is necessary, the new materials should match the materials being replaced in composition, design, texture, color, and other visual qualities. Original architectural features that are covered should be uncovered, exposed, repaired, and maintained.
- 2.3 It is NOT appropriate to cover or replace historic materials with substitute materials, such as aluminum, vinyl, hard board (concrete siding), or plywood panels. Architectural details that are not appropriate to the historic context and character of a building should never be added. At the same time, property owners should never use details from an earlier period to try to make a building look older than it is.
- 2.4 Historic architectural metals, such as pressed tin, aluminum, and cast or wrought iron, should always be retained. If these items are not repairable

due to rust or other deterioration, replacement materials should duplicate the form, details, texture, material, size, shape, color, pattern, and composition of the original. When cleaning of architectural metals is necessary, use the gentlest methods possible, such as water, a gentle, non-caustic soap, and soft bristle brushes.

3. Foundations

For most property owners of commercial properties, solid masonry walls on the exterior of the building will obscure the foundation of their historic property. For others, the foundation will resemble the type found in domestic architecture and will consist of either piers of masonry or a complete masonry wall on the perimeter of the structure as well as interior piers or walls for support and a sill plate connecting the perimeter wall with the rest of the building. Some historic commercial buildings in Downtown Boone will have cast concrete foundations below the first floor level of the primary façade. In some cases, masonry walls have been added between original masonry piers on the perimeter of the foundation.

Settling—sometimes of an inch or more—is quite common and should be expected in a historic property, often in an uneven or disproportionate manner along the entirety of the foundation. Settling also typically cracks mortar joints. For this reason, it is part of routine maintenance to periodically re-point mortar joints and inspect for more severe settling problems. In some cases, property owners will need to consult with a masonry contractor or civil engineer to correct serious settling problems. A number of less expensive and fairly common repair “tricks” are inappropriate for historic properties and can actually cause further damage to the historic fabric and integrity of the property.

- 3.1 Whenever a foundation requires repairs, always use the original bricks or stones if possible. If these materials are damaged beyond repair, replace them with bricks or stones similar in size, color, and surface texture to the originals. If using recycled bricks, always put the weathered side to the exterior in order to maintain the historic appearance of the foundation walls and/or piers.
- 3.2 In repairing or reconstructing a foundation, the historic bond patterns and mortar treatments should always be replicated. Brick header rows, band boards, and other horizontal design elements should match and align with the existing historic elements.
- 3.3 Sandblasting, painting, waterproofing, and parging—a technique of applying a cement-like coating to a deteriorating foundation in order to avoid repairs—should never be employed on the exposed portions of foundation exteriors, as all of these methods damage original masonry and mortar treatments. In addition, non-porous applications trap moisture that can freeze, cause further damage to masonry, and result in damage to the interior of the building.

- 3.4 Exposed concrete block and cast concrete and pre-cast concrete panels are strongly discouraged, unless these components are already part of the historic context of the property in question.
- 3.5 If closing in the openings between brick piers, use matching masonry materials or lattice that is slightly recessed from the façade plain of the historic masonry. Note that foundations need to be vented. Vents should be painted a color that blends with the existing foundation color.
- 3.6 Access doors to basements or foundation crawlspaces should always be located in an area not visible from the street unless a different configuration that aligns with the building's historic context already exists.

4. Masonry

Many commercial properties in Boone are composed of brick or stone masonry, and it is imperative that original masonry materials—many of which have a weathered appearance reflecting the history of the building—remain preserved whenever possible. For this reason, masonry should never be cleaned unless it is determined that perceived “dirt” is actually accumulated deposits and not the effects of weathering. If cleaning is pursued, always use the gentlest method available, preferably with low-pressure water, a mild, non-caustic detergent, and a natural bristle brush where needed. In addition, while re-pointing is sometimes necessary when mortar is missing or moisture problems have developed, it should only be completed in a manner that avoids smearing the mortar onto the surface of the masonry.

Terracotta, stucco, and concrete are other masonry elements that are occasionally found on historic commercial properties in Boone. In addition, many historic commercial properties feature chimneys, arches, quoins, lintels, sills, cornices, corbelling, and pediments that are all essential to the historic character of the building in question.

- 4.1 It is NOT appropriate to paint masonry materials, such as brick, concrete block, or stone, that were historically unpainted. If there is historic precedent for painting of masonry in the building's original historic context, it should be completed using colors that can be documented with original historic photographic evidence or analysis of original paint samples. Removal of non-historic paint from masonry should be completed using a chemical paint remover specifically intended for masonry and using the gentlest application means possible.
- 4.2 Whenever feasible, historic masonry, including decorative masonry features, should be repaired rather than replaced or covered. When replacement is necessary, it should always be completed using traditional materials of like composition, size, color, shape, pattern, texture, and quality to the originals that are being replaced.



Retaining original masonry configurations, patterns, and detailing is essential to preserving the architectural character of Boone's historic districts. Photo courtesy of Eric Plaag, 2013.

- 4.3 Re-pointing of masonry should also be completed using materials that duplicate the existing mortar in appearance, texture, and color. Colored sands or mineral-pigmented mortar can be used to achieve a match with the existing mortar. Portland cement should be avoided in mortar, as it may produce a mortar that is stronger than the surrounding masonry, potentially causing the masonry to crumble.
- 4.4 Unless there is a specific reason for using waterproof or water-repellent coatings (e.g., brick that has previously been sandblasted, creating a porosity problem), these treatments should be avoided, as they can accelerate deterioration of historic masonry.
- 4.5 When repairing or replacing masonry or mortar, take care to maintain the alignment, bond pattern, joint spacing, color, texture, and size of the original masonry.

- 4.6 Unless there is historic precedent for its use on the building in question, stucco should never be applied to existing masonry walls. If historic stucco is being repaired, the stucco mixture should duplicate the original appearance, color, and texture as closely as possible.



This West King Street property has suffered from poor attempts at re-pointing the masonry between the roofline and upper story windows. Photo courtesy of Eric Plaag, 2013.

- 4.7 Masonry should never be treated with abrasive stripping methods, sandblasting, or high-pressure water cleaning, as these methods almost always immediately damage the “skin” of the brick and the mortar joints, and they can make the masonry more susceptible to spalling, or flaking of the masonry surface as a result of the introduction of moisture. Masonry should only be cleaned using the gentlest method available, including low-pressure water, soft natural brushes, and, if necessary, non-abrasive, non-toxic chemicals that will not damage the masonry being treated.
- 4.8 All historic masonry architectural features, including cornices, moldings, chimneys, and other decorative flourishes, should be retained as they are essential to the architectural character and integrity of the building.

- 4.9 Deteriorated masonry chimneys and boiler stacks should never be shortened or covered with parging. Instead, the original chimney configuration should be restored on historic properties using historically appropriate masonry and mortar materials. In addition, the design of the original chimney should be maintained, including corbelling, clay chimney pots, and other original decorative features. Metal chimney caps may be added if they are unobtrusive and do not alter the design of the chimney, but metal vent pipes that protrude through the top of the chimney are not appropriate. Wooden box chimneys and chimneys made of simulated brick or stone are also inappropriate.
- 4.10 Proper maintenance of masonry is essential to its long-term survival. Property owners should conduct periodic checks for moisture problems and cracking, and they should remove any vegetation that adheres to masonry (such as ivy and other vine plants) or that hinders ventilation and drainage around masonry elements. Vegetation should never be sprayed with defoliant, pesticides, or other harsh chemicals. Please consult with the Planning and Inspections Department for guidance on removal of vegetation of masonry.

5. Wooden Elements

Wooden bulkheads below display windows, window sashes, cornices, doors and doorframes, and trim are probably the most commonly found wooden historic materials in Boone's commercial historic district, although wood siding is visible on some domestic architecture in the downtown commercial area (such as the Jones House or the old Watauga County Jail). These wooden design elements are important components of the architectural character and integrity of Boone's historic commercial properties.

Maintaining wooden elements is essential to the preservation of the historic properties on which they appear. In addition to repairing and/or replacing damaged wooden details, it is imperative that a regular maintenance program be in place in order to protect the integrity of historic properties that feature wooden design components. This program should include routine caulking and sealing, cleaning, and painting or staining where appropriate.

- 5.1 The use of artificial siding (vinyl, aluminum, asphalt, asbestos, Masonite, pressboard, hardboard etc.) to cover original wood siding is not permitted in the Downtown Boone historic districts or on locally designated historic properties in the Downtown area because it destroys the integrity of historic properties. Beyond covering up original architectural details, its installation damages the historic materials underneath, and the artificial siding itself often traps moisture that can lead to further damage of the historic materials. Because these man-made materials cover historic

natural materials, they can also hide damage caused by termites, carpenter ants, fungi, and other natural invaders.

- 5.2 The original form, details, and materials of exterior wooden features and trim should be preserved whenever feasible. If damage is present, repair using existing historic materials is always preferable over replacement. Where necessary, patching with new wood, the use of epoxy, splicing, consolidating, and reinforcing deteriorated sections should be considered before replacing historic elements. If replacement is necessary, new materials should duplicate the form, details, texture, size, shape, color, pattern, and composition of the historic wooden elements and should be obtained from salvage or antique suppliers. Only the portion that requires replacement should be replaced. The Commission will consider the use of substitute materials ONLY if the preservation of the historic material is not technically feasible, or is no longer available.
- 5.3 Because its use is not historic to Downtown Boone's historic districts, artificial bark siding is strongly discouraged in the Downtown Boone Historic District.
- 5.4 Wooden elements that were traditionally stained, such as cedar shingles, should never be painted, as this destroys the historic appearance and integrity of the building.
- 5.5 Whenever possible, the removal of non-historic artificial siding and trim materials to uncover or facilitate the restoration of original historic wooden details is strongly encouraged.
- 5.6 It is never appropriate to replace historic wooden architectural materials—especially in siding, trim, or window sashes—with contemporary substitute materials such as vinyl or aluminum.

6. Windows, Doors, and Awnings

The arrangement of doors and windows on an historic property is one of the most important elements of building design. It is imperative that these arrangements be preserved in order to maintain the integrity of individual historic properties and the integrity of historic districts. Because older windows and doors were not always designed with heating and cooling efficiency in mind, it is often tempting to property owners to replace these features with modern doors and windows. Despite the apparent advantages of doing so, replacement with modern doors and windows is often far more expensive than repairing existing historic doors and windows, and their use often completely destroys the integrity of the historic property in question. Furthermore, many companies are now producing "modern" wood replacement windows that replicate the appearance of their historic antecedents with fixed muntins but feature double-pane glass to assist with heating and cooling efficiency. The Commission reviews proposals

for the use of modern wood replacement windows carefully to insure that muntin thickness aligns with the muntin dimensions of historic windows.

Boone's downtown commercial historic district has also suffered from the installation of various architectural elements designed to simulate a "mountain village" appearance. These typically consist of large, wooden porch attachments or awnings that are not historically appropriate to the downtown area and its historic context. Metal and modern fabric awnings have also appeared on some properties, disrupting the integrity of many of Boone's historic commercial properties.

- 6.1 The pattern, arrangement, location, size, and shape of windows and doors contribute significantly to a building's historic character, and their consistency within the district helps unify the buildings in context to one another. For this reason, it is always preferable to repair damaged windows and doors rather than replacing them. Furthermore, it is imperative that the fenestration pattern of the door and window openings on the building and of the doors and windows themselves (muntin width, number of lites per sash, etc.) be maintained when repairs to or replacement of elements is underway. It is never appropriate to introduce new features, such as vents, bays, windows, or door openings, in exterior walls if they diminish the historic character of the wall or damage historic materials.



Historic window patterns, like those found here on the Watauga County Bank building, should always be repaired and preserved rather than replaced. Architectural flourishes, like the night depository door below the window, which is no longer used, should be retained, as they help tell the story of an historic property's function and importance to the community. Photo courtesy of Eric Plaag, 2013.

- 6.2 Whenever possible, the original window and door hardware should be preserved and maintained, as these components are also vital elements of historic properties.



Original clerestory windows, like these found on one West King Street property, contain elaborate details that contribute to the character, appearance, and integrity of the downtown historic district. Photo courtesy of Eric Plaag, 2013.

- 6.3 Whenever possible, other original window and door elements, such as sashes, glass, sills, frames, casings, weather-stripping, lintels, architraves, and shutters, should be repaired rather than replaced. This includes sidelights and fanlights on both doors and windows, which are vital architectural elements that help identify the style and period of a particular property. Snap-in muntins are not historically accurate and should always be avoided.
- 6.4 Unless restoring the appearance of a building to its original, historic context, the pattern, arrangements, and dimensions of doors and windows on principal elevations should be retained. On elevations not visible from the street, new door or window openings should be proportionate to existing ones and include matching design elements.



Reflective glass, like the kind found on this Depot Street property, is not historically accurate to Boone's commercial historic districts and should never be used if visible from the street or public rights of way. Photo courtesy of Eric Plaag, 2013.

- 6.5 Reflective or tinted glass is not historically accurate to Boone's commercial historic district or historic properties and should never be used if visible from streets or public rights of way. Property owners whose buildings already possess reflective or tinted glass should endeavor to replace this glass with materials that are more historically appropriate to their building and the district.
- 6.6 If a building did not historically possess shutters, they should not be added. Similarly, historic shutter elements should be repaired and retained. Existing shutters should never be replaced with materials that are not historic to the property (metal, vinyl, or plastic shutters, for example), nor should they be replaced with shutters of a different size or configuration, especially those that do not fit the window opening and are attached to existing siding or masonry.

- 6.7 Shutters should be attached to the window casing, not the siding or masonry, unless the original historic context of the property featured shutters attached to the siding or masonry.
- 6.8 It is appropriate to have original windows repaired and storm windows added to historic properties. This approach is preferable to replacement of original windows. Storm windows protect original windows, reduce heat loss, and are not a permanent change to a structure when installed properly. Original window and door elements should never be damaged or destroyed when storm windows or doors are installed on historic properties. Storm windows and doors should blend with the historic property, rather than appearing to be tacked on as an afterthought. Storm doors should have full glass with no meeting rails or muntins, while storm windows should have a meeting rail that aligns with the meeting rail of the window.
- 6.9 Raw metal storm windows and doors are not appropriate. When possible, interior storm windows are encouraged. If exterior storm windows and/or doors are installed, frames should be painted wood or painted or baked enamel finish aluminum.



Shed roof porticoes like this one on West King Street attempt to create a "mountain village" appearance but are not historically appropriate to the Downtown Boone's historic districts and damage the integrity of the district.

Photo courtesy of Eric Plaag, 2013.

- 6.10 Awnings, porches, shed roof porticoes, and arcades that attempt to create a “mountain village” appearance or that are not historically accurate to Boone’s downtown historic context only work to damage the integrity and appearance of the district. Property owners whose buildings possess such features should endeavor to remove them and restore the façade of their property to its historic appearance. They should never be incorporated into additions or new construction within the Downtown Boone historic districts.



Awnings should be historically appropriate to the buildings they are attached to, and they should never obscure historic architectural features. This awning on West King Street, for example, is stylistically inappropriate to the building and almost entirely covers the structural glass that was once visible above this storefront. Photo courtesy of Eric Plaag, 2013.

- 6.11 Awnings on properties in the historic district should always be historically appropriate in accordance with available photographic and historic documentation, and they should never obscure vital architectural components of the original building. Awning- styles with no documented historic precedent should never be added to properties in the historic district. For example, properties that historically possessed flat awnings

anchored by cables or steel rods should retain these kinds of awnings. In cases where they have been removed, and particularly in cases where they have been replaced with modern, sloped awnings, property owners should endeavor to remove the modern feature and restore the original awning configuration with appropriate materials based on historic documentation. Sloped awnings should be composed of canvas or acrylic. Metal awnings are never appropriate, except for historic properties erected after World War II that historically had metal awnings at the time of their construction.

- 6.12 Awnings on windows, entryways, and porches should be appropriate in design, proportion, scale, and color to the architectural style and period of the property. Window awnings should be mounted within the window or entry opening, directly on the frame. If this is not possible, they should be attached just outside the opening. If attached to a masonry building, all awning attachments should be made in mortar joints and never in the brick itself.



The historic Boone Drug flat awning supported by cables anchored to the façade is visible to the far left in this photo of the effects of the 1940 Boone Flood along King Street. Where possible, original awning configurations like this one should be restored to historic downtown buildings. Photo courtesy of [Becky Haney-David Wyke Collection and Digital Watauga Project](#).

- 6.13 If awnings must be used as signs, they should be kept discreet and not detract from the architectural features and details of the building.
- 6.14 Awnings and canopies that are illuminated from within must be covered or finished with fully opaque material.

- 6.15 New construction, additions, and renovations to existing historic buildings or properties within historic districts should maintain established proportions and spacing of window and door openings.

7. Roofs:

Among the most significant and important of the distinguishing characteristics of historic properties are the roof form and pitch, which are often essential to identifying the architectural style of a building. For this reason, it is imperative that every effort be made to preserve and maintain the original roof configuration and materials on historic properties, including dormers, turrets, balustrades, parapets, etc. While historic roofing materials should always be preserved whenever possible—especially if they consist of specialty roofing materials such as slate or tile—many roofing elements will require replacement due to deterioration and age.

Many of the commercial buildings in the downtown Boone historic district featured flat or gently sloping roofs behind a parapet wall along the façade and sometimes the side elevations when they were first built.

- 7.1 Significant changes to roofs of historic properties, such as the raising or lowering of pitch, the removal or alteration of widow's walks, dormers, turrets, balustrades, bargeboards, quarter round, cornices, corbelling, parapets, coping, dentil moldings, brackets, eaves, rafter tails, weather vanes, or lightning rods, the cutting back of roof overhang, and the replacement of historic roofing materials with modern materials that do not replicate the original appearance of the historic property's roof, are not permitted. Specialty roofing materials, such as tile or patterned slate, should never be replaced with composition shingles.
- 7.2 Whenever possible, deteriorated soffits, fascia, moldings, brackets, eaves, rafter tails, cornices, coping, and other important roof components should be repaired. If replacement is necessary, it should be completed using historic materials if possible, and at minimum with equivalent materials that replicate the appearance, configuration, size, scale, and composition of the original historic materials. Underlying roofing components are just as important. For example, tongue-and-groove soffit lumber should never be replaced with plywood, and whenever possible, roof decking should be replaced with similar materials rather than modern materials that are not historically appropriate to the ~~house-building~~.
- 7.3 Dormers and gables should never be added to the principal elevations visible from the street (unless replacing an historic element that had been previously removed) and should be added to rear elevations only when it can be shown that they are appropriate for the building style. The addition of dormers to commercial block buildings is especially inappropriate and should be avoided on all occasions and reversed in cases where this

change has already been made. Skylights, solar panels, power ventilators, and mechanical equipment should always be restricted to the rear portions of the roof or areas behind parapet walls and hidden from the street.

- 7.4 It is important to provide adequate ventilation for roofing components, as excessive heat buildup under the roof can shorten the life of shingles. Ventilators should be located in an inconspicuous place, preferably on rear roof slopes not visible from the street, and low-profile mechanical or power ventilators are best. Soffit vents are permissible as long as the original soffit lumber is retained. On historic properties that already possess ~~louvered~~ louvered, ~~wood~~ gable vents, these should never be covered or replaced with metal louvers.
- 7.5 Tar or roofing cement should never be used as a substitute for properly installed flashing. In most instances, metal flashing is always preferred over asphalt shingle weaving, particularly in valley flashing situations.
- 7.6 Deteriorated roof coverings should be replaced with materials that are compatible with the old in composition, size, texture, pattern, and color once the structural integrity of the roof decking is assured. If at all possible, the use of historic replacement materials for slate, clay tile, terra cotta, pressed metal shingle, and wood shingle roofs is always preferred over new materials. Unless historically appropriate to the building in question, or unless totally obscured by street view by parapets, white or very light shingles-roofing materials are not permitted. Exposed tarpaper rolls are ~~also not~~ never permitted as a roofing material.
- 7.7 Metal gutters, downspouts, and other drainage devices are common on historic properties and should always be retained whenever possible, as they provide important protection for both the roof and the foundation of the property. Built-in gutters that are an important part of the architecture of the building should always be repaired rather than replaced if they become deteriorated. When metal finishes must be replaced because of rust or other deterioration, replace ONLY deteriorated material or detail with new materials that match the previously existing historic material in composition, size, shape, texture, pattern, color, and detail. Replacement gutters and downspouts should never conceal or interfere with architectural trim details. It is not appropriate to paint metal finishes, such as metal downspouts or copper trim, if these items were historically unpainted.
- 7.8 Flashing materials should blend in color with the roof or chimney color. Whenever possible, historically appropriate splash blocks at the base of downspouts should be used to direct water away from the building's foundation.

- 7.9 Roof capping on commercial buildings with original flat roofs was typically made of tile. Modern capping systems that are often used in conjunction with rubber membrane roofs are inappropriate.

8. Entrances, Porches, and Balconies:

One of the most significant and defining characteristics of all architecture is the main or front entrance, including any porches that surround or frame that entrance. In Boone, the front porch in domestic architecture was also often one of the most socially important areas of a home—a place where hosts greeted their guests and where neighbors often exchanged news and stories with one another. Unfortunately, main or front entrances are also often the most altered elements of historic properties. Given that many properties in Boone's commercial historic district were once residences, retaining their original porch and entrance components is especially important for understanding the building's history in context with the district.

Many historic entrances, porches, and balconies contain architectural elements that are essential to communicating the architectural style of the home. Machine-carved balustrades, spindles, brackets, and posts were common in many of Boone's historic homes, but hand-worked elements are also not uncommon. Preserving these details is vital to preserving the appearance and integrity of Boone's historic architecture.

- 8.1 Entrances, porches, and balconies, as used in this section, include front, back, and side porches, mudrooms, porticos, sleeping porches, balconies, pergolas, terraces, widow's walks, and entrances. Components of porches include steps, balustrades, columns, trellises, skirt boards, fascias, brackets, and various ornamental details. Most original porches and balconies were built with a slight pitch away from the residence to facilitate the runoff of rainwater.
- 8.2 Because of their architectural significance, porches, balconies, and entrance configurations—especially those on the front or main elevation—and all of their architectural details (steps, balustrades, brackets, spindlework, columns, roofs, etc.) should be preserved in their original form and detail whenever possible. It is inappropriate to enclose porches and balconies on the front or main elevation for use as an interior space. In addition, the original pitch of porches and balconies should be maintained in order to facilitate the runoff of rainwater and snowmelt. Porches and balconies must be properly maintained and repaired as necessary, as they are exposed to the weather and will deteriorate if regular maintenance is not conducted.
- 8.3 If an historic porch or balcony is completely missing (or if architectural elements associated with the porch or balcony are missing), it should be replaced with a reconstruction based on accurate historic documentation or a new design that is appropriate for the structure in terms of

architectural style, materials, roof form, details, scale, size, and ornamentation. Adding details that are not historical to create a false historical appearance is never appropriate.

- 8.4 If an historic porch or balcony requires repairs, use only materials that are compatible with the original materials associated with the porch or balcony. These replacement materials should match the previously existing historic materials in composition, size, shape, texture, pattern, color, and detail.
- 8.5 Whenever possible, existing infill on historic porches and balconies should be removed and the original appearance of the porch or balcony restored.
- 8.6 Side porches or porches not located on the main elevation may be enclosed for interior space, provided that the proposed design of the enclosure is compatible with the architecture of the historic property. Side porches and porches not located on the main elevation may also be screened, provided that framing for the screening and the screening itself is placed behind columns or balustrades. Any such enclosures or screening should be designed so that they can later be removed without damage to the integrity of the historic structure.



Historic stairways and walkways in front of a property, like this one in front of the Linney House on West King Street, are important historic resources on the landscape of properties in historic districts. They should be maintained and preserved whenever possible. Photo courtesy of Eric Plaag, 2013.

- 8.7 Original porch steps should always be retained. If repair or replacement of porch step materials is necessary, the design, configuration, dimensions, and materials should match the original as closely as possible. In addition, historic stairways and walkways in front of a building—even though not technically part of the building's architecture—are nevertheless an important part of the landscape that accompanies the property and often inform the architectural style and patterns of the property. These elements

should always be retained and repaired with appropriate materials whenever possible.

- 8.8 Decks may be added on the rear elevation of a historic property, provided their addition does not require the removal of large, healthy trees, and their design is compatible in scale with the historic property and district. They should always be designed and installed in such a manner that they may be removed without damage to the historic building. Removal of historic building materials to facilitate the installation of a deck is never acceptable.
- 8.9 Vegetative screening should be employed to obscure the visibility of decks from the street. The underside of decks should also employ latticework or vegetative screening to incorporate the deck element into the general whole of the property in question.
- 8.10 Floor coverings, such as artificial turf, indoor/outdoor carpeting, linoleum, and other similar materials (aside from a small doormat near an entrance) should never be installed on porch, balcony, or deck floors, as these materials can trap water and damage the historic architectural elements below.

9. *Paint and Paint Color:*

For most of Boone's downtown historic commercial properties, which typically were made of masonry and rarely painted, determining historic paint colors, except on trim, ornamentation, windows, original stucco walls, or other architectural details, is usually not a problem. For Boone's downtown properties that were once residences, though, paint color is an issue. Determining the original colors associated with historic properties, especially those built before World War II, is very difficult because of the rarity of color photography during the pre-World War II period. While color chronology tests can help to determine original paint colors (contact the State Historic Preservation Office for assistance), this process is difficult, sometimes inconclusive, and often expensive.

Instead, the architectural style of a building can often be a guide to historic colors. Victorian domestic architecture, especially Queen Anne style homes—often known colloquially as “painted ladies”—were usually painted in a variety of bold, contrasting colors that might seem gaudy to modern eyes. By contrast, Depression-era homeowners often relied on basic white paint or whitewashing, as it was believed that houses painted white would sell more quickly; as a result, more traditional or historic paint colors may have been covered up through these practices.

The Town of Boone UDO, Section , regulates the colors used in commercial properties throughout Boone. Application of new paint, to buildings in the historic district must conform with this UDO Section , unless historic precedence for use of a

nonconforming color can be demonstrated through historic images or color chronology testing. ~~While the Boone Historic Preservation Commission does not regulate paint colors per se,~~ Property owners are advised to seek assistance from the HPC and/or the State Historic Preservation Office when considering paint schemes for historic properties. Beyond this, some general guidelines are applied by the HPC when considering paint in relation to historic properties.

- 9.1 It is NOT appropriate to apply paint or other coatings to unpainted wall materials and surfaces/finishes that were historically left unpainted, including masonry, stonework, wood shingles, stained wood surfaces, and metal.
- 9.2 It is NOT appropriate to use abrasive techniques for cleaning or removing paint from exterior walls and trim, such as sandblasting, high-pressure waterblasting, or other methods that may damage the exterior materials surface. In general, old paint should not be removed unless there is a compelling reason to do so, such as revealing an obscured architectural detail or correcting a severe peeling or cracking problem in existing paint.
- 9.3 Select paint colors that are appropriate for the building's architectural style and that are complementary to neighboring buildings. In general, color should function as a method of contrasting among different materials and architectural elements that make up the housebuilding. Contrasting colors that accent architectural details and entrances are discouraged, except in those cases where this design element was common to the historic architectural style of an existing historic property and there is historic precedent for such accenting. ~~Typically, trimwork—including window and door casings and surrounds, soffits, fascia, and other elements—is often painted with a contrasting or lower value hue than the weatherboard or siding, especially on Victorian-era properties. Wood shingles are usually stained a dark color and often darker than any associated wood siding.~~
- 9.4 Wooden porch steps should always be painted to match the color of a wooden porch floor.

10. Utilities and Energy Retrofit:

Updating utilities and energy systems in historic properties is a common and natural event in the life of a building. As technology improves and environmentally friendly mechanical systems become available, many property owners will desire to improve the efficiency of their historic properties. The Boone HPC encourages the installation, rehabilitation, or replacement of mechanical systems—in compliance with local building codes and utility company standards—that will improve the overall efficiency of those properties. That said, these mechanical systems, when installed in or on an historic property, must comply with certain essential guidelines.

- 10.1 Install utilities and mechanical equipment in areas and spaces that will require the least possible alteration to the plan, materials, and appearance of the building. Installation at the rear of the structure, if feasible, is preferred.
- 10.2 It is NOT appropriate to locate mechanical equipment farther forward on the property than the midpoint of the primary structure.
- 10.3 Ductwork, piping, fuel tanks, plumbing vents, solar collectors, and satellite dishes should not be visible from the street. Equipment that can be seen from the street should be screened with shrubbery or fencing.
- 10.4 If an interior location is not feasible, place utilities and mechanical equipment in inconspicuous locations and/or conceal with architectural elements such as downspouts.
- 10.5 The location of solar collectors or solar panels should be aligned on the building's roof in the direction of greatest effectiveness with a minimized view of such equipment from the primary façade of the structure.

11. Accessibility, Health, and Safety Considerations:

Modern building codes and/or the needs of the people who own, shop, work, and live in historic properties often mean that a variety of accessibility and safety elements must be installed in those properties. Careful planning insures that the integrity of historic properties can be maintained in spite of the addition of these non-historic elements.

- 11.1 New exterior fire escapes are not permitted on historic properties unless more adequate exit facilities cannot be provided. If they must be installed, fire escapes generally should be located at the rear of the building and never along an exposed elevation.
- 11.2 Introducing items such as wheelchair ramps, fire exits, and fire stairs without damaging the character of a historic structure requires careful planning. Owners should introduce fire exits, stairs, landings, and ramps on rear or inconspicuous side locations. If access ramps must be installed in a manner that makes them visible from the public right-of-way, they should be constructed in a manner that makes them as simple and compact as possible and limits their projection from the building.
- 11.3 Construct fire exits, stairs, landings, and ramps in such a manner that they do not damage or significantly obscure historical materials and features. Such additions should be designed to be complementary to the architectural style, materials, scale, and function of the historic property.

- 11.4 Whenever possible, existing exterior fire escapes and stairways that are not original to historic properties should be relocated from front or exposed elevations to a rear or unexposed elevation.

12. Additional Guidelines on Artificial Materials:

While most of Boone's downtown historic properties were built using traditional materials, over the years, some properties have been covered with aluminum, vinyl, asbestos, or other non-traditional materials. Due to the loss of both historic character and original materials inherent in the application of such substitute materials, the damage caused during installation, and the potential for undetected insect infestation and moisture damage, the practice is not acceptable for a historic property.

- 12.1 The removal of previously installed substitute siding is strongly encouraged.
- 12.2 Previously installed vinyl windows and snap-in muntins are examples of inappropriate replacements for wood windows and should also be removed and replaced with more historically appropriate materials whenever possible.
- 12.3 Fake stone in all of its forms is inappropriate, as are "contemporary" bonding techniques, including the "stacked stone" design. Faux brick and roughcasting are also inappropriate.

13. Additions to Existing Buildings:

The completion of an addition to a historic property may improve the functionality of an existing building, but it also has the potential to seriously damage the historic integrity of that property. Generally speaking, additions accordingly should be kept to a minimum and always be reversible without resulting in permanent damage to the essential form and integrity of the historic property.

- 13.1 New additions should be compatible with the original building in scale, placement, proportion, and design, including roof shape, materials, color, location and design of windows and doors, cornice heights, and other design elements. Synthetic materials are strongly discouraged in alterations to existing buildings, and the use of the highest-quality exterior facing materials is encouraged.
- 13.2 New additions should NOT imitate an earlier historic style or architectural period, but they also should not differ from the earlier historical style so much as to be a distraction from or incompatible with the historic design.
- 13.3 Additions should be differentiated from the original by the use of setbacks or other devices. Whenever possible, additions should be located to the

rear or in an inconspicuous location on the side of the original building. They should never be attached to the front of the historic property.

- 13.4 An addition should NOT obscure the original form and proportions of the main building or of other historical additions. Do not add fanciful decorative elements and colors that are out of place or not in keeping with the historic context of the district and/or an individual historic property. Additions such as rooftop penthouses or additional stories should NOT be constructed unless there is documented historic evidence to justify the change.
- 13.5 Additions should be constructed on a smaller scale than the historic structure and not overpower it.
- 13.6 Construction should be carried out in a manner that avoids removal or loss of historic materials and damage or destruction of significant original architectural features.
- 13.7 Construction should impact the exterior walls of the original building as minimally as possible using existing door and window openings for connecting the addition to the original building.
- 13.8 Historically, most of Boone's downtown commercial buildings had flat roofs. Walls should not appear to terminate at flat roofs. Instead, flat roofs should be concealed from view by using historically appropriate pitched roof features, parapets, or a mixture thereof. Where only one elevation has this condition, the parapet or other feature will continue four feet along the adjacent elevation. The minimum slope for pitched roofs is four feet vertically to every twelve feet horizontally. Where a parapet intersects with a pitched roof element, there shall be no apparent breaks in the parapet wall.
- 13.9 Residential roof types are discouraged, except in historic properties that were originally residences or historic commercial properties that historically featured a residential roof type.

14. *New Construction of Commercial Buildings within Historic Districts:*

It is inevitable that new buildings will be constructed within existing historic districts. The intention of these design guidelines is not to prevent such changes but to ensure that new construction is compatible with and complementary to the integrity and architectural character of Boone's historic districts. While new buildings should not attempt to replicate existing historic properties, they should mesh with and support the historic design principles of the district in which they are built. These guidelines are intended to preserve the integrity of Boone's historic areas while also encouraging sensitive and appropriate new construction.

- 14.1 New construction within historic districts should not seek to duplicate historic buildings in the district or mimic their appearance. That said, new construction should strive to be sensitive to and compatible with the character-defining features of an existing historic district. Thus, new construction should employ architectural design that reflects its current time, place, use, and culture, provided that this design is compatible with the character of the historic district.
- 14.2 New construction should incorporate the predominant materials existing in surrounding historic buildings when possible. Synthetic materials are strongly discouraged in new construction, and the use of the highest-quality exterior facing materials is encouraged.
- 14.3 Design, height, massing, and proportions of new buildings should complement and be compatible with the dimensions of neighboring buildings with similar character and style. Roofs, fenestration, and materials should be compatible with surrounding buildings. Traditional separations between storefronts and upper facades should be maintained and consistent with those existing in adjacent or nearby buildings. Vertical divisions maintain the feeling of traditional building widths and should be maintained. New buildings generally should align with adjacent buildings facing on the same street and conform to existing setbacks from the street. The primary façade and main building entry shall face the primary public way.
- 14.4 Combining lots is not preferred in Boone, as it disrupts the historical town planning system.
- 14.5 The appropriateness of the site for a new construction project will be evaluated based upon its compatibility with the district context in terms of setback, spacing, orientation, topography, height, and landscaping. New buildings should have setbacks, orientation, lot coverage, and spacing that align with existing historic properties and comply with the provisions of the Town UDO.
- 14.6 New construction should respect the existing topography and vegetation on the site. Large-scale grading to level or otherwise dramatically alter the natural slope of a lot is destructive to the historic landscape and is not appropriate. Whenever possible, existing trees and historic landscape features should be incorporated into the design for a new property. If large trees must be removed, they should be replaced with trees similar in type and species. During construction, any mature tree that will not be removed should be protected with appropriate fencing around the tree's canopy area that will eliminate construction parking, material storage, and concrete washout that could harm the mature tree.

- 14.7 The appropriateness of a proposed new building will be evaluated based on compatibility in terms of scale, height, form, massing, materials, openings, roof pitch, roof type, and other details with the district context.
- 14.8 Incorporate architectural elements and details into new construction that provide human scale, such as porches and trim. Do not add fanciful decorative elements and colors that are out of place or not in keeping with the historic context of the district and/or adjacent historic properties.
- 14.9 Oversized and monumental scale architecture is not appropriate, and the overall height and width of the new buildings should be compatible with neighboring structures and Town UDO requirements.
- 14.10 Design new buildings using exterior materials typical of historic buildings in the district, including brick, wood, and stone.
- 14.11 It is NOT appropriate in new construction to use contemporary substitute materials such as vinyl or aluminum siding or artificial stacked stone in place of traditional materials.
- 14.12 Historically, most of Boone's downtown commercial buildings had flat roofs. Residential roof types are discouraged. Roof planes should be hidden from view on the façade, and rooflines should be decorated using historic decorative details, using historic photographs and/or neighboring buildings as a guide. Walls should not appear to terminate at flat roofs. Instead, flat roofs should be concealed from view by using historically appropriate pitched roof features, parapets, or a mixture thereof. Where only one elevation has this condition, the parapet or other feature will continue four feet along the adjacent elevation. The minimum slope for pitched roofs is four feet vertically to every twelve feet horizontally. Where a parapet intersects with a pitched roof element, there shall be no apparent breaks in the parapet wall.

15. Height, Width, Spacing, and Setback Requirements:

For details on building height, width, spacing, and setback requirements for commercial structures in the Town of Boone, please consult the Town of Boone UDO. Generally speaking, building spacing in historic districts shall maintain consistency with the spacing between surrounding structures to the greatest degree possible.

***Design Guidelines
for
Historic Streetscapes,
Landscapes, Cemeteries,
Monuments,
and Other Resources***

***Design Guidelines for Historic Streetscapes,
Landscapes, Cemeteries, Monuments, and Other Resources***

1. Streetscapes:

In contrast to the natural elements around which communities are often organized, historic streetscapes instead represent the built environment that defines the character, context, and components around which a community grows and evolves. Typically, buildings are the most obvious and dominant streetscape features, but this type of landscape includes other elements, including the spaces between buildings, private yards, alleyways and streets, sidewalks and other pedestrian elements, lighting, fences, public benches, retaining walls, monuments, public art, and street signage.

With regard to all streetscapes, the following guidelines should be observed:

- 1.1 The form, scale, and massing of building façades located along public ways should be preserved.
- 1.2 The width, alignment, and configuration of streets, alleys, sidewalks, and walkways within historic districts should be retained and preserved.
- 1.3 The intended sightlines and views of public monuments and public art should be maintained.
- 1.4 Historic streetscape features, including lighting, fences, benches, and signage, should be preserved.
- 1.5 When installing new street and building lighting, select fixtures that complement the height and character of existing streetscape features and surrounding architecture, and that align with the historic context of the property in question. Employ the minimal street lighting levels required for public safety while striving to eliminate light pollution. Whenever possible, lighting should be directed toward the ground, away from surrounding properties, and be shielded from direct view.
- 1.6 All historic streetscape elements between buildings—most particularly road width, grade, crown, swale, curbing, sidewalks, lawns, tree plantings, and setbacks—should be preserved and maintained.
- 1.7 Shared and public open spaces visible from public ways created by private yards, natural settings, and building setbacks should be preserved and maintained.
- 1.8 Historic traffic circulation patterns along sidewalks and roadways, including dual or one-way designations, should be preserved and maintained whenever possible.

- 1.9 Existing historic property lines, block patterns, setbacks, and other land divisions—both natural and created—should be maintained.
- 1.10 When necessary, prune or remove and replace trees that threaten public safety, utilities, or property. When considering new plantings near existing utilities, select historically appropriate species that will not interfere with the utility when they reach mature height.
- 1.11 Historic street paving and sidewalk materials, as well as historic curbing, should be retained and preserved, using salvaged or historically compatible materials when repairs are necessary. If historic materials cannot be found, substitute materials may be used, provided they replicate the durability, color, texture, and appearance of the original historic materials.
- 1.12 To prevent damage to historic street paving and sidewalk materials, the Town of Boone and property owners should avoid the application of de-icing salts, relying instead on less intrusive materials such as sand or non-salt chemical de-icers (including calcium magnesium acetate).
- 1.13 New paving and sidewalk materials, especially new accessibility features, should be designed to be consistent with the character and appearance of historic paving materials.
- 1.14 Because historic streetscapes often did not account for the high volume of automobile traffic found today in Boone, parking areas are often a challenge. New parking areas should be as unobtrusive as possible, located behind buildings with access from alleyways and secondary streets rather than main thoroughfares, and screened with historically appropriate natural plantings and/or fences.
- 1.15 Materials, architectural features, and entrance orientations of all historic buildings associated with historic streetscapes should be preserved and maintained. Non-historic architectural features, including promenades, porches, and other additions to buildings intended to create an imagined “mountain village” appearance that is not an accurate reflection of Boone’s historic buildings and streetscapes, should be removed and/or altered to more accurately reflect the context and history of Boone’s streetscapes. When possible, public-private partnerships, including programs like the Main Street Façade Grant program, should be utilized to restore historic streetscape features.
- 1.16 Historic accessory structures, such as garages, sheds, and other outbuildings, should be preserved and maintained in situ. Deteriorating buildings should be repaired using salvaged materials that match existing

ones. When repair of accessory structures is not possible, only those accessory structures for which there is sufficient historic documentation should be reconstructed using materials and configurations similar to the original structure.

- 1.17 New accessory structures should be complementary to the scale, form, materials, and details of surrounding historic buildings, but built in such a way that they do not convey a false sense of historic association. New structures should be located at the rear of historic properties so that they do not intrude upon the historic streetscape.
- 1.18 Property owners and the Town of Boone should protect, encourage, and replace as necessary all street plantings that are in keeping with the historic context of the streetscape and for which there are historic precedents.

2. Lots and Street Frontages:

- 2.1 No lot may be created that is so narrow or otherwise so irregularly shaped that it would be impractical to construct on it a building that could satisfy applicable setback requirements for the district.
- 2.2 Where a lot fronts two (2) or more streets, the minimum lot width requirement shall be considered met if the lot width at the building line from any one of such streets meets the minimum lot width requirement.
- 2.3 No lot created after the effective date of Article XII Section 202 of the Town of Boone UDO **[what is this date? Put it here.]** shall be entitled to a variance from any building setback requirement.
- 2.4 The minimum width of the frontage of a lot on a street shall be eighty (80) percent of the minimum lot width required for the lot. Easement areas shall be excluded from this requirement.
- 2.5 Where a lot fronts two (2) or more streets, the minimum street frontage width requirements shall be considered met if the frontage along any one of such streets meets the minimum street frontage width requirements.
- 2.6 Where a lot fronts on a turning circle of a cul-de-sac or at a point of a street where the radius of the curvature of the right-of-way is less than ninety (90) feet, the minimum street frontage width requirement shall not apply.

3. Landscapes and Ecologically Sensitive Areas:

Boone has a number of inconspicuous but nevertheless historic landscape features in its jurisdiction, ranging from the open meadows surrounding the Doris Church House on Junaluska Rd. to the densely wooded lot adjacent to the Rivers House at Rivers St. and Moretz Dr. Because the demands of expanding development rarely stop to consider the importance of these kinds of landscape features and their links to Boone's history, it is essential that the Town of Boone have a comprehensive set of guidelines for the treatment of these valuable historic resources.

Landscape features, regardless of whether they consist of formally planned, human-constructed gardens or naturally evolving woodlands and meadows in the community, are essential to maintaining and preserving the character, aesthetic appeal, and history of the Town of Boone. Evaluating and preserving the integrity of such existing features and their historical significance requires documentation with historic images, maps, and other data. As with architecture, the preservation and restoration of historic landscape features is always preferred over elimination or replacement, but when the integrity of an existing feature is seriously compromised, new features should be designed to be compatible with the historic context of the vicinity and simultaneously identifiable as a new feature rather than as an attempt to recreate the old.

Some of these historic landscapes are essential to understanding the settlement patterns of our community. As the Town of Boone and the educational institution now known as Appalachian State University grew rapidly during the early twentieth century, for example, the landscape along Boone Creek evolved rapidly from its pastoral origins. While much of this historic landscape to the north of Rivers St. has been compromised by modern development, especially in relationship to the University, pockets still remain. Among these are the warehouse district positioned directly along the north side of the creek, south of Howard St. from just west of South Water St. to the vicinity of Appalachian St. While this may seem an unlikely example of an historic landscape, the wholesale removal of these buildings and the burial of Boone Creek underground—which has occurred in many other areas of Boone along Boone Creek and other tributaries—would erase this natural resource and the settlement patterns associated with it from Boone's tangible past.

It is important to maintain landscaping details that enhance the character of historic districts. Additions to landscaping such as fences, lighting, garden art, and streetscape furniture should be in accordance with the surrounding environment. The purpose of the landscaping guidelines is to regulate the planting and preservation of landscape material; to promote the general health, safety, and welfare of the community; to facilitate the creation of an attractive environment; to protect property values; to further the urban design and economic development of the community; and to encourage skilled installation and continued maintenance of all plant materials.



Keeping historic landscapes and waterways open, rather than burying them under concrete, not only preserves the history of Boone but also prevents and/or minimizes the effects of flooding and other environmental problems. Photo courtesy of Eric Plaag, 2013.

Regarding ecologically sensitive areas and natural areas, the Town of Boone has seen dramatic development over the past fifty years, much of which has adversely impacted

the stream corridors flowing through town as well as once-forested and open areas in the community. As a result, the remaining ecologically sensitive and natural environments within the Town's limits are valuable resources, especially in the context of the Town's urban environment. Contrary to the public perception when the occasional flooding rainstorm visits Boone, these areas actually help slow and filter rainwater and runoff, improve air and water quality, provide natural habitat, and offer aesthetic contributions to the community. In addition, some of these natural areas offer essential clues to the settlement history of Boone and the ways in which its natural resources have been utilized for the better part of two centuries.

Accordingly, the following guidelines should be followed in an effort to maintain these vital resources:

- 3.1 Maintain mature street trees. When removal or replacement is warranted, replace with historically appropriate, indigenous cultivars that will thrive at the site and that will achieve a similar canopy and street edge definition at maturity.
- 3.2 Use plant materials that are indigenous to the historic districts. New plant material should complement those found on the site and in historic districts.
- 3.3 Retain and maintain landscape elements that contribute to the character of the historic districts such as mature trees and hedge rows, grassy lawns, foundation plantings, paving materials, found covers, fountains, sanctuary, outbuildings and gardens.
- 3.4 Keep the location of new landscape features consistent with the location of similar elements in historic districts.
- 3.5 It is inappropriate to introduce contemporary plant edging materials such as exposed landscape timbers in primary and secondary areas of visual concern.
- 3.6 Maintain the relationship between building mass and open space that exists on the block or streetscape. Property owners should preserve the historic spatial arrangements and land-use patterns within the Town of Boone as they have changed over time, and they should strive to protect character-defining elements of both constructed and natural landforms, including the topography and open spaces surrounding historic buildings and landscape features.
- 3.7 Locate additions and new construction, if possible, in areas that do not necessitate the removal of mature plantings or cause the disruption of the established rhythm of building mass and open space. New construction should not interrupt or obstruct significant views and sight lines within

defined historic districts, and existing intrusions within defined historic districts should either be removed or screened with plantings.

- 3.8 Property owners should maintain historic views to and from buildings, especially the facades of these buildings. Use outbuildings, public art, statuary, and fountains as focal points in public and private spaces. Avoid placing such elements in areas that will obscure historic buildings or their architectural features. Due to the subjectivity involved in the evaluation of art, the HPC shall only consider the appropriateness of the location of the art in reviewing applications for Certificates of Appropriateness.
- 3.9 Development of new and existing developed parcels should be regulated to minimize impacts on ecologically sensitive areas.
- 3.10 The Town of Boone and its residents should prioritize the uncovering and restoration of natural stream corridors through town, and new development that impedes, obscures, or covers these stream corridors is not appropriate.
- 3.11 Natural landforms and outcroppings, trees, plantings, and other natural features in ecologically sensitive areas should be preserved, protected, and maintained using ecologically approved methods.
- 3.12 Property owners should maintain no-mow zones along stream corridors.
- 3.13 In cooperation with property owners within and bordering historic landscapes and ecologically sensitive areas, the Town of Boone will encourage historically appropriate tree plantings of indigenous species, especially within parks and along stream corridors; maintain appropriate recreational trails through ecologically sensitive areas and public parks in order to increase public awareness of and participation in the preservation of these areas and to discourage the misuse of these areas; and monitor the condition of trees and other plantings within natural areas, public parks, and along streetscapes to track and prevent the encroachment of diseases and pests.

4. Fences and Garden Walls:

- 4.1 Every development shall provide sufficient landscape so that neighboring properties are shielded from adverse external effects on that development and the development is shielded from the negative impacts of adjacent uses such as parking lots.
- 4.2 To ensure that landscape materials do not constitute a traffic hazard, a sight triangle ten (10) feet by seventy (70) feet will be observed at all intersections of driveways/streets with adjacent streets. Required street

trees shall be planted outside of the sight triangle area. Shrubs planted within sight distance triangles shall be of a type with a maximum mature height of twenty-four (24) inches. For detailed descriptions of screening regulations, see the Town of Boone UDO.

- 4.3 Preserve historic fences and garden walls. Preservation requires continual maintenance and repair. A sound paint surface is essential to maintaining and protecting wooden and iron fences. On wooden fences, seal all joinery to avoid moisture damage. To prevent rust and corrosion on iron fences, clean surfaces with a wire brush to remove all loose paint and rust, then prime immediately with high quality metal primer before the finish coat is applied. Corrosion will occur whenever metal is left unpainted. Brick and masonry walls are vulnerable to uneven ground settling and mortar failure due to weather exposure and vegetation. Resist the tendency to allow plants such as ivy to grow on brick walls as the plants will trap moisture and cause deterioration.
- 4.4 Retain and preserve all character-defining features of historic fences and walls including gates, decorative pickets, finials, and hardware.
- 4.5 Repair rather than replace historic fence and wall materials. If replacement is necessary, replace only those sections in need of replacement. Match the original in composition, height, scale, proportion, color, texture, material and design.
- 4.6 Design new fences that are compatible with the associated building, site, and streetscape in terms of composition, height, scale, proportion, color texture, material and design. Fences and walls based on historic designs are encouraged. New designs that meet the aforementioned criteria are also acceptable.
- 4.7 Use fences or walls in a manner that is historically appropriate such as for demarcating property lines and screening private areas from the public right-of-way.
- 4.8 Use walls and hedgerows in the downtown area to screen parking lots. A masonry wall or single species evergreen hedge will maintain the sense of an "edge" to the streetscape in a similar manner as a building. The peripheral screen will also hide wheels, bumpers, and paving, thereby eliminating the undesirable aspects of the automobile while at the same time, not jeopardizing safety.
- 4.9 Avoid the use of utilitarian fences in primary areas of visual concern.

5. Garages and Accessory Buildings:

- 5.1 Original structures should be retained and preserved if at all possible.
- 5.2 Construct new garages and accessory buildings that are compatible with historic outbuildings in the district in terms of roof form, materials, size, scale proportion and details.
- 5.3 Garages and outbuildings should ALWAYS be located to the rear or side yards and traditional locations in relation to the main residential building.
- 5.4 If it is necessary to replace a historic outbuilding, replace it with a design based on documentary evidence of the original outbuilding, or with a new design similar in form, scale, size, materials and detail as other buildings in the district. Design and construction of the new structure shall be in proportion with other outbuildings of its type within the historic districts.
- 5.5 It is inappropriate to introduce gazebos to primary or secondary AVC without documentary evidence to support their existence in the district during the period of significance. If constructed in the tertiary AVC, gazebos should not be visible from the public right-of-way and must meet the other guidelines for outbuildings and accessory buildings.
- 5.6 It is inappropriate to introduce features and details to an outbuilding that will create a false sense of historic development. For example, it would be inappropriate to add Art Deco features using historic materials to a newly constructed accessory building, as doing so might inappropriately suggest that the accessory building was constructed during the 1930s.
- 5.7 Consult the Town of Boone UDO for setback requirements and lot coverage limitations for all accessory buildings. As a general rule, no accessory building may be further forward to the street setback line than the front-most point of the principal structure.

6. Driveways and Off-Street Parking:

- 6.1 Retain historic driveway configuration and materials whenever possible.
- 6.2 Construct new driveways to conform to the configuration, width, location, and materials of existing driveways.
- 6.3 Locate new driveways and off-street parking areas in residential neighborhoods in tertiary areas. If this is not possible, driveways should be placed in the least conspicuous area of the lot.
- 6.4 Discourage additional curb-cuts, new driveways, or drive-thrus in the commercial area of the historic districts.

- 6.5 It is inappropriate to pave large off-street parking areas that occupy the majority (more than 50%) of the rear yard so that the residential character of the site is severely compromised or lost.
- 6.6 It is inappropriate to demolish contributing buildings or outbuildings to create new parking areas.
- 6.7 It is inappropriate to destroy mature plantings to create new parking areas. Incorporate said plantings into the design and provide for their protection.
- 6.8 Incorporate trees, shrubbery, fencing, or other landscape devices around the periphery and within parking areas.
- 6.9 Utilize a low evergreen hedge or masonry wall, not to exceed 36" in height, along the street frontage of all parking lots. This landscape element will screen automobile wheels, bumpers, and paving, thereby eliminating the harshest aspects of the automobile without compromising surveillance and safety.
- 6.10 Discourage parking lots on corners, as this creates large voids in the streetscape.
- 6.11 Follow the guidelines for exterior lighting in illuminating parking areas.
- 6.12 Design lighting levels for safety. Avoid spilling light onto adjacent properties.

7. Exterior Lighting:

- 7.1 Select lighting that is compatible with the building, site, height and character of existing streetscape features, and the surrounding architecture, and that aligns with the historic context of the property in question, in terms of design, materials, use, size, scale, location, and level and angle of illumination.
- 7.2 Avoid placing fixtures in areas that will obscure or damage character-defining architectural or landscape features.
- 7.3 It is inappropriate to replace original light fixtures when they exist. If no evidence of fixtures is present, select unobtrusive light fixtures that are compatible with the building and site and do not disrupt adjacent properties. Use a white light source.
- 7.4 Employ minimal lighting levels required for public safety while striving to

eliminate light pollution. Whenever possible, lighting should be directed toward the ground, away from surrounding properties, and be shielded from direct view.

- 7.5 Locate lighting sources in strategic locations on the building or landscape to create a subtle and inviting ambience.
- 7.6 Avoid removal of historic light fixtures that would alter the historic character and integrity of a property.
- 7.7 All public streets, sidewalks, and other common areas or facilities in subdivisions created after the effective date of Section 261 of Article XV of the Town of Boone UDO **[WHAT IS THIS DATE???)** shall be sufficiently illuminated to ensure the security of property and the safety of persons using streets, sidewalks, and other common areas or facilities.
- 7.8 All entrances and exits in substantial buildings used for nonresidential purposes and in two-family or multifamily developments containing more than four (4) dwelling units shall be adequately lighted to ensure the safety of persons and the security of the buildings.
- 7.9 Lighting within any lot that unnecessarily illuminates any other lot and substantially interferes with the use or enjoyment of such other lot is prohibited. Lighting unnecessarily illuminates another lot if it clearly exceeds the standards set forth in the Town of Boone UDO.
- 7.10 Screen from view ground-mounted accent or spotlights. Such lights should not highlight non-target structures, signs, or premises.
- 7.11 See the Signage guidelines for information on illumination of signs.

8. Signage:

- 8.1 No signs shall be located in or overhang any right-of-way, including alleys and sidewalks, except for government signs. All signs shall be set back a minimum of one (1) foot from the right-of-way.
- 8.2 No signs shall create any vision obstructions onto a public right-of-way, alley, sidewalk, adjacent drive, or private drive entering onto a street. Signs or floodlights erected or placed in such a manner as to cause glare that impairs driver vision on a roadway or causes a nuisance to adjacent property as defined in N.C. General Statute 136-32.2 are also prohibited.
- 8.3 Freestanding signs must be placed in a landscape area that is at least three (3) feet in width and at least the length of the greatest dimension of

the sign. Curbing, railroad ties, bricks, fencing, and/or other suitable vehicular barrier shall enclose the landscaped area.

- 8.4 Attached signs shall not project higher than the building soffit or eave height and shall not extend beyond the edge of any wall or other surface to which they are mounted (this does not refer to projecting signs).
- 8.5 The area of a sign shall be measured according to the following rules as applicable:
- o In the case of freestanding, projecting, canopy, or marquee signs, area consists of the entire surface area on which copy could be placed. The supporting structure or bracing of a sign shall not be counted as a part of the sign area unless such structure or bracing is made part of the sign's message. Where a sign has two (2) display faces back to back, the area of only one face shall be considered as the sign area. When a sign has more than one display face, all areas that can be viewed simultaneously shall be considered the sign area. All signs are limited to two (2) faces.
 - o In the case of a sign (or other freestanding, projecting, canopy, or marquee) whose message is fabricated together with the background that borders or frames the message, sign area shall be the total area of the entire background.
 - o In the case of a sign (other than freestanding, projecting, canopy, or marquee) whose message is applied to a background that provides no border or frame, sign area shall be computed by continuous rectilinear lines, or a circle or an eclipse enclosing the extreme limits of the letters, writing, representation, emblem, or other display, together with any material or color forming an integral part of the background of the display used to differentiate the sign from the backdrop or structure against which it is placed.
- 8.6 All freestanding signs shall follow the following criteria:
- o No freestanding sign shall be placed less than forty (40) feet from another freestanding sign.
 - o Freestanding signs shall not be located in satellite parcels of real estate.
 - o All freestanding signs, support structures, and required landscaping areas shall be at least one (1) foot from any right-of-way or easement.
- 8.7 Interior lighting for signs, where permitted, shall not exceed eleven (11) watts per bulb (the standard industry size). In the case of the use of

exterior lighting by floodlights, such lights must comply with N.C. General Statute 136.32.2.

- 8.8 Awning, canopy, projecting, and suspended signs may be no less than eight feet at their lowest point above any sidewalk.
- 8.9 All signs must be placed in accordance with the regulations contained in the Town of Boone UDO.

9. Cemeteries and Monuments:

Boone was home to mountain settlers and Native Americans long before it evolved into the small town and university hub that it is today. Historically, these people, like later town residents, buried their dead within or along the boundaries of their communities as they were understood in their time. As a result, Boone is now home to a number of historic cemeteries, family graveyards, and individual burial plots—some not clearly identified by above-ground markers and monuments—that now sit in the midst of the most bustling portions of the community. One such example is the cemetery located near Howard and Brown Streets on the northeast fringe of the university campus. Development around the site has created stability problems for the cemetery itself, and the lack of a defined maintenance plan for the site has resulted in questions about ownership of the plot and the best practices for preserving and maintaining this crucial resource for understanding Boone's history.

In addition, over the arc of Boone's history, several monuments have been erected to the memory of significant residents or events in the community. Responsibility for ownership and maintenance of these resources has not always been clear, resulting in unfortunate and often problematic disagreements about the best practices for handling these resources. One such example is the Daniel Boone Monument presently located on Town property at the west end and on the south side of Rivers Street. While this monument remains significant to the Town's history and is presently stabilized, past practices have resulted in the loss of many of the materials and some of the integrity of the original monument.

Accordingly, in order to protect, preserve, and maintain these often overlooked but important cultural resources located on both public and private property, both the Town of Boone and private property owners should:

- 9.1 Preserve, protect, and maintain the existing historic landforms, topography, and landscape features—including fences, walkways, gates, trees and other plantings, memorials, monuments, and markers—associated with these resources.
- 9.2 Avoid the use of chemical treatments, landscape equipment, fertilizers, and earth-moving devices that are known or likely to result in damage to

the historic fabric of these resources, including grave markers, monuments, headstones, and footstones.

- 9.3 Stabilize leaning or loose grave markers, monuments, headstones, and footstones, and prioritize the appropriate restoration of damaged or missing elements of these resources using standards developed by the Secretary of the Interior for the preservation of such resources.⁴
- 9.4 Before treating any type of masonry, correctly identify the materials and document their condition. During treatment, avoid the use of hard mortars on weathered masonry, and treat corroding metal anchors and fences to avoid further damage to masonry elements.
- 9.5 When vandalism occurs, store broken or damaged elements on site until restoration can occur.
- 9.6 If cleaning of grave markers, monuments, headstones, or footstones is pursued, use the gentlest procedures available and consult a masonry conservator before using any chemical cleaners. Household products, including bleach, lye, ammonia, and similar items, should never be used.⁵

10. Archaeology:

There is evidence of Native American activity in Boone long before the town was established. The Cherokee Indians used the area as hunting grounds before Daniel Boone. Because the Town of Boone is now in its third century of post-Native American settlement, with modern businesses and other uses taking the place of historic land uses and settlement patterns, it should be expected that these new land uses may uncover archaeological resources—either historic or pre-historic—that may be vital to understanding Boone's settlement patterns and history. It must be a priority for the Town of Boone, its residents, and its business owners to identify, protect, and preserve any archaeologically significant resources that might be uncovered during either renovation or new construction. The following section outlines the protocol for preserving artifacts if such an event occurs.

New construction and large-scale renovations typically entail a great deal of site grading and trenching, which have the potential to disrupt artifacts. The following guidelines outline the process for reporting archaeological finds and obtaining the proper permits, licenses, and funds associated with building projects on archaeological sites. Professional technical advice and consultation on archaeology is available from the SHPO or the Office of State Archaeology (OSA). Contact the Town of Boone Planning and Inspections Department for additional contact information.

⁴ More information on the Secretary's Standards can be found in the appendices to this document.

⁵ The North Carolina SHPO maintains a list of qualified preservation consultants and conservators with experience working on North Carolina historic properties.

- 10.1 Landowners should leave known archaeological resources intact and undisturbed whenever possible, and when disturbance is not avoidable, prepare a mitigation plan for the documentation, preservation, and protection of those resources using professional archaeologists who follow accepted standards, methods, and practices for resource mitigation and/or recovery.
- 10.2 Notify the Planning Department, the Boone Cultural Resources Department, the SHPO, and the OSA in the early planning stages of the project to assess the potential for presence of archaeological resources on site. In cases where such potential is identified, owners are required to prepare an archaeological assessment report, including an inspection of the proposed area where subsurface disturbance will occur, as well as a site map showing areas of archaeological sensitivity. In addition, landowners may be required to submit to an archaeological survey of their project area by a professional archaeologist whose qualifications meet the Standards of the Secretary of the Interior for archaeology.
- 10.3 Minimize ground-disturbing activity to reduce the possibility of destroying unknown archaeological resources.
- 10.4 Avoid the use of heavy machinery or equipment on site that may damage archaeological resources. When new archaeological resources are discovered, owners should cease the use of such equipment and stop work on the site immediately until such time that these resources can be documented, preserved, and protected. To begin this documentation, notify the Planning Department, the Cultural Resources Department, the SHPO, and the OSA.

11. Parks and Public Spaces:

The Town of Boone is also home to several parks and public spaces frequently utilized for community events in addition to their intrinsic pastoral and aesthetic purposes. Such locations include the Horn of the West amphitheater area, the Daniel Boone Native Gardens, Strawberry Hill, and the Jones House property, among others. Because these areas see a high volume of public traffic, they create a special challenge for protection, preservation, and maintenance by the Town and, in some cases, their private owners.

The Town of Boone and its residents should observe the following guidelines in managing these important cultural landscapes:

- 11.1 Preserve historic landscape features that are critical to park identity and form, including landforms, topography, roadways, pathways, trails, trees and other plantings (both natural and planned), fences, and other resources.

- 11.2 Preserve and protect significant views into, out of, and within parks and public spaces. Carefully weigh the impact on both visitors and nearby residents and businesses when adding or removing landscape features, trails, walkways, and roadways.
- 11.3 When considering the introduction of public art to any park or streetscape, ensure that the art will not permanently or irreversibly alter the historic character of nearby historically significant buildings or landscapes.
- 11.4 Regularly inspect public art for signs of vandalism and deterioration, and maintain protective coatings. When repairs are necessary, use industry best practices and the gentlest available treatments. If necessary, consult with a conservator to determine the best treatment practices.
- 11.5 Preserve, protect, and maintain significant primary and accessory structures, including pavilions and fountains, that are essential to the identity of the cultural landscape. When planning new accessory structures, including monuments, public art, interpretive signage, memorials, and similar features, weigh their potential impact on historic views associated with the park and the general character and aesthetics of the public space in its historic context. Necessary accessory structures used for service purposes (maintenance sheds, restrooms) should be as unobtrusive as possible and designed to blend into the park's historic landscape.

Guidelines for Relocation and Demolition

Guidelines for Relocation and Demolition

1. Relocation of Buildings:

- 1.1 Choose relocation only as a “last resort” to demolition.
- 1.2 In consultation with the Planning Department, the Cultural Resources Department, and the SHPO, document the original site through drawings and photographs prior to relocating the historic resource.
- 1.3 Work with reputable and experienced contractors to accomplish the relocation.⁶
- 1.4 Plan the relocation route thoroughly. Contact local utility providers and building officials to secure necessary permits and discuss a work plan for the move. Coordinate efforts to ensure minimum delays en route.
- 1.5 Secure the structure to be moved to minimize damage during the move and to deter vandalism.
- 1.6 Choose a site for a relocated building that corresponds proportionally to the size of the structure.
- 1.7 Position the building on the new site in such a manner that its orientation to the street, setback, and lot coverage is compatible to and harmonious with the existing structures on the block to which it is moved.
- 1.8 Ensure that the shape, mass, and scale of the building to be moved conforms to the existing structures on the block to which it is moved.
- 1.9 Move a building as a single unit in order to prevent the unnecessary loss of historic building fabric. Partial or complete disassembly is only acceptable when absolutely necessary.

2. Demolition:

- 2.1 In reviewing a request to demolish a building in the district, the HPC also considers whether the proposed demolition will adversely affect other buildings in the district or the overall character of the district.
- 2.2 When considering demolition of a historic building, the property owner is encouraged to work closely with the HPC in reviewing all alternatives prior to this course of action.

⁶ The North Carolina SHPO maintains a list of qualified preservation consultants and building movers with experience working on North Carolina historic properties.

- 2.3 An application for a Certificate of Appropriateness (COA) authorizing the relocation, demolition, or destruction of a designated landmark or a building, structure, or site within the district may not be denied except if the State Historic Preservation Officer determines that the structure has statewide significance as defined in the criteria of the National Register of Historic Places. This decision may be overturned in instances where the HPC finds that the owner would suffer extreme hardship or be permanently deprived of all beneficial use or return by virtue of the denial.
- 2.4 The effective date of such a certificate may be delayed up to 365 days from the date of approval. This period shall be reduced by the HPC where it finds that the owner would suffer extreme hardship or be permanently deprived of all beneficial use of or return from such property by virtue of the delay.
- 2.5 If the HPC has voted to recommend designation of a property as a landmark or designation of an area as a district, and final designation has not yet been made by the Town Council, the demolition or destruction of any building, site, or structure located on the property of the proposed landmark or in the proposed district may be delayed by the HPC for a period of up to 180 days or until the Town Council takes final action on the designation, whichever occurs first.

Bibliography

- Akers, Donna G. *Boone*. Charleston, SC: Arcadia, 2003. Print.
- Akers, Donna G. & Brian Lambeth. *Watauga County*. Charleston, SC: Arcadia, 2008. Print.
- Center for Historic Architecture & Design. *Delaware City Historic Design Standards*. University of Delaware for the town of Delaware City. Website, PDF. <http://www.delawarecity.delaware.gov/hpc/histdistr/clintonstdesign.pdf>
- Bisher, Catherine W., Southern, Michael T. and Jennifer F. Martin. *A Guide to the Historic Architecture of Western North Carolina*. Chapel Hill, NC: The University of North Carolina Press, 1999. Print.
- Burlington (NC) Historic Preservation Commission. *Design Review Manual*. Burlington, NC: Burlington Historic Preservation Commission, n.d. Website, PDF. Accessed 2013. <http://www.ci.burlington.nc.us/index.aspx?NID=543>.
- Commission for Historical and Architectural Planning. *Baltimore City Historic Preservation Procedures and Design Guidelines*. Baltimore: Baltimore City Department of Planning, 2012. Website, PDF. <http://www.baltimorecity.gov/Portals/0/agencies/chap/public%20downloads/illustrated%20Baltimore%20City%20Historic%20Preservation%20Procedures%20and%20Design%20Guidelines.pdf>.
- Hendersonville (NC) Historic Preservation Commission. *Design Guidelines*. Hendersonville, NC: Hendersonville Historic Preservation Commission, 2010. Website, PDF. http://www.hendersonvillehpc.org/coa-process/guidelines/index_html/?searchterm=design%20guidelines.
- Montford Historic District Design Review Guidelines. Asheville, NC: City of Asheville, 2010. Website, PDF. <http://www.ashevilenc.gov/Portals/0/citydocuments/economicdevelopment/montfordguidelines2010FORWEB.pdf>.
- National Alliance of Preservation Commissions. *The Alliance Review*. Athens, Georgia. September/October 2009. Newsletter.
- North Carolina State Historic Preservation Office & Preservation North Carolina. *Handbook for Historic Preservation Commissions in North Carolina*. Raleigh, NC. Website, PDF. <http://www.hpo.ncdcr.gov/handbook.pdf>
- Pezzoni, J. D., and Tony N. VanWinkle. *The Architectural History of Watauga County, North Carolina*. Durham, NC: BW&A Books, 2009. Print.

APPENDICES

Schmickle, William E. *The Politics of Historic Districts: A Primer for Grassroots Preservation*. Lanham, MD: AltaMira Press, 2007. Print.

Sekula, Greg. *City of New Bern Historic District Guidelines & Handbook*. 2009. Website, PDF. <http://www.newbern-nc.org/PI/docs/Historic%20District%20Guidelines%20and%20Handbook.pdf>

Sheperherdstown, WV *Historic District Design Guidelines*. 2010. Website, PDF. <http://www.shepherdstown.us/uploads/77/98/7798af8371b8250d8db1a08638e339be/HistoricGuidelines-HLC-approved.pdf>

Tyler, Norman, Ted Ligibel, and Ilene R. Tyler. *Historic Preservation: An Introduction to Its History, Principles, and Practice*. New York: W.W. Norton & Co, 2009. Print.

Note: Portions of the City of Raleigh historic design guidelines were also consulted for this project.

Glossary of Architectural Terms

Glossary of Architectural Terms

Adaptive Reuse - The process of converting a building to a use other than that for which it was designed, e.g. changing a house into an office.

Alkyd Resin Paint - A common modern paint using alkyd (one group of thermoplastic synthetic resins) as a vehicle for the pigment; often confused with oil paint.

Aluminum Siding - Sheets of exterior architectural covering, usually with a colored finish, fabricated of aluminum to approximate the appearance of wooden siding. Aluminum siding was developed in the early 1940s and became increasingly common in the 1950s and the 1960s.

Amenity - A building, object, area, or landscape feature that makes an aesthetic contribution to environment rather than one that is purely utilitarian.

Arcade - A series of arches supported on piers or columns attached to or detached from a wall.

Arch - A structure formed of wedge-shaped stones, bricks, or other objects laid so as to maintain one another firmly in position. A rounded arch generally represents classical or Romanesque influence whereas a pointed arch denotes Gothic influences.

Architrave - The lowest part of an entablature, sometimes used by itself as a casing for a window or door.

Art Deco - A style of decorative arts and architecture popular in the 1920s and 1930s, characterized by its use of geometric, angular forms; also referred to as Moderne or Art Moderne.

Asbestos Siding - Dense, rigid board containing a high proportion of asbestos fibers bonded with portland cement; resistant to fire, flame, or weathering and having a low resistance to heat flow. It is usually applied as large overlapping shingles. Asbestos siding was applied to many buildings in the 1950s.

Ashlar - A style of stonework consisting of individual stones that are shaped and tooled to have even faces and square edges.

Asphalt Shingle - A shingle manufactured from saturated construction felts (rag, asbestos, or fiberglass) coated with asphalt and finished with mineral granules on the side exposed to the weather.

Asphalt Siding - Siding manufactured from saturated construction felts (rag, asbestos, or fiberglass) coated with asphalt and finished with mineral granules on the side exposed to the weather. It sometimes displays designs seeking to imitate brick or stone. Asphalt siding was applied to many buildings in the 1950s.

Attic Ventilator - In houses, a screened or louvered opening, sometimes in decorative shapes, located in gables or soffits. Victorian styles sometimes feature sheet soffits or metal ventilators mounted on the roof ridge above the attic.

Awning - A rooflike covering of canvas, often adjustable, over a window, a door, etc., to provide protection against the sun, rain, and wind. Aluminum awnings were developed in the 1950s.

Balustrade - A low barrier formed of balusters, or uprights, supporting a railing.

Band (Band Course, Bandmold, Belt) - Flat trim running horizontally in the wall to denote a division in the wall plane or a change in level.

Bargeboard (also Vergeboard) - A wooden member, usually decorative, suspended from and following the slope of a gable roof. Bargeboards are used on buildings inspired by Gothic forms.

Bay - An opening or division along the face of a structure. For example, a wall with a door and two windows is three bays wide. A bay can also be a projection of a room or facade having windows.

Beltcourse - A projecting course of bricks or other material forming a narrow horizontal strip across the wall of a building, usually to delineate the line between stories, also referred to as a string course.

Beveled Glass - Glass panes whose edges are ground and polished at a slight angle so that patterns are created when panes are set adjacent to one another.

Board and Batten - A method of covering exterior walls using vertical boards, with narrow strips of wood or battens used to cover the joints between boards.

Bond - The pattern in which bricks are laid.

Bracket - A divide, either ornamental, structural, or both, set under a projecting element, such as the eaves of a house.

Bulkhead - The panels below the display windows on a commercial storefront.

Bungalow Style - An early 20th century architectural style that grew out of the Arts and Crafts movement of the 19th century. Its basic characteristics are long, low profiles; overhanging, bracketed eaves; wide engaged porches with square, squat brick piers supporting wood posts; and informal interior arrangements.

Buttress - A vertical mass of masonry projecting from or built against a wall to give additional strength at the point of maximum stress. Sometimes wooden buttresses are

added to frame Gothic Revival-style buildings as decorative, but not supporting features.

Capital - The topmost member, usually decorated or molded, of a column or pilaster.

Cararra Glass - Pigmented structural glass developed and popularized in the early 20th century for facing Art Deco and Art Modern-style commercial buildings.

Casing - The exposed trim molding, framing, or lining around a door or a window; may be either flat or molded.

Cast Iron - Iron that has been shaped by being melted and cast in a mold.

Caulking - A resilient mastic compound, often having a silicone, bituminous, or rubber base; used to seal cracks, fill joints, prevent leakage, and/or provide waterproofing.

Cementitious Board - A material composed of cement, sand, and cellulose fiber. First introduced in the early twentieth century as a substitute for slate. Today cementitious board has a variety of uses including exterior siding and roofing.*

Center-Hall Plan - A plan in which the hall or passage extends through the center of a house and is flanked by two or more rooms.

Certificate of Appropriateness - A document awarded by a preservation commission or architectural re-view board allowing an applicant to proceed with a proposed alteration, demolition, or new construction in a designated historic area or site, following a determination of the proposal's suitability according to applicable criteria.

Certified Historic Structure - For the purpose of the federal preservation tax incentives, any structure subject to depreciation as defined by the Internal Revenue Code that is listed individually on the National Register of Historic Places or located in a registered historic district and certified by the secretary of the interior as being of historic significance to the district.

Certified Rehabilitation - Any rehabilitation of a certified historic structure that the Secretary of the Interior has determined is consistent with the historical character of the property or the district in which the property is located.

Chalking - The formation of a powder surface condition from the disintegration of a binder or an elastomer in a paint coating; caused by weathering or an otherwise destructive environment.

Chamfer - A beveled edge or corner.

Chamfered Post - A square post with the edges of its corners cut away or beveled.

Checking - Small cracks in a film of paint or varnish that do not completely penetrate to the previous coat; the cracks are in a pattern roughly similar to a checkerboard.

Clapboard - Horizontal wooden boards, tapered at the upper end and laid so as to cover a portion of a similar board underneath and to be covered by a similar one above. The exposed face of clapboard is usually less than 6 inches wide. This was common outer face in the nineteenth and early twentieth century buildings.

Classical - Embodying or based on the principles and forms of Greek and Roman architecture.

Clerestory - Windows located relatively high in a wall that often tend to form a continuous band. This was a feature of many Gothic cathedrals and was later adapted to many of the Revival styles found here.

Clipped Gable - A gable the peak of which is truncated for decorative effect; often the roof overhangs the missing peak.

Colonial Revival Style - Late 19th and early 20th century style that combines features of Classical and Colonial architecture.

Colonnade - A small-scale column, generally employed as a decorative element on mantels, overmantels, and porticoes.

Column - A vertical shaft or pillar that supports or appears to support a load.

Common Bond - A method of laying brick wherein one course of headers is laid for every three, five, or seven courses of stretchers.

Composition Board - A building board, usually intended to resemble clapboard, fabricated from wood or paper fabric under pressure and at an elevated temperature, usually with a binder.

Coping - The cap or the top course of a masonry wall.

Corbel - A projection (or building out) from a masonry wall, sometimes to support a load and sometimes for decorative effect.

Corner Block - A square piece, either plain or decorated that forms a corner of a window or door surround.

Corner Boards - Vertical boards nailed on the external corners of frame buildings to provide a method of finishing and joining the ends of the weatherboards.

Cornice - The lowest point of any predominant molded and projecting horizontal member that crowns an architectural composition, such as a wall near the roofline or the

top of the parapet wall. Said cornice, from which the line is determined, shall not exceed three feet. (This definition is consistent with the definitions found in the New Bern Land Use Ordinance Article XXI Section 15-413)

Cresting - Ornamental ironwork, often highly decorative, used to embellish the ridge of a gable roof or the curb or upper cornice of a mansard roof.

Crossette - A lateral projection of the head of the molded architrave or surround of a door, window, mantel, or paneled overmantel; also know as an "ear" or "dog-ear".

Crown Molding - The upper molding of a cornice, often serving to cap or crown the vertical facing or fascia of a boxed cornice. Also, the term is frequently given to the molding used to decorate the joints between walls and a ceiling.

Crenellation - Alternating indentations and raised sections of a parapet, creating a toothlike profile some-times known at a battlement. Crenellation is a detail found most commonly in the Gothic Revival style.

Cultural Resource - A building, structure, district, site, object, or document, that is of significance in American History, architecture, archeology, or culture.

Cupola - A small structure, usually polygonal, built on top of a roof or tower, mostly for ornamental purposes.

Deck - An uncovered porch, usually at the rear of a building; popular in modern residential design.

Demolition by Neglect - The destruction of a building through abandonment or lack of maintenance.

Dentil - Small, closely spaced blocks, often toothlike, used as an ornamental element of a classical cornice.

Design Guidelines - Criteria developed by preservation commissions and architectural review boards to identify design concerns in an area and to help property owners ensure that rehabilitation and new construction respect the character of designated buildings or districts.

Design Review - The process of ascertaining whether modifications to historic and other structures, set-tings, and districts meet standards of appropriateness established by a governing or advisory review board.

Dogtrot Plan - A plan in which two pens with their own chimneys separated by an open center passage.

Dormer - A structure containing a window (or windows) that projects through a pitched roof.

Doric Order - A classical order characterized by simple unadorned capitals supporting a frieze of vertically grooved tablets or triglyphs set at intervals.

Dormer Window - An upright window, set in a sloping roof, with vertical sides and front, usually with a gable, shed, or hip roof.

Double-Hung Window - A window with two sashes that open and close by sliding up and down in a cased frame.

Double-Pile House - A center-hall plan house that is two rooms deep on each side of the hall.

Double-Shoulder Chimney - An exterior chimney the sides of which angle inward to form shoulders twice as it ascends from the base to the cap.

Downspout - A vertical pipe, often of sheet metal, used to conduct water from a roof drain or gutter to the ground or cistern.

Dressed - Descriptive of stone, brick, or lumber that has been prepared, shaped, or finished by cutting, planing, rubbing, or sanding one or more of its faces.

Eave - The part of a sloping roof that projects beyond the wall.

Eclectic or Eclecticism - A method of design in architecture in which elements from a variety of stylistic sources are selected and combined in new and original ways.

Elevation - A drawing showing the vertical elements of a building, either exterior or interior, as a direct projection to a vertical plane.

Ell - A secondary wing or extension of a building, often a rear addition, positioned at right angles to the principal mass.

Eminent Domain - The power of a government to acquire private property for public benefit after payment of just compensation to the owner.

Enabling Legislation - Federal or state laws that authorize governing bodies within their jurisdictions to enact particular measures or delegate powers such as enactment of local landmarks and historic district ordinances, zoning, and taxation.

Engaged Porch - A porch the roof of which is continuous structurally with that of the main section of the building.

English Bond - A method of laying brick wherein one course is laid with stretchers and the next with headers, thus bonding the double thickness of brick together and forming a high-strength bond of alternating courses of stretchers and headers.

Entablature - The horizontal part of a Classical order of architecture, usually positioned above columns or the frieze; the uppermost element is the cornice.

Escutcheon - A protective plate, sometimes decorated, surrounding, the keyhole of a door, a light switch, or similar device.

Etched Glass - Glass whose surface has been cut away with a strong acid or by abrasive action into a decorative pattern.

Extended Use - Any process that increases the useful life of an old building, e.g. adaptive use or continued use.

Exterior End Chimney - A chimney located outside the walls of a house, usually against the gable end of a building.

Fabric - The physical material of a building, structure, or city, connoting an interweaving of component parts.

Facade - The face or front of a building.

Fanlight - A semicircular window, usually above a door or window, with radiating muntins suggesting a fan.

Fascia - A flat board with a vertical face that forms the trim along the edge of a flat roof, or along the horizontal, or eave side of a pitched roof. The rain gutter is often mounted on it.

Fluting - Shallow, concave grooves running vertically on the shaft of a column, pilaster or other surface.

Federal Style - The style of architecture popular in America from the Revolution through the early 19th century (in North Carolina from about 1800-1840). The style is characterized by the use of delicate Classical ornament.

Fenestration - The arrangement of windows on a building.

Finial - an ornament, usually turned on a lathe, placed on the apex of an architectural feature such as a gable, turret, or pediment.

Flashing - A thin impervious material placed in construction to prevent water penetration, to provide water drainage, or both, especially between a roof and a wall.

Flemish Bond - A method of laying brick wherein headers and stretchers alternate in each course and, vertically, headers are placed over stretchers to form a bond and give a distinctive cross pattern.

Flush Siding - An exterior wall treatment consisting of closely fitted horizontal boards with joints that are carefully formed to be hidden and flush, giving a very uniform, flat siding appearance.

Foundation - The supporting portion of a structure below the first-floor construction, or below grade, including footings.

French Window - long window reaching to the floor level and opening in two leaves like a pair of doors.

Fretwork - A geometrically meandering strap pattern; a type of ornament consisting of narrow fillet or band that is folded, crossed, and interlaced.

Frieze - The middle portion of a Classical entablature, located above the architrave and below the cornice. The term is usually used to describe the flat, horizontal board located above the weatherboards of most houses.

Gable - The triangular portion of a wall formed or defined by the two sides of a double-sloping roof; often referred to as an "A" roof.

Galvanize - To coat steel or iron with zinc, as, for example, by immersing it in a bath of molten zinc.

Gambrel Roof - A gable roof more or less symmetrical, having four inclined surfaces, the pair meeting at the ridge having a shallower pitch.

Georgian Style - The prevailing style of the eighteenth century in Great Britain and the North American Colonies, so named after George I, George II, and George III. It is derived from Classical, Renaissance, and Baroque forms.

German Siding - Wooden siding with a concave upper edge that fits into a corresponding rabbet in the siding above.

Gingerbread - Thin, curvilinear ornamentation produced with machine powered saws.

Glazed Header - A brick having a glossy, dark coating ranging in color from gray green to almost black, formed on the outer surface through direct exposure to flame and intense heat during the firing process. In Flemish bond brickwork, this glazed surface is often used for decorative effect by laying the brick so that the glazed ends or headers are exposed to form a pattern in the wall.

Glue-Chip Glass - A patterned glass with a surface resembling frost crystals common in turn-of-the-century houses and bungalows.

Gothic Arch - A pointed arch commonly used in Gothic Revival architecture especially churches.

Gothic Revival Style - The nineteenth-century revival of the forms and ornament of medieval/Gothic European architecture, characterized by the use of the pointed arch, buttresses, pinnacles, and other Gothic details in a decorative fashion. The style was popular for church architecture in North Carolina well into the 20th Century.

Greek Revival Style - The mid-19th century revival of the forms and ornamentation of the architecture of ancient Greece.

Gutter - A shallow channel of metal or wood set immediately below or built in along the eaves of a building to catch and carry off rainwater.

Hall-Parlor Plan - A traditional vernacular plan consisting of two principal rooms: a larger "hall," often nearly square, and an adjoining smaller "parlor." In most instances, the hall was entered directly from the outside and had a fireplace centered on the end wall; it was the room where most domestic activities took place. The smaller parlor tended to be used for sleeping.

Harmony—Pleasing agreement of parts in color, size, scale, texture, and materials.

Header - The end of a brick, sometimes glazed.

Hipped Roof - A roof that slopes back equally from each side of a building. A hip roof can have a pyramidal form or have a slight ridge.

Historic district - A geographically definable area with a significant concentration of buildings, structures, sites, spaces, or objects unified by past events, physical development, design, setting, materials, workman-ship, sense of cohesiveness or related historic and aesthetic associations. The significance of a district may be recognized through listing on a local, state, or national landmarks register and may be protected legally through enactment of a local historic district ordinance administered by a historic district board or commission.

House Museum - A museum whose structure itself is of historical or architectural significance and whose interpretation relates primarily to the building's architecture, furnishings, and history.

Human Scale - A combination of qualities in architecture or the landscape that provides an appropriate relationship to human size, enhancing rather than diminishing the importance of people.

Interior End Chimney - A chimney positioned on the interior side of the gable end of a house.

Italianate Style - A revival of elements of Italian Renaissance architecture popular during the mid-and late 19th century, characterized by the presence of broad projecting or overhanging cornices supported by ornate sawn brackets. Other features include the use of arched windows and heavy hoodmolds.

Jamb - The vertical sides of an opening, usually for a door or a window.

Jerkin Head Roof - A roof whose end has been formed into a shape midway between a gable and a hip, resulting in a truncated or "clipped" appearance; sometimes called clipped gable.

Joist - One of a series of parallel timbers or beams, usually set on edge, that span a room from wall to wall to support a floor or ceiling; a beam to which floorboards, ceiling boards, or plaster laths are nailed.

Keystone - The central wedge-shaped stone at the crown of an arch or in the center of a lintel.

Landmarks Register - A listing of buildings, districts, and objects designated for historical, architectural, or other special significance that may carry protection for listed properties.

Landscape - The totality of the built or human-influenced habitat experienced at any one place. Dominant features are topography, plant cover, buildings, or other structures, and their patterns.

Latex Paint - A paint having a latex binder (an emulsion of finely dispersed particles of natural or synthetic rubber or plastic materials in water).

Lattice - A network, often diagonal, of interlocking lath or other thin strips used as screening, especially in the base of a porch.

Light - A pane of glass.

Lintel - A beam of wood or stone that spans an opening; in masonry construction it frequently supports the masonry above the opening.

Lunette - A semicircular opening.

Mansard Roof - A four-sided double-pitch roof characteristic of the Second Empire Style.

Mixed Use - a variety of authorized activities in an area or a building as distinguished from the isolated uses and planned separatism prescribed by many zoning ordinances.

Mildew - A fungus that grows and feeds on paint, cotton and linen fabrics, etc., that are exposed to moisture; causes discoloration and decomposition of the surface.

Modillion - A horizontal bracket, often in the form of a plain block, ornamenting, or sometimes supporting, the underside of the cornice.

Molding - A decorative band having a constant profile or having a pattern in low relief, generally used in cornices or as trim around openings.

Mortar - A mixture of portland cement, lime, putty, and sand in various proportions, used for laying bricks or stones. Until the use of hard portland cement became general, the softer lime-clay or lime-sand mortars and masonry cement were common.

Mortise and Tenon - A joint made by one member having its end cut as a projecting tongue (tenon) that fits exactly into a groove or hole (mortise) in the other member. Once joined in this fashion, the two pieces are often secured by a peg.

Mullion - A vertical member dividing a window area and forming part of the window frame.

Muntin - A molding forming part of the frame of a window sash and holding one side of a pane.

Newel Post - The principal post used to terminate the railing or balustrade of a flight of stairs.

Neoclassical Style- A style of architecture popular during the first half of the twentieth century. Elements draw heavily from Greek Revival and early Classical revival.

Ogee - A double curve formed by the combination of a convex and concave line, similar to an s-shape.

Oil Paint - A paint in which a drying oil, usually linseed oil, is the vehicle for the pigment; rarely used as a house paint since the mid-twentieth century when it was commonly replaced by alkyd resin paints.

Palladian Window - A window design featuring a central arched opening flanked by lower square-headed openings separated from them by columns, pilasters, piers, or narrow vertical panels.

Panel - A portion of a flat surface set off by molding or some other decorative device.

Parapet - A low wall along a roof or terrace, used as decoration or protection.

Patio - An open, outdoor living space adjacent to a building, usually surfaced with stone, tiles, or concrete and at ground level.

Pediment - A crowning element of porticoes, pavilions, doorways, and other architectural features, usually of low triangular form, with a cornice extending across its base and carried up the raking sides; sometimes broken in the center as if to accommodate an ornament; sometimes of segmental, elliptical, or serpentine form.

Pen - A one-room structure, the term is usually used when referring to log buildings. Many dwellings erected by the first settlers of the North Carolina piedmont were single-pen structures. Many of these dwellings were expanded into two-pen houses following the double-pen, saddlebag, or dogtrot plans.

Pilaster - A shallow pier or rectangular column projecting only slightly from or engaged to a wall. Pilasters are usually decorated like columns with a base, shaft, and capital.

Porte Cochere - A projecting porch that provides protection for vehicles and people entering a building; a common feature of the early 20th century Colonial Revival and Bungalow styles.

Portico - A roofed space, open or partly enclosed, often with columns and a pediment, that forms the en-trance and centerpiece of the facade of a building.

Portland Cement - A very hard and strong hydraulic cement (one that hardens under water) made by heating a slurry of clay and limestone in a kiln.

Preservation - Generally, saving old and historic buildings, sites, structures, and objects from destruction or deterioration, and providing for their continued use by means of restoration, rehabilitation, or adaptive use and continued maintenance. The Secretary of Interior's Standards for Rehabilitation defines it as, "the act or process of applying measures to sustain the existing form, integrity, and materials of a historic property. It may include stabilization work, where necessary, as well as ongoing maintenance of the historic building materials".

Preservation Commission - A generic term for an appointed municipal or county board that recommends the designation of and regulates changes to historic districts and landmarks. It may be called a historic district review board or commission, or architectural or design review board.

Primer - A paint applied as a first coat that serves the function of sealing and filling on wood, plaster, and masonry.

Queen Anne Style - A popular late 19th century revival of early 18th century English architecture, characterized by irregularity of plan and massing and a variety of textures.

Quoin - Ornamental blocks of wood, stone, brick, or stucco placed at the corners of a building and projecting slightly from the front of the facade.

Rafters - Structural timbers rising from the plate at the top of a wall to the ridge of the roof and supporting the roof covering.

Raised panels - A portion of a flat surface, as in the panel of a door or wainscoting, that is distinctly set off from the surrounding area by a molding or other device and is raised above the surrounding area.

Rake - Trim members that run parallel to a roof slope and form the finish between the wall and a gable roof extension.

Rehabilitation - "The act or process of returning a property to a state of utility through repair or alteration which makes possible an efficient contemporary use while preserving those portions or features of the property which are significant to its historical, architectural, and cultural values" as defined by the Secretary of Interior's Standards for Rehabilitation.

Renovation - Modernization of an old or historic building that may produce inappropriate alteration or eliminate important features and details.

Repointing - Raking out deteriorated mortar joints and filling into them a surface mortar to repair the joint.

Restoration - "The act or process of accurately recovering the form and details of a property and its setting as it appeared at a particular period of time by means of removal of latter work or by the replacement of missing earlier work" as defined in the Secretary of the Interior's Standards for Rehabilitation.

Returns - Horizontal portions of a cornice that extend part of the way across the gable end of a structure at eave level.

Roofing Tile - A tile for roofing, usually of burnt clay; available in many configurations and types, such as plain tiles, single-lap tiles, and interlocking tiles.

Rusticated Stone - Masonry or wood in which each principal face is rough or highly patterned with a tooled margin.

Saddlebag Plan - A plan in which two single-pen rooms are joined together, separated by a single interior chimney.

Sandblasting - An extremely abrasive method of cleaning brick, masonry, or wood that involves directing high-powered jets of sand against a surface. Sanding, flattening down, rubbing-Smoothing a surface with abrasive paper cloth either by hand or by machine.

Sash - The frame, usually of wood, that holds the pane(s) of glass in a window; may be movable or fixed; may slide in a vertical plane or may be pivotal.

Sawnwork - Ornamentation in cutout planking, formed with a bandsaw. Popular in the 1880s and the 1890s, this decorative detailing is flat.

Second Empire Style - An eclectic style derived from the grand architecture of the French Second Empire of Napoleon III (1852-1870), popularly used in America from the 1860s to the 1880s, especially for public buildings, and characterized by heavy ornament and high mansard roofs with dormers.

Section 106 - The provision of the National Historic Preservation Act of 1966 that requires the head of a federal agency financing or licensing a project to make a determination of the effect of the project or property on or eligible for the National Register of Historic Places. This is the only protection the National Register provides for listed properties.

Segmental Arch - An arch formed on a segment of a circle or an ellipse.

Sense of Place - The sum of the attributes of a locality, neighborhood, or property that give it a unique and distinctive character.

Shed Room - A one-story appendage to a larger structure, covered by a simple shed or sloping roof that "leans" against the principal building mass.

Sheet Metal - A flat, rolled-metal product, rectangular in cross-section and form; when used as roofing material, usually tin- or zinc-plated.

Shingle - A roofing unit of wood, asphalt, slate, tile, or other material cut to stock lengths, widths, and thicknesses; used as an exterior covering on roofs and applied in a overlapping fashion.

Shoulder - The sloping shelf or ledge created on the side of a masonry chimney where the width of the chimney changes.

Shutters - Small wooden louvered or solid panels hinged on the exterior of windows, and sometimes doors, to be operable.

Sidelight - A framed area of fixed glass of one or more panes positioned to either side of a door or window opening.

Sill - A heavy horizontal timber positioned at the bottom of the frame of a wood structure, that rests on top of the foundation; also, the horizontal bottom member of a door or window frame.

Soffit - The exposed undersurface of any overhead component of a building, such as an arch, balcony, beam, cornice, lintel, or vault.

Spindle Frieze - A row of lathe-turned spindles included as the uppermost decorative feature of a gallery or porch below the cornice; also known as an openwork frieze.

Stabilization - "The act or process of applying measures designed to re-establish a weather resistant enclosure and the structural stability of unsafe or deteriorated property while maintaining the essential form as it exists at present," according to the Secretary of Interior's Standards for Rehabilitation.

Street Furniture - Municipal equipment placed along streets including light fixtures, fire hydrants, police and fire call boxes, signs, benches, and kiosks.

Streetscape - The distinguishing character of a particular street is created by its width, degree of curvature, paving materials, design of the street furniture, forms of surrounding buildings, and the presence of vegetation (especially trees) along the curb or sidewalk.

Stretcher - The long face of a brick when laid horizontally.

String Course - A projecting course of bricks or other material forming a narrow horizontal strip across the wall of a building, usually to delineate the line between stories, also referred to as a belt course.

Stucco - An exterior finish, usually textured, composed of portland cement, lime, and sand mixed with water. Older-type stucco may be mixed from softer masonry cement rather than portland cement.

Style - A type of architecture distinguished by special characteristics of structure and ornament and often related in time, also, a general quality of distinctive character.

Surround - The border or casing of a window or door opening, sometimes molded.

Tax Incentive - A tax reduction designed to encourage private investment in historic preservation and re-habilitation projects.

Terneplate - Sheet metal coated with terne metal, which is an alloy of lead containing up to 20 percent tin.

Terra Cotta - A ceramic material, molded decoratively and often glazed, used for facings for buildings or as inset ornament.

Textured Siding - Wood cut in various flat patterns, such as half rounds or scallops, and applied to portions of facades to create a picturesque or romantic look. This

treatment was generally used in Queen Anne-style buildings. Surface textures are often found in diamond, scallop, staggered butt, or composite patterns.

Tongue and Groove - A joinery system in which boards are milled with a tongue on one side and a groove on the other so that they can be tightly joined with a flush surface alignment.

Townscape - The relationship of buildings, shapes, spaces, and textures that give a town or area its distinctive visual character or image.

Trabeated - A method of construction employing posts and lintels; hence, a term used to describe a standard Greek Revival entrance door having a transom and sidelights.

Tracery - An ornamental division of an opening, especially a large window, usually made with wood. Tracery is found in buildings of Gothic influence.

Transom (Over-Door Light) - A narrow horizontal window unit above a door.

Turned - Fashioned on a lathe, as in a baluster, newel, or porch post.

Turret - A small tower, usually corbelled from a corner.

Vernacular - In architecture, as in language, the nonacademic local expressions of a particular region. For example, a vernacular Greek Revival structure may exhibit forms and details that are derived from the principles of formal Classical architecture but are executed by local builders in an individual way that reflects both local or regional needs, tastes, climatic conditions, technology, and craftsmanship.

Victorian - The general term used to describe the wide variety of eclectic revival styles that were introduced in British and American architecture during the reign of Queen Victoria (1837-1901)

Vinyl Siding - Sheets of thermal plastic compound made from chloride or vinyl acetates, as well as some plastics made from styrene and other chemicals, usually fabricated to resemble clapboard.

Visual Pollution - Anything that, because of its placement or intrinsic nature, is offensive to the sense of sight, e.g. garbage dumps.

Vitrolite - Pigmented structural glass developed and popularized in the early 20th century for facing Art Deco and Art Modern-style commercial buildings.

Water Blasting - A cleaning method similar to sandblasting except that water is used as the abrasive. As in sandblasting, high-pressure water jets can damage wood and masonry surfaces.

APPENDICES

Water Table - A belt course differentiating the foundation of a masonry building from its exterior walls.

Weatherboard - Wood siding consisting of overlapping horizontal boards usually thicker at one edge than the other.

Wrought Iron - Iron that is rolled or hammered into shape, never melted.

These terms have been compiled from a variety of sources including Landmark Yellow Pages by the National Trust for Historic Preservation, The Architecture of Wake County, NC by Kelly Lally, and Design Guidelines for Raleigh Historic Districts, Raleigh Historic District Commission, as well as Reid Thomas, Restoration Specialist, Eastern Office, NC SHPO.

Appendices

Appendix A: N.C. General Statutes

North Carolina Enabling Legislation for the Creation of Historic Preservation Commissions by Counties and Municipalities G.S. 160A-400.1-400.14

Note: The following text has been taken from the North Carolina General Assembly General Statutes Web site at <http://www.ncga.state.nc.us/Statutes/Statutes.html>. Complete texts (by full chapters, not sections) of all General Statutes may be downloaded in HTML, PDF, and RTF formats at that site.

160A-400.1. Legislative findings.

The historical heritage of our State is one of our most valued and important assets. The conservation and preservation of historic districts and landmarks stabilize and increase property values in their areas and strengthen the overall economy of the State. This Part authorizes cities and counties of the State within their respective zoning jurisdictions and by means of listing, regulation, and acquisition: (1) To safeguard the heritage of the city or county by preserving any district or landmark therein that embodies important elements of its culture, history, architectural history, or prehistory; and (2) To promote the use and conservation of such district or landmark for the education, pleasure and enrichment of the residents of the city or county and the State as a whole. (1989, c. 706, s. 2.)

160A-400.2. Exercise of powers by counties as well as cities.

The term "municipality" or "municipal" as used in G.S. 160A-400.1 through 160A-400.14 shall be deemed to include the governing board or legislative board of a county, to the end that counties may exercise the same powers as cities with respect to the establishment of historic districts and designation of landmarks. (1989, c. 706, s. 2; 1989 (Reg. Sess., 1990), c. 1024, s. 40.)

160A-400.3. Character of historic district defined.

Historic districts established pursuant to this Part shall consist of areas which are deemed to be of special significance in terms of their history, prehistory, architecture, and/or culture, and to possess integrity of design, setting, materials, feeling, and association. (1989, c. 706, s. 2.)

160A-400.4. Designation of historic districts.

Any municipal governing board may, as part of a zoning or other ordinance enacted or amended pursuant to this Article, designate and from time to time amend one or more historic districts within the area subject to the ordinance. Such ordinance may treat historic districts either as a separate use district classification or as districts which overlay other zoning districts. Where historic districts are designated as separate use districts, the zoning ordinance may include as uses by right or as conditional uses those uses found by the Preservation Commission to have existed during the period sought to be restored or preserved, or to be compatible with the restoration or preservation of the district. No historic district or districts shall be designated until:

(1) An investigation and report describing the significance of the buildings, structures, features, sites or surroundings included in any such proposed district, and a description of the boundaries of such district has been prepared, and (2) The Department of Cultural Resources, acting through the State Historic Preservation Officer or his or her designee, shall have made an analysis of and recommendations concerning such report and description of proposed boundaries. Failure of the department to submit its written analysis and recommendations to the municipal governing board within 30 calendar days after a written request for such analysis has been received by the Department of Cultural Resources shall relieve the municipality of any responsibility for awaiting such analysis, and said board may at any time thereafter take any necessary action to adopt or amend its zoning ordinance.

The municipal governing board may also, in its discretion, refer the report and proposed boundaries to any local preservation commission or other interested body for its recommendations prior to taking action to amend the zoning ordinance. With respect to any changes in the boundaries of such district subsequent to its initial establishment, or the creation of additional districts within the jurisdiction, the investigative studies and reports required by subdivision (1) of this section shall be prepared by the preservation commission, and shall be referred to the local planning agency for its review and comment according to procedures set forth in the zoning ordinance. Changes in the boundaries of an initial district or proposal for additional districts shall also be submitted to the Department of Cultural Resources in accordance with the provisions of subdivision (2) of this section.

On receipt of these reports and recommendations, the municipality may proceed in the same manner as would otherwise be required for the adoption or amendment of any appropriate zoning ordinance provisions. (1989, c. 706, s. 2.)

160A-400.5. Designation of landmarks; adoption of an ordinance; criteria for designation.

Upon complying with G.S. 160A-400.6, the governing board may adopt and from time to time amend or repeal an ordinance designating one or more historic landmarks. No property shall be recommended for designation as a historic landmark unless it is deemed and found by the preservation commission to be of special significance in terms of its historical, prehistorical, architectural, or cultural importance, and to possess integrity of design, setting, workmanship, materials, feeling and/or association.

The ordinance shall describe each property designated in the ordinance, the name or names of the owner or owners of the property, those elements of the property that are integral to its historical, architectural, or prehistorical value, including the land area of the property so designated, and any other information the governing board deems necessary. For each building, structure, site, area, or object so designated as a historic landmark, the ordinance shall require that the waiting period set forth in this Part be observed prior to its demolition. For each designated landmark, the ordinance may also provide for a suit-able sign on the property indicating that the property has been so designated. If the owner consents, the sign shall be placed upon the property. If the

owner objects, the sign shall be placed on a nearby public right-of-way. (1989, c. 706, s. 2.)

160A-400.6. Required landmark designation procedures. As a guide for the identification and evaluation of landmarks, the commission shall undertake, at the earliest possible time and consistent with the resources available to it, an inventory of properties of historical, architectural, prehistorical, and cultural significance within its jurisdiction. Such inventories and any additions or revisions thereof shall be submitted as expeditiously as possible to the Office of Archives and History. No ordinance designating a historic building, structure, site, area or object as a landmark nor any amendment thereto may be adopted, nor may any property be accepted or acquired by a preservation commission or the governing board of a municipality, until all of the following procedural steps have been taken:

(1) The preservation commission shall (i) prepare and adopt rules of procedure, and (ii) prepare and adopt principles and guidelines, not inconsistent with this Part, for altering, restoring, moving, or demolishing properties designated as landmarks.

(2) The preservation commission shall make or cause to be made an investigation and report on the historic, architectural, prehistorical, educational or cultural significance of each building, structure, site, area or object proposed for designation or acquisition. Such investigation or report shall be forwarded to the Office of Archives and History, North Carolina Department of Cultural Resources.

(3) The Department of Cultural Resources, acting through the State Historic Preservation Officer shall either upon request of the department or at the initiative of the preservation commission be given an opportunity to review and comment upon the substance and effect of the designation of any landmark pursuant to this Part. Any comments shall be pro-vided in writing. If the Department does not submit its comments or recommendation in connection with any designation within 30 days following receipt by the Department of the investigation and report of the commission, the commission and any city or county governing board shall be relieved of any responsibility to consider such comments.

(4) The preservation commission and the governing board shall hold a joint public hearing or separate public hearings on the proposed ordinance. Reasonable notice of the time and place thereof shall be given. All meetings of the commission shall be open to the public, in accordance with the North Carolina Open Meetings Law, Chapter 143, Article 33C.

(5) Following the joint public hearing or separate public hearings, the governing board may adopt the ordinance as proposed, adopt the ordinance with any amendments it deems necessary, or reject the proposed ordinance.

(6) Upon adoption of the ordinance, the owners and occupants of each designated landmark shall be given written notification of such designation insofar as reasonable diligence permits. One copy of the ordinance and all amendments thereto shall be filed by the preservation com-mission in the office of the register of deeds of the county in which the landmark or landmarks are located. Each designated landmark shall be indexed according to the name of the owner of the property in the grantee and grantor indexes in the register of deeds office, and the preservation commission shall pay a

reasonable fee for filing and indexing. In the case of any landmark property lying within the zoning jurisdiction of a city, a second copy of the ordinance and all amendments thereto shall be kept on file in the office of the city or town clerk and be made available for public inspection at any reasonable time. A third copy of the ordinance and all amendments thereto shall be given to the city or county building inspector. The fact that a building, structure, site, area or object has been designated a landmark shall be clearly indicated on all tax maps maintained by the county or city for such period as the designation remains in effect. (7) Upon the adoption of the landmarks ordinance or any amendment thereto, it shall be the duty of the preservation commission to give notice thereof to the tax supervisor of the county in which the property is located. The designation and any recorded restrictions upon the property limiting its use for preservation purposes shall be considered by the tax supervisor in appraising it for tax purposes. (1989, c. 706, s. 2.)

160A-400.7. Historic Preservation Commission.

Before it may designate one or more landmarks or historic districts, a municipality shall establish or designate a historic preservation commission. The municipal governing board shall determine the number of the members of the commission, which shall be at least three, and the length of their terms, which shall be no greater than four years. A majority of the members of such a commission shall have demonstrated special interest, experience, or education in history, architecture, archaeology, or related fields. All the members shall reside within the territorial jurisdiction of the municipality as established pursuant to G.S. 160A-360. The commission may appoint advisory bodies and committees as appropriate.

In lieu of establishing a historic preservation commission, a municipality may designate as its historic preservation commission, (i) a separate historic districts commission or a separate historic landmarks commission established pursuant to this Part to deal only with historic districts or landmarks respectively, (ii) a planning agency established pursuant to this Article, or (iii) a community appearance commission established pursuant to Part 7 of this Article. In order for a commission or board other than the preservation commission to be designated, at least three of its members shall have demonstrated special interest, experience, or education in history, architecture, or related fields. At the discretion of the municipality the ordinance may also provide that the preservation commission may exercise within a historic district any or all of the powers of a planning agency or a community appearance commission.

A county and one or more cities in the county may establish or designate a joint preservation commission. If a joint commission is established or designated, the county and cities involved shall determine the residence requirements of members of the joint preservation commission. (1989, c. 706, s. 2.)

160A-400.8. Powers of the Historic Preservation Commission.

A preservation commission established pursuant to this Part may, within the zoning jurisdiction of the municipality:

- (1) Undertake an inventory of properties of historical, prehistorical, architectural, and/or cultural significance;
- (2) Recommend to the municipal governing board areas to be designated by ordinance as "Historic districts"; and individual structures, buildings, sites, areas, or objects to be designated by ordinance as "Landmarks";
- (3) Acquire by any lawful means the fee or any lesser included interest, including options to purchase, to properties within established districts or to any such properties designated as land-marks, to hold, manage, preserve, restore and improve the same, and to exchange or dispose of the property by public or private sale, lease or otherwise, subject to covenants or other legally binding restrictions which will secure appropriate rights of public access and promote the preservation of the property;
- (4) Restore, preserve and operate historic properties;
- (5) Recommend to the governing board that designation of any area as a historic district or part thereof, or designation of any building, structure, site, area, or object as a land-mark, be revoked or removed for cause;
- (6) Conduct an educational program with respect to historic properties and districts within its jurisdiction;
- (7) Cooperate with the State, federal, and local governments in pursuance of the purposes of this Part. The governing board or the commission when authorized by the governing board may contract with the State, or the United States of America, or any agency of either, or with any other organization provided the terms are not inconsistent with State or federal law;
- (8) Enter, solely in performance of its official duties and only at reasonable times, upon private lands for examination or survey thereof. However, no member, employee or agent of the commission may enter any private building or structure without the express consent of the owner or occupant thereof;
- (9) Prepare and recommend the official adoption of a preservation element as part of the municipality's comprehensive plan;
- (10) Review and act upon proposals for alterations, demolitions, or new construction within historic districts, or for the alteration or demolition of designated landmarks, pursuant to this Part; and
- (11) Negotiate at any time with the owner of a building, structure, site, area, or object for its acquisition or its preservation, when such action is reasonably necessary or appropriate. (1989, c. 706, s. 2.)

160A-400.9. Certificate of appropriateness required.

- (a) From and after the designation of a landmark or a historic district, no exterior portion of any building or other structure (including masonry walls, fences, light fixtures, steps and pavement, or other appurtenant features), nor above-ground utility structure nor any type of outdoor advertising sign shall be erected, altered, restored, moved, or demolished on such landmark or within such district until after an application for a certificate of appropriateness as to exterior features has been submitted to and approved by the preservation commission. The municipality shall require such a certificate to be issued by the commission prior to the issuance of a building permit or other permit granted for the purposes of constructing, altering, moving, or demolishing structures, which certificate may be issued subject to reasonable conditions necessary

to carry out the purposes of this Part. A certificate of appropriateness shall be required whether or not a building or other permit is required.

For purposes of this Part, "exterior features" shall include the architectural style, general design, and general arrangement of the exterior of a building or other structure, including the kind and texture of the building material, the size and scale of the building, and the type and style of all windows, doors, light fixtures, signs, and other appurtenant fixtures. In the case of outdoor advertising signs, "exterior features" shall be construed to mean the style, material, size, and location of all such signs. Such "exterior features" may, in the discretion of the local governing board, include historic signs, color, and significant landscape, archaeological, and natural features of the area. Except as provided in (b) below, the commission shall have no jurisdiction over interior arrangement and shall take no action under this section except to prevent the construction, reconstruction, alteration, restoration, moving, or demolition of buildings, structures, appurtenant fixtures, outdoor advertising signs, or other significant features in the district which would be incongruous with the special character of the landmark or district.

(b) Notwithstanding subsection (a) of this section, jurisdiction of the commission over interior spaces shall be limited to specific interior features of architectural, artistic or historical significance in publicly owned landmarks; and of privately owned historic landmarks for which consent for interior review has been given by the owner. Said consent of an owner for interior review shall bind future owners and/or successors in title, provided such consent has been filed in the office of the register of deeds of the county in which the property is located and indexed according to the name of the owner of the property in the grantee and grantor indexes. The landmark designation shall specify the interior features to be reviewed and the specific nature of the commission's jurisdiction over the interior.

(c) Prior to any action to enforce a landmark or historic district ordinance, the commission shall (i) prepare and adopt rules of procedure, and (ii) prepare and adopt principles and guidelines not inconsistent with this Part for new construction, alterations, additions, moving and demolition. The ordinance may provide, subject to prior adoption by the preservation commission of detailed standards, for the review and approval by an administrative official of applications for a certificate of appropriateness or of minor works as defined by ordinance; provided, however, that no application for a certificate of appropriateness may be denied without formal action by the preservation commission. Prior to issuance or denial of a certificate of appropriateness the commission shall take such steps as may be reasonably required in the ordinance and/or rules of procedure to inform the owners of any property likely to be materially affected by the application, and shall give the applicant and such owners an opportunity to be heard. In cases where the commission deems it necessary, it may hold a public hearing concerning the application. All meetings of the commission shall be open to the public, in accordance with the North Carolina Open Meetings Law, Chapter 143, Article 33C.

(d) All applications for certificates of appropriateness shall be reviewed and acted upon within a reasonable time, not to exceed 180 days from the date the application for a certificate of appropriateness is filed, as defined by the ordinance or the commission's rules of procedure. As part of its review procedure, the commission may view the premises and seek the advice of the Division of Archives and History or such other expert advice as it may deem necessary under the circumstances.

(e) An appeal may be taken to the Board of Adjustment from the commission's action in granting or denying any certificate, which appeals (i) may be taken by any aggrieved party, (ii) shall be taken within times prescribed by the preservation commission by general rule, and (iii) shall be in the nature of certiorari. Any appeal from the Board of Adjustment's decision in any such case shall be heard by the superior court of the county in which the municipality is located.

(f) All of the provisions of this Part are hereby made applicable to construction, alteration, moving and demolition by the State of North Carolina, its political subdivisions, agencies and instrumentalities, provided however they shall not apply to interiors of buildings or structures owned by the State of North Carolina. The State and its agencies shall have a right of appeal to the North Carolina Historical Commission or any successor agency assuming its responsibilities under G.S. 121-12(a) from any decision of a local preservation commission. The commission shall render its decision within 30 days from the date that the notice of appeal by the State is received by it. The current edition of the Secretary of the Interior's Standards for Rehabilitation and Guidelines for Rehabilitating Historic Buildings shall be the sole principles and guidelines used in reviewing applications of the State for certificates of appropriateness. The decision of the commission shall be final and binding upon both the State and the preservation commission. (1989, c. 706, s. 2.)

160A-400.10. Conflict with other laws.

Whenever any ordinance adopted pursuant to this Part requires a longer waiting period or imposes other higher standards with respect to a designated historic landmark or district than are established under any other statute, charter provision, or regulation, this Part shall govern. Whenever the provisions of any other statute, charter provision, ordinance or regulation require a longer waiting period or impose other higher standards than are established under this Part, such other statute, charter provision, ordinance or regulation shall govern. (1989, c. 706, s. 2.)

160A-400.11. Remedies.

In case any building, structure, site, area or object designated as a historic landmark or located within a historic district designated pursuant to this Part is about to be demolished whether as the result of deliberate neglect or otherwise, materially altered, remodeled, removed or destroyed, except in compliance with the ordinance or other provisions of this Part, the city or county, the historic preservation commission, or other party aggrieved by such action may institute any appropriate action or proceedings to prevent such unlawful demolition, destruction, material alteration, remodeling or removal, to restrain, correct or abate such violation, or to prevent any illegal act or

conduct with respect to such building, structure, site, area or object. Such remedies shall be in addition to any others authorized by this Chapter for violation of a municipal ordinance. (1989, c. 706, s. 2.)

160A-400.12. Appropriations.

A city or county governing board is authorized to make appropriations to a historic preservation commission established pursuant to this Part in any amount that it may determine necessary for the expenses of the operation of the commission, and may make available any additional amounts necessary for the acquisition, restoration, preservation, operation, and management of historic buildings, structures, sites, areas or objects designated as historic landmarks or within designated historic districts, or of land on which such buildings or structures are located, or to which they may be removed. (1989, c. 706, s. 2.)

160A-400.13. Certain changes not prohibited. Nothing in this Part shall be construed to prevent the ordinary maintenance or repair of any exterior architectural feature in a historic district or of a landmark which does not involve a change in design, material or appearance thereof, nor to prevent the construction, reconstruction, alteration, restoration, moving or demolition of any such feature which the building inspector or similar official shall certify is required by the public safety because of an unsafe or dangerous condition. Nothing in this Part shall be construed to prevent a property owner from making any use of his property that is not prohibited by other law. Nothing in this Part shall be construed to prevent a) the maintenance, or b) in the event of an emergency the immediate restoration, of any existing above-ground utility structure without approval by the preservation commission. (1989, c. 706, s. 2.)

160A-400.14. Delay in demolition of landmarks and buildings within historic district.

(a) An application for a certificate of appropriateness authorizing the relocation, demolition or destruction of a designated landmark or a building, structure or site within the district may not be denied except as provided in subsection (c). However, the effective date of such a certificate may be delayed for a period of up to 365 days from the date of approval. The maximum period of delay authorized by this section shall be reduced by the commission where it finds that the owner would suffer extreme hardship or be permanently deprived of all beneficial use of or return from such property by virtue of the delay. During such period the preservation commission shall negotiate with the owner and with any other parties in an effort to find a means of preserving the building or site. If the preservation commission finds that a building or site within a district has no special significance or value toward maintaining the character of the district, it shall waive all or part of such period and authorize earlier demolition, or removal. If the commission or planning agency has voted to recommend designation of a property as a landmark or designation of an area as a district, and final designation has not been made by the local governing board, the demolition or destruction of any building, site, or structure located on the property of the proposed landmark or in the proposed district may be delayed by the commission or planning agency for a period of up to 180 days or

until the local governing board takes final action on the designation, whichever occurs first.

(b) The governing board of any municipality may enact an ordinance to prevent the demolition by neglect of any designated landmark or any building or structure within an established historic district. Such ordinance shall provide appropriate safeguards to protect property owners from undue economic hardship.

(c) An application for a certificate of appropriateness authorizing the demolition or destruction of a building, site, or structure determined by the State Historic Preservation Officer as having statewide significance as defined in the criteria of the National Register of Historic Places may be denied except where the commission finds that the owner would suffer extreme hardship or be permanently deprived of all beneficial use or return by virtue of the denial. (1989, c. 706, s. 2; 1991, c. 514.)

160A-400.15. Demolition by Neglect to Contributing Structures Outside Historic Districts

Notwithstanding G.S. 160A-400.14 or any other provision of law, the governing board of any municipality may apply its demolition by neglect ordinances to contributing structures located outside the local historic district within an adjacent central business district. The governing board may modify and revise its demolition by neglect ordinances as necessary to implement this section and to further its intent. This section is applicable to any municipality with a population in excess of 100,000, provided such municipality (i) has designated portions of the central business district and its adjacent historic district as an Urban Progress Zone as defined in G.S. 143B-437.09 and (ii) is recognized by the State Historic Preservation Office and the U.S. Department of the Interior as a Certified Local Government in accordance with the National Historic Preservation Act of 1966, as amended (16 U.S.C. 470, et seq.), and the applicable federal regulations (36 C.F.R. Part 61), but is located in a county that has not received the same certification. (2011-367, s. 1.)

Appendix B: Federal Historic Preservation Information

National Park Service

<http://www.cr.nps.gov>

National Register of Historic Places (National Park Service)

<http://www.cr.nps.gov/places.htm>

Certified Local Government Program (National Program)

<http://www.cr.nps.gov/hps/tps/tax/rehabstandards.htm>

Advisory Council for Historic Preservation (Federal Liaison for Programs)

<http://www.achp.gov/>

Federal Preservation Tax Incentives Program

<http://www.cr.nps.gov/hps/tps/tax/index.htm>

The Secretary of Interior's Standards for Rehabilitation

<http://www.cr.nps.gov/hps/tps/tax/rehabstandards.htm>

Illustrated Guidelines for Rehabilitating Historic Buildings

<http://www.cr.nps.gov/hps/tps/tax/rhblindex.htm>

Preservation Briefs-A Series of Informative Pamphlets (Listed Below)

<http://www.cr.nps.gov/hps/tps/briefs/presbhom.htm>

Preservation Brief 01: Assessing Cleaning and Water Repellent Treatments for Historic Masonry Buildings

<http://www.cr.nps.gov/hps/tps/briefs/brief01.htm>

Preservation Brief 02: Repointing Mortar Joints in Historic Masonry Buildings

<http://www.cr.nps.gov/hps/tps/briefs/brief02.htm>

Preservation Brief 03: Conserving Energy in Historic Buildings

<http://www.cr.nps.gov/hps/tps/briefs/brief03.htm>

Preservation Brief 04: Roofing for Historic Buildings

<http://cr.nps.gov/hps/tps/briefs/brief04.htm>

Preservation Brief 05: The Preservation of Historic Adobe Buildings

<http://www.nps.gov/hps/tps/briefs/brief05.htm>

Preservation Brief 06: Dangers of Abrasive Cleaning to Historic Buildings

<http://www.cr.nps.gov/hps/tps/briefs/brief06.htm>

Preservation Brief 07: The Preservation of Historic Glazed Terra Cotta

<http://www.cr.nps.gov/hps/tps/briefs/brief07.htm>

Preservation Brief 08: Aluminum and Vinyl Siding on Historic Buildings: The Appropriateness of Substitute Materials for Resurfacing Historic Wood Frame Buildings

APPENDICES

<http://www.cr.nps.gov/hps/tps/briefs/brief08.htm>

Preservation Brief 09: The Repair of Historic Wooden Windows

<http://www.cr.nps.gov/hps/tps/briefs/brief09.htm>

Preservation Brief 10: Exterior Paint Problems on Historic Woodwork

<http://www.cr.nps.gov/hps/tps/briefs/brief10.htm>

Preservation Brief 11: Rehabilitating Historic Storefronts

<http://www.cr.nps.gov/hps/tps/briefs/brief11.htm>

Preservation Brief 12: The Preservation of Historic Pigmented Structural Glass
(Vitrolite and Carrara Glass)

<http://www.cr.nps.gov/hps/tps/briefs/brief12.htm>

Preservation Brief 13: The Repair and Thermal Upgrading of Historic Steel
Windows

<http://www.cr.nps.gov/hps/tps/briefs/brief13.htm>

Preservation Brief 14: New Exterior Additions to Historic Buildings: Preservation
Concerns

<http://www.cr.nps.gov/hps/tps/briefs/brief14.htm>

Preservation Brief 15: Preservation of Historic Concrete: Problems and General
Approaches

<http://www.cr.nps.gov/hps/tps/briefs/brief15.htm>

Preservation Brief 16: The Use of Substitute Materials on Historic Building
Exteriors

<http://www.cr.nps.gov/hps/tps/briefs/brief16.htm>

Field Code Changed

Preservation Brief 17: Architectural Character—Identifying the Visual Aspects of
Historic Buildings as an Aid to Preserving Their Character

<http://www.cr.nps.gov/hps/tps/briefs/brief17.htm>

Preservation Brief 18: Rehabilitating Interiors in Historic Buildings—Identifying
Character-Defining Elements

<http://www.cr.nps.gov/hps/tps/briefs/brief18.htm>

Preservation Brief 19: The Repair and Replacement of Historic Wooden Shingle
Roofs

<http://www.cr.nps.gov/hps/tps/briefs/brief19.htm>

Preservation Brief 20: The Preservation of Historic Barns

<http://www.cr.nps.gov/hps/tps/briefs/brief20.htm>

Preservation Brief 21: Repairing Historic Flat Plaster—Walls and Ceilings

APPENDICES

<http://www.cr.nps.gov/hps/tps/briefs/brief21.htm>

Preservation Brief 22: The Preservation and Repair of Historic Stucco

<http://www.cr.nps.gov/hps/tps/briefs/brief22.htm>

Preservation Brief 23: Preserving Historic Ornamental Plaster

<http://www.cr.nps.gov/hps/tps/briefs/brief23.htm>

Preservation Brief 24: Heating, Ventilating, and Cooling Historic Buildings:
Problems and Recommended Approaches

<http://www.cr.nps.gov/hps/tps/briefs/brief24.htm>

Preservation Brief 25: The Preservation of Historic Signs

<http://www.cr.nps.gov/hps/tps/briefs/brief25.htm>

Preservation Brief 26: The Preservation and Repair of Historic Log Buildings

<http://www.cr.nps.gov/hps/tps/briefs/brief26.htm>

Preservation Brief 27: The Maintenance and Repair of Architectural Cast Iron

<http://www.cr.nps.gov/hps/tps/briefs/brief27.htm>

Preservation Brief 28: Painting Historic Interiors

<http://www.cr.nps.gov/hps/tps/briefs/brief28.htm>

Preservation Brief 29: The Repair, Replacement, and Maintenance of Historic
Slate Roofs

<http://www.cr.nps.gov/hps/tps/briefs/brief29.htm>

Preservation Brief 30: The Preservation and Repair of Historic Clay Tile Roofs

<http://www.cr.nps.gov/hps/tps/briefs/brief30.htm>

Preservation Brief 31: Mothballing Historic Buildings

<http://www.cr.nps.gov/hps/tps/briefs/brief31.htm>

Preservation Brief 32: Making Historic Properties Accessible

<http://www.cr.nps.gov/hps/tps/briefs/brief32.htm>

Preservation Brief 33: The Preservation and Repair of Historic Stained and
Leaded Glass

<http://www.cr.nps.gov/hps/tps/briefs/brief33.htm>

Preservation Brief 34: Applied Decoration for Historic Interiors: Preserving
Historic Composition Ornament

<http://www.cr.nps.gov/hps/tps/briefs/brief34.htm>

Preservation Brief 35: Understanding Old Buildings: The Process of Architectural
Investigation

<http://www.cr.nps.gov/hps/tps/briefs/brief35.htm>

APPENDICES

Preservation Brief 36: Protecting Cultural Landscapes: Planning, Treatment, and Management of Historic Landscapes

<http://www.cr.nps.gov/hps/tps/briefs/brief36.htm>

Preservation Brief 37: Appropriate Methods of Reducing Lead-Paint Hazards in Historic Housing

<http://www.cr.nps.gov/hps/tps/briefs/brief37.htm>

Preservation Brief 38: Removing Graffiti from Historic Masonry

<http://www.cr.nps.gov/hps/tps/briefs/brief38.htm>

Preservation Brief 39: Holding the Line: Controlling Unwanted Moisture in Historic Buildings

<http://www.cr.nps.gov/hps/tps/briefs/brief39.htm>

Preservation Brief 40: Preserving Historic Ceramic Tile Floors

<http://www.cr.nps.gov/hps/tps/briefs/brief40.htm>

Preservation Brief 41: The Seismic Retrofit of Historic Buildings: Keeping Preservation in the Forefront

<http://www.cr.nps.gov/hps/tps/briefs/brief41.htm>

Preservation Brief 42: The Maintenance, Repair, and Replacement of Historic Cast Stone

<http://www.cr.nps.gov/hps/tps/briefs/brief42.htm>

Preservation Brief 43: The Preparation and Use of Historic Structure Reports

<http://www.cr.nps.gov/hps/tps/briefs/brief43.htm>

Preservation Brief 44: Replacement, and New Design of Awnings

<http://www.cr.nps.gov/hps/tps/briefs/brief44.htm>

Preservation Brief 45: Preserving Historic Wood Porches

<http://www.nps.gov/history/hps/tps/briefs/brief45.htm>

Preservation Brief 46: The Preservation and Reuse of Historic Gas Stations

<http://www.nps.gov/history/hps/tps/briefs/brief46.htm>

Preservation Brief 47: Maintaining the Exterior of Small and Medium Sized Historic Buildings

<http://www.nps.gov/history/hps/tps/briefs/brief47.htm>

Appendix C: The Secretary of the Interior's Standards for the Treatment of Historic Properties

Buildings which are 30 years old or older should be renovated according to the Secretary of the Interior's Standards for Rehabilitation which are as follows:

The Standards are to be applied to specific rehabilitation projects in a reasonable manner, taking into consideration economic and technical feasibility.

- 1) A property shall be used for its historic purpose or be placed in a new use that requires minimal change to the defining characteristics of the building and its site and environment.
- 2) The historic character of a property shall be retained and preserved. The removal of historic materials or alteration of features and spaces that characterize a property shall be avoided.
- 3) Each property shall be recognized as a physical record of its time, place, and use. Changes that create a false sense of historical development such as adding conjectural features or architectural elements from other buildings shall not be undertaken.
- 4) Most properties change over time; those changes that have acquired historic significance in their own right shall be retained and preserved.
- 5) Distinctive features, finishes and construction techniques or examples of craftsmanship that characterize a property shall be preserved.
- 6) Deteriorated historic features shall be repaired rather than replaced. Where the severity of deterioration requires replacement of a distinctive feature, the new feature shall match the old design, color, texture and other visual qualities and, where possible, materials. Replacement of missing features shall be substantiated by documentary, physical or pictorial evidence.
- 7) Chemical or physical treatments, such as sandblasting, that cause damage to historic materials shall not be used. The surface cleaning of structures, if appropriate, shall be undertaken using the gentlest means possible.
- 8) New additions, exterior alterations, or related new construction shall not destroy historic materials that characterize the property. The new work shall be differentiated from preserved. If such resources must be disturbed, mitigation measures shall be undertaken.
- 9) New additions and adjacent or related new construction shall be undertaken in such a manner that if removed in the future, the essential form and integrity of the historic property and its environment would be unimpaired.

Appendix D: DBDA Guidelines for Construction Methods and Materials for Properties within the Municipal Service District

- A. All work must conform to existing building codes and ordinances of the Town of Boone.
- B. Height: Additions or new construction should fall within the range of 10% of mean building height found in the block. Buildings at the ends of blocks should be similar in height to buildings on adjoining corners.
- C. Width: Additions or new construction should respect the primacy of established width by designing rhythmic division of the façade to maintain existing progression.
- D. Setback: Additions or new construction should maintain the uniform setback of buildings and align with façades.
- E. Proportion of Openings: New construction, additions, and remodeling of existing buildings should maintain established proportion and spacing of window openings.
- F. Materials: The quality of building materials varies widely, and it is the quality of the finish materials and its application that determines compatibility. Use the highest quality facing materials possible. Materials that are compatible in quality, color, texture, finish and dimension to those existing in the project area are encouraged.
- G. Roof Forms: Gabled and/or residential roofs are not appropriate; historically downtown buildings have flat roofs. The roof plane should be hidden from view on the front façade. Decoration of the roofline by use of special materials, forms, or decorative details, using examples from surrounding buildings as a guide is encouraged.
- H. Color: Colors should coordinate with neighboring buildings. The more intense hues of a color are discouraged. The use of more than one vivid color per building is discouraged. The use of colors that are disharmonious with other colors used on the buildings or found on the adjacent buildings is discouraged. Contrasting colors which accent architectural details and entrances are encouraged.
- I. Cornices: (1) The retention and repair of existing cornices is strongly encouraged wherever possible. (2) The re-creation of missing cornices should be done with care, using surrounding existing cornices as a guide.
- J. Side Elevations and Rear Façades: (1) Side elevations and rear façades should be treated as a main façade. (2) The development of rear or side entrances with appropriate design is encouraged.
- K. Signs: Sign guidelines for the central business district have been developed to prevent visual clutter in the downtown areas and to improve the general visual quality of downtown. Individuality and creativity are encouraged within the

framework of quality. Signs should relate to each other through quality, not necessarily through uniform materials, lettering, or size. All signs are controlled by the Sign Ordinance of the Town of Boone. Qualities of good signs are as listed below: (1) Good signs have the following characteristics: legibility, clarity, attractiveness, durability, and good placement.

(2) Most buildings are designed with a defined sign space. The location of signs of appropriate size in these spaces is strongly encouraged. (3) Plastic, illuminated signs are strongly discouraged. Consider attached, flat, or hanging signs lit with outside indirect lighting. (4) All signs must meet zoning and building code requirements. (5) Hanging or projecting signs or hand-painted window signs of good quality are encouraged.

- L. Awnings: (1) Awnings should relate to the shape and color of the building. (2) Metal canopies are strongly discouraged, except when historically appropriate, and their removal and replacement with fabric awnings is strongly encouraged. If installed or retained, they should be designed or treated in a manner that adds to the visual quality of the building. (3) All awnings must meet zoning and building code requirements.

Appendix E: Sample Façade Incentive Grant Application
(FOR MORE INFORMATION AND TO DOWNLOAD THE OFFICIAL
APPLICATION VISIT: <http://downtownboonenc.com/default/assets/File/2014-2015%20DBDA%20Facade%20Grant.pdf>

Downtown Boone Development Association
Façade Improvement Grant Program
Fiscal Year 2014-2015

Parcel Pin ID # for proposed improvement _____
 Building Address _____
 City _____ State _____ Zip code _____

Applicant Information

Applicant's Name _____
 Best contact phone # _____ Email _____
 Mailing Address _____
 City _____ State _____ Zip code _____
 Business Name _____
 Business Address _____
 City _____ State _____ Zip code _____
 Business phone # _____ Email _____
 Length of time at this location _____
 Length of time remaining on lease (if applicable) _____
 Date of next lease renewal (if applicable) _____

Owner(s) Information (if different from applicant)

Name(s) _____
 Best contact # _____ Email _____
 Mailing Address _____
 City: _____ State: _____ Zip code: _____

Description of Project (attach additional documents and pages if needed)

Total Estimated Cost of Improvement(s) \$ _____

Signature of Applicant _____ Date _____

Please Check:

- ☐ I have attached project plans and design information.
- ☐ I have attached sample paint colors or other materials (if applicable).
- ☐ I have attached photograph(s) of the existing condition of the area on the property where the proposed work is to be completed.
- ☐ I have attached copies of cost estimates for the project.
- ☐ I have attached the signed **Owner Disclosure** form.
- ☐ I have attached a signed copy of the Secretary of the Interior's Standards for Rehabilitation indicating that I have read and understand the program's requirements and intend to follow the guidelines.
- ☐ I understand that work completed prior to the processing and subsequent approval of this application will not be considered eligible for funding.
- ☐ I acknowledge that the DBDA is not liable to the applicant, owner, or any third party for any obligation or claims of any nature growing out of, arising from, or otherwise related to the project or application undertaken by the applicant and/or owner including liens of any kind. I hereby waive and hold harmless the DBDA, the Town of Boone, their officials, employees, agents, and volunteers for any such claims.

Signature of Applicant _____

Date _____

Owner/Agent Disclosure Form

I, _____ (*property owner*) hereby grant _____
 (*business owner*) permission to apply for the Façade Improvement Grant (FIG). I understand that
 if _____ (*business owner*) should be awarded monies through the
 FIG program that the building that I, _____ (*property owner*) own
 will undergo a façade renovation as outlined in the attached FIG application, which I have
 reviewed and approve.

_____ (*property owner initials*) I acknowledge that the DBDA is not liable to the applicant,
 owner, or any third party for any obligation or claims of any nature growing out of, arising from, or
 otherwise related to the project or application undertaken by the applicant and/or owner including
 liens of any kind. I hereby waive and hold harmless the DBDA, the Town of Boone, their officials,
 employees, agents, and volunteers for any such claims.

Business Owner: _____
 Best contact phone #: _____
 Signature: _____
 Date: _____

Property Owner: _____
 Best contact phone #: _____
 Signature: _____
 Date: _____

Owners/Agent Disclosure Form

We, _____(property owners) hereby grant _____(business owner) permission to apply for the Façade Improvement Grant (FIG). We understand that if _____(business owner) should be awarded monies through the FIG program that the building we, _____(property owners) own will undergo a façade renovation as outlined in the attached FIG application, which we have reviewed and approve.

_____ (property owner initials) I acknowledge that the DBDA is not liable to the applicant, owner, or any third party for any obligation or claims of any nature growing out of, arising from, or otherwise related to the project or application undertaken by the applicant and/or owner including liens of any kind. I hereby waive and hold harmless the DBDA, the Town of Boone, their officials, employees, agents, and volunteers for any such claims.

Business Owner: _____
Best contact #: _____
Signature: _____
Date: _____

Property Owners: _____
If applicable, Member Manger of LLC : _____
If applicable, President of the Corporation: _____
Best contact # for above person: _____
Signature(s): _____

Date: _____

**BOONE TOWN COUNCIL MEETING
AUGUST 15, 2019**

REQUEST TO HONOR OUR PAST

BY

MARY ETTA MORETZ

BOONE TOWN COUNCIL MEETING

AUGUST 15, 2019

REQUEST TO HONOR OUR PAST

Thank you for allowing me to petition you this evening to recognize an iconic pioneer who helped to tame our beautiful mountain home.

Before I continue with my petition, I would like to thank the Town of Boone for all of the amazing historic preservation work you have done in the past few years. I know that many people have been involved, from the Historic Planning Board to the Watauga Historical Society to the Junaluska Heritage Association and to leaders such as Dr. Eric Plaag and Dr. Bettie Bond.

Because I am part of the history of our area not only because I will celebrate my 77th birthday in a few days, but also because I descended from many of the earliest settlers in our area, those who came from the Plantations of Happy Valley as well as the Greenes who came from the Jersey Settlement in Lexington, NC right after the Revolutionary War bringing their brothers-in-law the Eggers and the Wilsons with them, and the Moretzes who came in the early 1800's from the Hickory

area, and because I have always loved history, I have made it my quest to learn about our past.

There were few settlers west of the crest of the Appalachian Mountains until after the Revolutionary War, and the ones who were here were in danger and were in violation of British Law. The British issued the Proclamation Act of 1763 following the French and Indian War establishing the Proclamation Line at the crest prohibiting settlers from going over the line. Even though they had won the French and Indian War with the help of the Colonists, they absolutely could not afford any more wars, and war they thought they would have with the Indians if settlers crossed the line. This made Colonists angry, and a few did cross the line especially desperate people such as freed or runaway indentured servants. For reference, read The Last of the Mohicans by James Fenimore Cooper, a romanticized version yet full of basic truth. Herders and hunters did cross the line, people such as Benjamin Howard who claimed the entire Boone Valley as his western lands, and his neighbor Daniel Boone, who did not claim ownership but only the right to hunt. Howard's ancestors were the younger sons of royalty, the Dukes of Norfolk, who had settled in Jamestown in hopes of making their fortune. Mathew Howard, who had indentured servants thereby gaining additional land in Virginia, moved to Maryland at the request of his brother-in-law, Lord Baltimore, who was married to his sister. There is a Howard County in Maryland. Benjamin Howard was one of Mathew Howard's

descendants. He eloped with his bosses' daughter, moved to Stokes County and then to what today is in the Wilkes County section of Happy Valley.

There are many native Watauga residents who are descendants of Benjamin Howard and other plantation owners from Happy Valley such as the Councils, the Harmons, the Dulas, the Lenoirs, and the Hortons. Some of them know their lineage, but many more do not.

The iconic Pioneer that I want to tell you about today is an African American slave whose name is Burrell. Although little is known about him, much is known about him considering that he was a slave. When women and minorities are even mentioned in history, we know that something happened that was outstanding.

Burrell was one of Benjamin Howard's slaves. My sources have allowed me to pin down Burrell's life span as being from approximately 1745 to 1845. He was said to be over 100 in 1845 by Colonel James Martin Isbell (1837-1913), the great grandson of Benjamin Howard and who knew Burrell.

Howard himself was born in 1742 in Anne Arundel County, Maryland, and died in 1832 in Wilkes County, so he and Burrell were not only master and slave but also contemporaries. I believe, and will try to find more evidence, that Burrell was named for the slave trader who sold him to Howard.

According to Colonel James Martin Isbell, who was the original source cited as an authority in many local histories, newspaper articles and records, Benjamin Howard, his great grandfather, “owned land near the village of Boone and used to range his stock in the mountains surrounding that picturesque village. He built a cabin of logs in front of what is now the Boys’ Dormitory of the Appalachian Training School for the accommodation of himself and his herders whenever he or they should come from his home on the headwaters of the Yadkin, at Elkville. Among the herders was an African slave named Burrell. When Col. Isbell was a boy, say, about 1845, Burrell was still alive, but was said to have been over 100 years old. He told Col. Isbell that he had billeted [sic] Daniel Boone across the Blue Ridge to the Howard cabin in the first trip Boone ever took across the mountains.”

([https://www.wikitree.com/index.php?title=Isbell-687&public=1# note-2](https://www.wikitree.com/index.php?title=Isbell-687&public=1#note-2))

Daniel Boone and the Howards were not only neighbors but also friends. In fact, Isbell says that Boone often visited with the Howards no doubt sharing in their hospitality. Dr. Ina Van Noppen, a scholar on Boone, told me that Howard is the only person we know about whom Boone visited after he moved to Kentucky. On that visit, he likely reconnected with Burrell, the man who guided him through the passes to the High Country and who shared shelter and sustenance with him.

Dr. Robert L. Isbell, the great-great-grandson of Benjamin Howard, wrote about Burrell in his collected essays, The World of My Childhood (1955), a book about the settlers and plantation owners of the Happy Valley community which follows the Yadkin River into Wilkesboro. He says:

“Uncle Burrell was a slave of my great-great-grandfather Benjamin Howard’s home who later fell into the hands of my great-grandfather, Thomas Isbell, who had married Discretion, Benjamin Howard’s oldest daughter.

“Uncle Burrell lived alone in his cabin and at night had a custom of sitting and watching the stars in their movements, and was looked upon as a weather prophet. He must have seen farther than some the political life of his day, for Aunt Sophia recalls that he would say to her when she was a little girl: ‘You will be free some day [sic], child, but I will never be free.’ Aunt Sophia lived to see his words come true and spent most of her life a free woman....

“Uncle Burrell lived on the Yadkin River in the World of My Childhood at the time when Daniel Boone lived in his cabin a few miles below. When he finally came to the end of his days he was laid to rest under the broad spreading arms of a large black pine tree about 200 yards from the white folks’ graveyard on the same upland that overlooks the delta of Kings Creek and the fertile valley of the Yadkin for two miles, a scene of rare and matchless beauty.

“Two flat stones with round head and shoulders were placed and these stones were always very interesting to me. They remained intact through the long years- a century of them- and during the development at Grandin about 38 years ago, some vandal slyly took them to parts unknown, presumably to the North. They had listened to the soft and mournful requiem signed in the pine above through the long, long nights and guarded with sleepless vigilance their sacred trust until a ruthless hand carried them away.” (pp. 94,95)

There is no doubt in my mind that these words were spoken about a man who was dearly loved and respected. That he actually had burial markers is also remarkable since this was in a time when many white people had so such memorial and certainly not slaves.

Burrell was allowed to live with the Isbells, even though he had been willed to others. Benjamin Howard was in his 80's when he died. Burrell was also an elder. Howard willed Burrell, to my great-great- great grandmother, Mary (Polly) Howard along with his home. He willed slaves to his other children as well, including his daughter who married Jordan Councill, his son-in-law. Why would he will an elderly slave to his daughter Mary rather than to his sons? I believe it was because Burrell was his treasured friend as well as servant. I believe it is possible that Burrell saved his life when the Patriots were chasing him. (This old Tory later became a Patriot.) I feel certain that Howard knew that Mary would

take care of this now elderly servant. Mary in turn left Burrell specifically to her daughter Prudence, not her son, for the same reason. When Prudence married and moved into what today is Ashe County, she no doubt allowed Burrell to remain in Happy Valley with her Aunt Discretion Howard Isbell for his final years and among his own people. The fact that Burrell lived to be over 100 years of age speaks loudly to me that he was cared for, that he was respected and, yes, even loved.

So today, I petition the Boone Town Council, in the name of historic justice, to recognize this iconic pioneer by naming a street for him, placing an historic marker recognizing him as a pioneer, guide, herder, profit and beloved settler of our area, and commissioning a statue of him to stand beside the erroneously named "Boone Cabin" marker which was actually the "Howard Cabin" where he spent so many days guarding the livestock of his master and hosting hunters such as Daniel Boone.

(You may be wondering why Boone is named Boone. The Town Fathers deliberated about the name for the new County Seat. Should it remain Council's Store, should it be named for Howard? They decided upon naming it for Daniel Boone who only hunted here for a few years but who was already a famous man in Europe and America for marketing purposes. Oh, yes, they were in the real estate business way back then!)